

Contd from previous page -

marked. New trees A W Oak 15" dia N 62° 30' W 85 ft.
a W Oak 22" dia N 22° 30' E 47 ft.

✓ SE Cor. Sec. 61. Renewed this corner from the original
B.T. which I chopped open and found the scribe
#11 marks. I set an iron pipe also an oak post 4" x 4" x 40"

✓ 1/4 Cor. bet Secs. 16 & 21

Renewed this corner from the original B.T.s
the Tree N 35° 30' W was alive and standing showing
scars. the tree S 21° 45' W was down and nearly
burned up. the directions and distances checked

I set a 4" x 4" x 40" post and erected a mound

#12 of rock. Marked a new tree ^{A 14" B Oak} S 35° 30' W 110 ft

✓ Cor. to Secs. 15 + 16 + 21 + 22

Set an iron pipe also an oak post from
which the original B.T.s bear as follows

A B. Oak alive and standing S 22° 30' W 42 ft

A Stump showing scribe marks. S 67° 30' E 54 ft

A W Oak. B.T. standing N 56° 45' E 40 ft

A W Oak: N 13 1/2° W 34 ft

✓ 1/4 Cor. bet. 15 + 22.

Renewed this corner from both original
Bearing trees which were alive and standing
both trees show scars and check for direction and

#14 distance. Set an oak post. 4 x 4 x 40 also 1" x 30 iron
pipe and erected Mound of Rock.

✓ 1/4 Cor. bet 21 & 22.

Renewed this corner from the rotted remains
of both original trees which check closely for direction
and distance I set an oak post 4 x 4 x 40" also iron
pipe 1" x 30. from which mark new trees A B Oak 10" dia
#15 S 54° W 64 ft. A B. Oak 10" dia N 30° 1/4 W 16 ft

J. Ware Deputy
May 1921

make
this
corner
to get
wrong

T 26 S 6 R 6 W.

✓ 1/4 Cor. bet Secs 21+28.

I set an oak post 4x4x40" also iron pipe 1"x30" from which I stumped of original B 9 bears S 53 1/4° E 181 1/2 ft. I mag of B 9 bearing scribe marks N 68° 30' W 171 ft.

#16 Marked new trees A. B Oak 16" dia N 68° 30' W 40 ft
A. Dble. W Oak 24" dia South 68.5 ft.

✓ Cor. to Secs 27-28-33-34.

I renewed this corner from one original B 9. ^{714 ft on ground - Cuts for 264 R's.} S 67° 15' E (174 1/2) ft. which is alive and standing and bearing scribe marks also by tie to Meander cor. which I located from one of the Bearing trees. I set an oak post for Sec Cor. also erected a mound of rock.

mark. new trees A W Oak 10" dia N 50° W 47 ft.
#17 A W Oak 10" dia S 38° W 54 ft.

✓ 1/4 Cor. bet. 28-29

I renewed this corner from the original bearing trees both of which were alive and standing I set a 4x4x40" post also an iron pipe 1"x30"

✓ N W Cor. Cl. 42.

I renewed this corner by measurement from Corner. 13.30 Chs South I set a 4x4x40 post also an iron pipe 1 1/2"x30" dia from which B Oak 20" dia N 43° E 338 ft.
" " 14" dia S 40° E 62° ft.

✓ S W Cor. Cl 42 = N E interior L Cor.

I renewed this corner from what I believed to be a stump of the original B 9 which is a stump of B Oak 28" dia Ran S 26° E 57 1/2 ft from stump and set hub from which A. B. Oak 18" dia bearing scare bears S 19° E 129 lbs. instead of 29 lbs. as per field notes. (see over)

note this corner is set wrong

J W Cole Deputy May 1921

#20