

F.C. Traver  
July 15-1920  
Wit. J.C.C. Long  
J.P.D. Wolford

Cor. Secs 11-12-13-14 - Re-established from  
old B.T.s which I remarked and set a  
#1 1" x 30" Iron Pipe for Corner

✓ Cor. Sec. 14-15-22-23 Rest from old stump + one tree, no  
✓ scribe marks visible. Drove I. Pipe. Marked 36 Fir S 63 1/2° W 46' ft  
#2 30" Fir N 18° W 27' ft; 30" Fir S 42 1/2° E 22' ft; 12" Fir East 31 1/2' ft.

✓ Cor. Sec. 15-16-21-22. Rest from one O.B.T. others gone.  
Drove I. Pipe. Marked 24" Hemlock N 18° E 46' ft; 20" Hemlock N 57 1/2° W 24' ft  
#3 36" Fir S 50° W 48 1/2' ft

✓ 1/4 Cor bet 15 and 22. Rest from 1 O.B.T. and one stump.  
#4 Drove I. Pipe. Marked 18" W. Fir S 4 1/2° W 73 1/2' ft; 10" W. Fir N 54° E 27 1/2' ft.

✓ 1/4 Cor bet 15 and 16. Rest set midway bet sec corners to  
North and South: Drove yew wood stake. 14" Fir N 46° E 17 1/2' ft  
#5 14" Fir S 27° E 40' ft at 25° slope. Cor. on steep rocky hill side.

✓ Cor. Sec. 13-14-23-24. Rest from one O.B.T.  
✓ Drove I. Pipe 8" below ground in Prune orchard + 33' ft So. of fence.  
#6 Marked 12" B.O. N 16 1/2° W 159 3/4' ft; 18" B.O. N 36 1/2° E 176 1/2' ft. No other suitable

✓ 1/4 bet 13 & 14. Rest from 7 O.B.T.s badly rotted. Drove  
#7 Iron pipe. Marked 18" B.O. N 61° W 45' ft; 18" W.O. N 18° E 39 1/2' ft.

✓ 1/4 bet 11 & 14. Rest from one O.B.T. rotted. Drove  
#8 Iron pipe. Marked 14" Fir S 43° W 99' ft; O.B.T. 18" B.O. N 61° W 119 1/2' ft

✓ Sec Cor. 10-11-14-15. Rest from old 18" B.O. called for  
as corner. Only stub of corner tree is left + B.T.s are gone. Marked  
#9 new B.T.s. 16" B.O. N 68° W 21' ft; 24" B.O. S 77 1/2° W 60 1/2' ft; 8" Cedar  
S 57 1/2° E 23 1/2' ft; 4" Laurel N 71° E 35' ft.

✓ 1/4 Cor. bet 10 & 15. Rest from one O.B.T. + one stump.  
#10 Drove I. Pipe. Marked 30" Fir S 50° W 28' ft; 30" Fir N 9 1/2° E 28 1/2' ft.

✓ 1/4 Cor bet 14 & 15. Rest from one stump with "B.T." on it.  
#11 Drove Iron Pipe. Marked 30" Fir N 70° W 24 1/2' ft; 18" W. Fir S 46° E 21 1/2' ft

✓ Sec Cor. 9-10-15-16. Rest from one O.B.T. + 2 stumps. Drove Pipe  
✓ Marked 18" Fir S 88° W 24' ft; 30" Fir S 20° E 27 1/2' ft; 30" Fir N 71° E 9 1/2' ft

#12 20" Fir North 21 1/2' ft.

R. G. Stewart D.C.S. 1922  
C. G. Crocker - Blumburg - wire long "1" with wire

May 1916 1880

Feb. 30-1892 Witness Cor. to S.E. Cor. J.H. Gillam D.L.C. 46 T. 26 S. R. 7 W.  
 Original Cor. Washed out by River. This Cor. is one chain short of original. New B.T.  
 #13 B. Oak 16 in N. 59 1/2 W 39 Lks.

W.F. Briggs #14 N.W. Cor. D.L.C. 46 T. 26 S. R. 7 W.  
 Laurel 8 in S 45 E 102 Lks.  
 " 10 " S 42 1/2 W 84 "

#15 NE. Cor. D.L.C. 46 T. 26 S. R. 7 W.  
 B. Oak 30 in. S. 35 W. 200 Lks. (?)

#16 Corner Sections <sup>22/23</sup> ~~27/26~~ Set from Old B.T. in  
 Set. 23 other Trees gone. Set 1 1/4" x 18" Pipe.  
 Marked New B.T. { Fir 20" 25 E 38 ft; Fir 24" N 62 1/2 E 205 ft  
 W.O. 14" N 80 3/4 W 107 2/3 ft No Tree available <sup>in sec 27</sup>

Sept 13 1934 J.H. Wolford Surveyor  
 B.A. Lane } wit.  
 Jas F. Jeffries }

#17 F.C. Frear NE Richardson <sup>45 1/4</sup> COR ~~45 1/4~~ T. 26 S. R. 7 W., Set 4" x 4" x 30" Fir Stake  
 P.D. Wolford #17 (24" Fir N 86° E 24 ft  
 June 1934, from old B.T. Marked New B.T. 24" " S 49° E 22 3/4 ft

#18 May 18 1935 F.C. Frear The 1/4 Cor bet Sec 34 & 35 Re Set.  
 B.A. Lane } wit.  
 Carl Becker }  
 Set by  
 F.C. Frear from One Old B.T. Scribe marks Plain.  
 Set a 2" x 30" Iron Pipe 20 feet East on side  
 of Road for Witness Cor. from which  
 A 10" White Oak Bears N 43 1/2 E 42 feet  
 A 12" White Oak. " S 55 1/2 E 61.5 feet.

#19 Oct 26 1937 H.L. Eppstein vs. Arthur Boyer D.C.S.  
 B.A. Lane } wit.  
 Will Long }  
 Jno Paulson }  
 Wm Thompson Hrs. of }  
 Mrs Anna Emery Thompson }  
 Most northerly N.E. Cor. D.L.C. 43 (Stucker) Found orig S.S. rock,  
 to which this cor is tied, N. 504.2' 9/16 rock at N.W. Cor this D.L.C. from which  
 this cor is set, Mr Long & Mr Thompson witness that location for this cor.  
 should be in cen county road (as extended N) to the S. Set 4" Round oak post  
 1/2" Steel bar in center for Cor. fr. wh. fence cor brs W. 26'

#20 Apr 12 1939 H.L. Eppstein vs. Arthur Boyer D.C.S.  
 B.A. Lane } wit.  
 Harvey Eppstein }  
 Fred T. Recca }  
 1/4 Cor East side Sec 25. Set 1 1/2" x 36" Iron Pipe 8"  
 above Ground for corner. from stump of B.T. in  
 Sec 30, O.B.T good in Sec. 25, cut B.T. out on stump  
 Marked New B.T. Fir 18" dia N 87° E 17.3 feet  
 Old B.T. in Sec. 25 Good.