

*M. B. Gemond*  
 #1 N.E. Cor. of D.L.C. # 52  
 Renew from old B.T.  
 Set in a 3 1/4" x 36" Oak S. P. for wh  
 a 20" fir brs N. 60 1/2° W. 21 lbs. Also remarked  
 old for tree.

*J. W. Cole. Dep.*  
 #2 Cor. to Secs. 4-5, 8-9. (See Page 85)  
 Renewed cor. from old bearing trees and  
 set a 1 1/2" x 30 iron pin and a  
 3 x 3" x 36' oak post.

*H. L. Eppstein Dep.*  
 #3 1/4 Cor. Secs. 16 & 17 - Re-established from one old  
 B.T. which Brs. N. 60° E. 150 Lks. by setting a  
 4" x 4" x 36" Oak Stake from which  
 a 10" B. Oak brs. N. 46° 30' W. 50 1/2 Lks. C.S. B.T.  
 a 12" B. " " 5.28° E. 56 Lks. "

*Wit. G. P. P. Glen*  
 #4 N.E. Cor. D.L.C. 44 Re-Est. from Old Stone  
 by a 20" W. Oak brs N. 70° 30' E. 572 Lks. C.S. B.T.  
 a 24" B. " " 5.45° E 661 " "

*J. P. Frost*  
 #5 J.W. Cor. Sec. 32-7 re-establish from one Old  
 B.T. viz 18" Cedar brs 5.28° E. 11 2/3 ft. marks plain  
 other trees all destroyed. I set a 2" x 12" Wagon  
 Box from wh. a 24" Cedar brs 5.82° W. 28 3/4 ft.

*G. G. Stewart, D.L.C.*  
 #6 1/4 cor. But Sec. 21 & 28. Re Est. from 2 old B.T. One rotten.  
 (Dead - New B.T. 12" W.O. N 27 E. 34.3 ft. July 19-43 - Byer-Jess + Harold Marr Wits.)  
 Drove Iron Pipe: ~~Marked 12" Fir N 75° E 50 ft.~~ 12" W.O. N 27° E 34 3/4 ft

*Best Spring lead*  
 #7 Sec. Cor 21-22-27-28 Re. Est. from 2 old B.Ts. and one Stamp.  
 distances + Bearings did not check. Set Iron pipe according to  
 distances. Marked a 74" B.O. N 72° W 185 ft (old B.T.); 18" W.O.  
 S 1 1/2° W 135 ft. 18" B.O. N 89° E 169 ft. 18" B.O. N 75° E 73 ft. Set this corner for  
 3-29-27

*F. G. Stewart, D.L.C.*  
 #8 S.W. corner D.L.C. # 43, J. Matthews D.L.C. Re set from old  
 B.T. a Laurel that Chas bay cut + was rotten. Set I. Pipe  
 for Corner. Marked 74" W.O. S 85° W 74 5/8 ft. Remarked old B.T. 14" Laurel stub  
 S 40° W 8°.

*M. B. Gemond*  
*J. W. Cole. Dep.*  
*H. L. Eppstein Dep.*  
*Wit. G. P. P. Glen*  
*J. P. Frost*  
*G. G. Stewart, D.L.C.*  
*F. G. Stewart, D.L.C.*

see next pg.

H.L. Eppstein C.S. G.G. Stewart, D.C.S.  
 W.S. Crear  
 W.E. Chapman  
 W.L. Crear  
 Heman Odum  
 Ernest Kelly  
 Frank Odum  
 W.S. Crear  
 W.L. Crear  
 Heman Odum  
 Ernest Kelly  
 Frank Odum  
 W.S. Crear  
 W.L. Crear  
 Heman Odum  
 Ernest Kelly  
 Frank Odum  
 W.S. Crear  
 W.L. Crear  
 Heman Odum  
 Ernest Kelly  
 Frank Odum

#9 ME. cor D.L.C #44 (Eel corner). Reestablished from dead O.B.T.  
 MAR 3, 1936 15" W.O. S 59° E 36' Set by A. Boyer - NE Richardson  
 Set Iron Pipe for corner. Marked 6" W.O. S 15 1/2° W 6 3/4' 1 1/2" B.O. S 75 1/2° E 53 1/2' ft

#10 SE. corner D.L.C #43. J. Matthews.  
 Reestablish from 8" limb in maple - the O.B.T. Set Iron Pipe for corner + mark 20" Fir N 78° E 10 1/2 links; 6" W.O. N 63° W 37 links.

#11 Set inter-"L" corner to claim ~~39~~ from old stump ~~at~~ "X"  
 Saw analyzed Pipe Marked 10" B.O. S 55° E 56' feet, 6" W.O. N 69° W 42 1/2'

#12 Set S.W. corner of D.L.C. 51 from old trees found by me previously Marked W.O. 16" S 50° W 50.8 feet

#13 Set 1/4 cor between section 28-29 from one old B.T. <sup>which</sup> was in good shape with crisp marks plain, Marked New Trees Red Fir 10" N 13° W 13° feet Red Fir 6" S 73° E 17° feet

1/4 Cor Secs. 3 & 10.  
 Location identified from 1 OBT and fence corner. BT chopped out and badly rotted. Set ~~at~~ Pine limb for corner. New BTs 30" B.Oak N 66° 30' W 15 lks - 8" W Oak S 13° 45' E 67 lks.

#14  
 #15 1/4 Cor. Bet. Secs. 14-23 (F.B. No. 7 Page 38)  
 Fir 15" S. 80° E. 123 lks.  
 " 16" S. 1/2° E. 133 "

#16 1/4 Cor. Bet. 15 & 22 (F.B. No. 7 Page 61)  
 B.Oak 24" N. 44° W. 22 lks.  
 Fir 12" S. 30° W. 3 "

#19 1/4 Cor. Bet. Secs. 22-27 (F.B. No. 7 Page 61)  
 Fir 30" N. 72 1/2° W. 48 lks.  
 " 8" S. 42° E 52 "

See next page.