

N.W. Cor. J. Simmons DLC. 41

(F.B. No. 30 Page 43)

CS. Boyer #18

Ash 8" N. 87 1/2° W. 52 Lks. marked C. 41 C.S. B.T.

1/4 Sec Corner 15/22

~~Identified~~ Location identified from stump of fir BT as set by Roberts. (see previous page) 1904.

Oak BT down. Original Laurel BT. part of stump remaining Set for corner Iron Pipe from which

a fir 18" dia bears S 30° W 43 ft blazed & scribed 1/4 S 22 C.S. BT

#19 " 20" " " N 76° W 71 1/2 " " 1/4 S 15 C.S. BT.

1/4 Sec. Corner 22/27

Location identified from BT as set by Roberts 1904

Set a 1 1/4" Auto Axle from which


O.B.T. 36" Fir bears N 72 1/2° W 48 lks.

New B.T. 24" " " S 55° W 61.8 ft Blazed & scribed

#20 1/4 S. 27 C.S. B.T.

MAR 3-1936

NE Cor DLC. 44



Iron Pipe

15" White Oak - N 59° E. 36'

A. Boyer Dep.

The 6" W.O. S 15 1/2° W 68' as shown on prev. pg. (#84) has been

NE Richardson wit.

cut down so the above tree was marked as shown

#21

Mar. 22-38

NE Richardson Roy Strader

1/4 Cor. Secs. 4-5-8-9

Located from old B.T. and Iron Bar set by Cole  
Marked new trees

W. Oak 18" N. 20° E. 28 1/2 Ft Marked S. 4 - C.S. B.T.

B. " 10" N. 59 1/2° E. 48 " " " " "

#22 W. " 8" N. 81° W. 179 1/2 " " S. 5 " "

Dec. 9 1933 Ben B. Irving  
Deputy County Surveyor.  
Witnesses - N.E. Richardson  
J.S. Mall.

27-4

Ben B Irving D.C.S.  
Witnesses  
R.L. Irving

G. A. Lindbloom

June, 30, 1909

#23

SE Corner of the WMA Willis DLC No 45.

This corner is a 6" x 14" x 6" above the ground sandstone. The original bearing trees have been chopped out & scribe marks no longer legible. Blazed & scribed a Fir 24" dia. N 55° W 33 1/2'. SE DLC 45 CS BT. & a white oak 12" dia. which bears S 49° E 63 " " " " " "