

27-5

1934
J.H. Wolford
B.A. Lane
P.D. Wolford
#30
1/4 Corner 30+31.
Found Iron Pipe by Old Corner Post, One Original B.T.
other gone.

1934
Ben B. Irving
N.E. Richardson
B.A. Lane
#31
1/4 Corner 19+24

As this corner was lost. Set it in by proportional measurement.
by setting 1/2" x 30" Iron pipe 6" under ground in alley
of Block 57 City of Roseburg. From which the intersection
of Alley with Mosher Street & bears S 27°-00' E 170.92 feet
No tree near.

Meander corner bet. Secs 19+24 R. 5+6 W.

#32
An Iron Pipe set for corner. Old B.Ts. Not cut out
as they are in owner yard, Washington Hughes.

1935
Frank Cain
B.A. Lane
N.E. Richardson
#33
Meander corner bet. Secs 18+13 R. 5+6 W.

All indication of corner gone. Corner, 5/8" x 4 1/2" Iron Rod
set by proportional measurement, 4.8 feet south of the
South Rail S.P. RR. A channel iron 1 1/4" x 18", 14" in ground
under Right of way Fence. A Bridge bears N 16°-30' W 62.0 feet.
about 4550 feet from B.C. RR. curve left north of cut on RR.
A.W. Oak 14" diam. bears S 60°-30' W 117' Marked M.P. c.s. B.T.

J.H. Wolford
B.A. Lane
N.E. Richardson
#35
1/4 Cor. Bet Secs 13+18 R. 5+6 W.

Corner set by proportional distance. by setting 1/2" x 48"
pipe inside 2" x 48" pipe. About 250 ft. South + West of
Horaceburg's House. from which
A white Oak, 10" diam, bears S 57° W 223.5 ft, Marked 1/2 S. 13 C.S. B.T.
" " 18" " " 524°-10' W 242.3 " " " " "

Corner $\frac{12}{13} \frac{7}{18}$ set by proportional measurement by placing
10" x 10" x 14" sandstone 12" under ground, 3" under road
ditch. X on Top C.S. with two notches on North face
and four notches on South face. from which
S.W. corner of Lot 15 Fruitvale bears S 1°-58' E 1026.1 ft.
N.E. corner of D.L.C. #56 T. 27 S, R 6 W bears S 28°-24' E 857.7 ft.

#36

27-5

1/4 Corner secs. 7 & 12 R 5 & 6 W. set by proportional measurement by driving machine ~~gun~~ barrel 10" underground, Tin collar 1 brick on top 3 brick placed around, 4" x 4" x 48" post 24" in ground marked 1/4 S on North Face, C.S. on South; Face; S7 on East Face, & S12 on West Face
 #37 from which N.E. Cor D.L.C. 37 T 27 S R 5 W bears N 75° 12' E 924.9 Feet

Corner ¹¹⁶/₁₂₇ set by proportional measurement. by driving 5/8" x 42" iron bolt, 15" under ground with oak chunk 4" x 6" on top from which.
 #38 7 W. Oak 12" diam. bears N 40° E. 75.6 Ft. Marked T 27 S R 5 W Sec 6 C.S. B.T.
 7 W. Oak 20" " " N 46° W 132.0 " " T 27 S. R 5 W. Sec 1. C.S. B.T.
 No other Trees Near.

1/4 Corner bet secs 146 R 5 & 6 W b proportional measurement
 Drove 1 x 24" Machined Gun barrel 23" in ground & set a Yellow pine stake 3" sq x 36" long with R 5 W S. 6. on East Face
 #39 1/4 S. on North Face, R 6 W. S 6 on West Face, C.S. & 27 S on South Face
 From which 14" White Oak Bears S 68° 45' E 59.5 ft Marked 1/4 S C.S. B.T.
 20" White Oak, bears S 83° 10' W. 77.7 Ft marked 1/4 S. C.S. B.T.

Township Corner ³⁶/₃₁ T 26 + 27 S, R 5 + 6 W.
 set from stump, scribe visible, in S.E. & stump hole in S.W. set 1" x 48" pipe 42" in ground with pile
 #40 of Rock 20" sq base, 12" high From which
 10" White Oak Bears S 55° W 27.8 Ft.
 Marked T. 27 S, R. 6 W, S. 1. C.S. B.T.
 6" White Oak Bears S 14° E 15 Feet.
 Marked T. 27 S, R. 5 W, S. 6. C.S. B.T.
 6" White Oak Bears N 73° E 48° Feet
 Marked T. 26 S, R. 5 W, S. 31, C.S. B.T.
 10" White Oak Bears N 50° W 74 1/2 ft.
 Marked T. 26 S., R. 6 W, S. 36 C.S. B.T.

1/4 Corner bet secs. 7 & 18. set from stumps of old B. Ts. Marks visible on NE stump. Marked New
 #41 B. Ts. as follows } Blk Oak 8" diam., brs N 88° W 47.6 ft
 White Oak 6" diam., brs. S 53° 30' W } Marked 1/4 S. 7. C.S. B.T.
 Also U.S. C. & G. S. triangulation Sta. Rose. brs. N 55° 01' 30" E. 3175.6 Ft.

S.E. Cor to D.L.C. #37. set from O. B.T. N 15° W. 291.4 ft.
 #42 Scribe Marks plain. set for corner 3/4" Galv. Iron Pipe from which
 white Oak 12" diam., brs N 55° W 119.6 ft. Marked C. 137, C.S. B.T.
 white Oak 10" diam., brs. N 13 1/2° W 168.0 ft Marked C. 137. C.S. B.T.

1934.
 Ben B. Irving
 N.E. Richardson
 Ernest Brown.