

W.D. Hannon
F.C. Frean
Oscar Lundrey
#4 Jan 7 Feb. 1917
Hemphill, Co. Tex.

Set in 1/4 cor. bet. secs. 23 and 24 Tp 27-6
One old Bearing Tree in evidence.
New Corner is pipe 1" x 24" and stone 6" x 8" x 12" from wh.
A. Cedar 14" dia brs. N 25° 55' E. 16 lbs. dist (Cen. of tree.)
A. Fir 28" " " N 78° 30' W 11 " " (" ")

Same witnesses
as above

Set in sec. Cor. for sections 23, 24, 25, and 26, T. 27-6
From two old original B. Tree Stumps. Letter (Legid)
New Cor. is 2" x 36" iron pipe (gal.) from which exact sec. line N.
A. W. Oak. 15" dia brs N 00° 10' E 8.72 lbs. Nail in the tree marks
A. W. " 16" " " S. 75° 00' W 4.355 "
A. W. " 8" " " S 16° 07' E. 3.88 "

Set in for S.E. Cor. of John Leisure D.L.C. No 53. T27-6
A 2" x 36" gal iron pipe (One old tree in evidence)
A. W. Oak 12" dia brs. N 71° 38' W. .66.25 lbs.
A. Madrone 4" " " S 44° 54' W .6915 "

Set Cor 20-21-28-29
Renew from 2 O.B.T. standing and 2 stumps of O.B.T.
Set Iron Pipe for Cor.
Marked 8" W.O. N 45° E 50' ft
24" W.O. S 67° E 78' ft O.B.T.
18" W.O. N 30° W 67' ft
18" W.O. S 37 3/4° W. 134 links O.B.T.

1/4 Cor bet 28 & 29.
Renew from stumps of O.B.T.
Set Iron pipe for corner
Marked 8" Fir S 58° E 64' ft. 6" Pine N 25° E 90' ft
on line of old rail fence (E+W) sighting W. from cor.
Corner approx 35° So Road.

G. Stewart D.C.S.
G. Crocker A.S. Crease
witnesses
March - 1922

1/4 cor. West side Sec 6. Bet 68 / T 27-6 & T 27-7
Found O.B.T. Set 1/4" Iron Pipe : Marked a 10" W.O. S 67 1/2° E 43' ft
30" W.O. S 56° W 22 1/2' ft.

G. Stewart, Dep.
1924-17-22
Johas Sindt
J.F. Johnson witness
T.F. Bittel

27-6

G.G. Stewart Rep
1917-17-22
Chas. Kaiser; V.T. Boush; A
Johnson; Wittel; Smith
Witness
#10
121

Section cor. bet 687-T27-6 & 1017 T. 27SR7W.
Set 1" Iron Pipe; from one O.B.O. Others gone. Corner in Creek.
Marked a 14" Fir N42°E 16⁸ ft; 84" Fir S42°E 97³ ft; 80" W. Fir
S 55³/₄° W 57⁴ ft. 14" Fir N39° W 45⁴ ft.

G.G. Stewart
Deputy

Marchwest corner D.L.C #56.
Renewed from old pipe, set by F.C. Frear as corner. Set Pipe
for corner in edge pavement, in a projection at side of
pavement. Set in 6" Concrete; On Eden bower Pavement.
By Davis House.

F.C. Frear
Roadmaster
Jan. 9-1923
Wit. P.D. Wolford
#11
J. Dick Butkus

N.E. Corner D.L.C. #56 - Renewed from old
stake set by State Hwy. Engrs and later
Permanently established by Auto Axle set in
12 1/2" x 15" Concrete on ^{with} Eden bower Pavement

R.L. Epstein
J.H. Wolford
Richardson
Jan. 7-1929
#13

Section Corner 15-16-21-22, Renewed from
old B.T. Set Dodge Rear Axle, Marked
12" Maple N35°W 37 ft. Old B.T.
14" B. Oak S 53¹/₄° E 98 ft. 15" W. Oak S 71³/₄° W 102'

SW Cor. D.L.C #50. Wm McKinney D.L.C.
4x5 rock as called for in original notes, Blazed
and scribed BTs as follows.

- #14 8" Black Oak N43°E 62 lks. SW CL 50 CS BT
- 8" White Oak N70°E 66 lks SW CL 50 CS BT

APR 1 1928
Deputy County Surveyor
W.E. Richardson
Cliff Madley } Witnesses
#15
Y 16 E 55(?)

SE Cor Wm McKinney D.L.C #50
Found original BT. old surface rotted out
but figures plain on reverse chip. This corner
comes in present traveled portion of county road
Roseburg to Helrose. As it is planned to regrade this
section soon did not set anything for corner point
but marked new BTs as follows.

- #15 12" Laurel East 22 lks scribed thru bark SE CL 50 CS BT
 - 10" Black Oak N 55° E 30 lks. blazed and scribed SE CL 50 CS BT
- Corner is located 6' ft right of ¹/₂ sta 196+01 on new road survey.