

Burd Johnson Dep.  
Dec 1901  
NE Richardson  
Mt Bryer  
Be Irving  
Bert Lane  
WN.

S.W. Cor. Isaac Jones D.L.C. No 65.

Set a brass plate in Conc. post 6" x 6" x 36" in ground at fence intersection. This fence corner has been in place as the property corner for a great many years and has been used by the adjoining property owners for the true corner.

#16

H.L. Epstein H.L. Epps, Fern.  
Roscoe Conn Fred Goff  
Kenneth H Roscoe Conn  
Nov 1933 J.A. Peterean

N.W. Cor. D.L.C. No. 50 Exterior L corner

Set from testimony of Fred Goff as to location of witness tree & distance from interior L corner.

#17

B. Oak 20" Dia. S 18° E 229.8 Feet

Cor. Sec 32-33-495 Astoria is buried in Ground

For this corner, witness trees in Sec 5-32-33 in Place Tree in Sec 4-90NE. NO TREES NEAR.

#18

1/4 Cor. 15/16 location determined from deed descriptions and location of County Road as given in old recorded surveys.

#19

Set 1" Iron pipe <sup>driven 6" underground</sup> on County Road at terminus there of. 30" Black Oak bears S 2° E 29' blazed and scribed 1/4 5 15-16. C.S. BT

#20

S.E. Cor. D.L.C. No 43. Measured From Iron Pipes on Laurel Crest Plat & From NE Cor. Cl. 43, And Set 1" x 30" Shaft for corner. Marking a W Oak 30" Dia. N 71° E 466' feet, Marked S.E. Cl. 43. C.S. B.T.

Nov. 15, 1934  
Wit Jacob W Jones  
Ben F Jones  
Bert A Lane. 72a  
H.L. Epstein  
Ca. Surveyor

#21

Car 9/10 / 16/15. This Cor was a <sup>chipped</sup> river Boulder Buried in Field by previous Surveyor. I set a 1 1/4" x 18" Iron Bar under stone with charcoal around from which;

40" Oak bears S 83° 30' W 185' ft.

#22

S.W. Corner (concrete Basement) of Ben. F. Jones House Bears N 67° 30' W 156.7 ft.

Apr 6 - 1935  
Mar 26 - 1935

27-6

Apr 6 - 1935  
witness  
C.W. Crocker  
Ray Webber  
Harry Titus  
Ernest Brown

Mar 26, 1935  
F.C. Frear  
witness  
P.D. Wolford  
J.H. Wolford

✓ A, E.S.E. Cor of D.L.C. #55 Set Iron Pipe for Cor.  
from one old B.T. Marking Plain, Marked new B.T.  
20" White Oak S 49° 28' W 97° ft. Bear True carried from  
30" White Oak S 5° 02' W 116 5/8". C.F. Survey.

✓ Cor. <sup>18/17</sup>/<sub>19/20</sub> Set 3" x 3" x 30" Oak Stake from two Old  
Bearing trees, from which New Bearing Trees are as  
follows: 16" R Fir S 51° E 12.9 ft; 14" B. Oak N 86° W 43.8 ft,  
12" Laurel S 61 1/2° W, 44.9 ft; 10" B Oak N 32 3/4° E 41.3 ft.

#23

1/4 Cor. Bet. 13 & 18 On East Line of T 27-6 W.  
1/2" x 48" Pipe inside 2" x 48" Pipe About 250 Ft.  
✓ South of H. Burg House in Fence Row.  
W. Oak 10" S. 57° W. 223 5/8 Ft.

#24

" " 18" S. 24 1/4° W. 242 3/8 "

M.C. on Right Bank of S. Umpqua River on East  
Line of T. 27-6 W. Bet. Secs. 13 & 18

An Iron Rod 5/8" x 4 1/2' with 3 prongs  
on top 4 8/16 Ft. from S.P.R.R. South Rail  
W. Oak 14" S. 60 1/2° W. 117 4/16 Ft.

A Chanel from 1 1/4" x 18" under Right of Way  
Fence Brs. N. 16 1/4° W. 62° Ft.

#25

Cor. is about 45' S. of B.S. of R.R. Curve  
North of Cut on R.R.

N.W. Cor. Cl. 63 T. 27-6 W.

Wagon Skein

✓ Inside of East Rail of S.P.R.R. 59 1/2 Ft. East  
Soldiers Home Smoke Stack S. 45 1/2° W.  
Beacon Mt. Nebo S. 3 1/4° W.

#26

Mt. Rose Δ Sta. S. 89° E.