

F.C. Freear Dep.  
Wit. W.S. Hamilton  
W.D. Dyser  
Oct. 11-1919

Cor. of Secs. 16-17-20-21 - Re-established from original B.T.S. all standing - By setting a 1 1/2" x 48" Iron Pipe and remarking the B.T.S.

99 Stuart  
Oct 30-22  
Wit. T. Scott  
R. Conner  
C. Kamm

1/4 Cor. bet 1 & 12. Re est. from one O.B.T. faintly scribed  
Drove 1/2" I Bar + Post. Marked. 24" B.O. 75 2 1/2 E 14 ft; 12" B.O. 23 W 21 1/2 ft

J.W. Cole  
Geo. Finley  
Mary Branch  
#16

Cor. to Secs. 23-24-25-26.  
Renewed this corner from three original B.T.s which check for direction and distance. Hole where fourth tree stood visible also checking. I set a 1/2" x 30" Iron rod also 4x4 x 40 oak post for corner.

J.W. Cole  
Mr. Caslow  
#17  
4/28/24

1/4 Corner between Secs 25-26  
Renewed this corner from orig tree S 47° W 12 lks which I chopped open and found scribe mark. I set a cedar post and mound of rock and marked a W Oak 10" 76 8° 00' W 30 ft  
" " W Oak 5" 75° 30' E 27"  
I also set steel auto axle at corner

99 Stewart  
Geo. Cooper  
A. Som  
Oct 26 1924

ELL corner D.L.G. No. 42: Set 8" x 12" x 18" Rock for corner  
#18 from O.B.T. badly rotted - Marked 36" W.D. N 15° W 33 ft.  
1/4 Cor. bet 11 & 12. Drove 3/4" Iron Pipe from one O.B.T. standing and one stump.  
#19 Marked 18" W.D. 78 4° W 60 ft; 6" W.D. 52 9 1/2° W 50 ft

Richardson  
W.S. Richardson  
Alvin Anderson  
Nov. 21 1929

NW Est. Cor C1 43  
Location identified from OBT 24" WD scribed C43 275 7 W  
Set post scribed "NW CL 43 CS ~~BT~~" from which the OBT bears S 63 1/2° E 66 lks which I reblazed and scribed NW CL 43 CS BT and a new BT 16" W. Oak bears S 40° E 76 lks scribed "  
#20

27-7

Nov 191929

Blind during

NE Richardson  
Alvin Anderson / witness  
County Surveyor

✓ SW Cor DLC #44  
Location identified from corner tree which it was necessary to chop down leaving as a corner post that portion originally blazed and from OBT as described in the records of the County Surveyor.  
Reblazed & scribed Orig. BT and set as an

#21 additional BT a 24" Fir N59°W 27' ft

✓ 1/4 Cor. South, Line Sec 31. Standard Govt Pipe (149/31) Set by Minch U.S. Surveyor. I marked New Witness trees; as follows  
#22 Fir 10" S.75°E. 20' Feet; W. Oak 24" S 56°-30'W. 46' Feet.

✓ 1/4 Cor Bet. Secs. 30 & 31. I set a cedar Post 4"x4"x36" in ground where old C.S. Post was, Marking following witness trees.  
#23 W. Oak 16" S47°-15'W. 65' Feet; W. Oak 589°E 135' Feet.

✓ 1/4 Cor West Line Sec. 31. set 1"x18" Drift Bolt for corner from two old B.T. I marked two New Witness Trees as follows;  
#24 Fir 10" N35°W 27' Feet; 12" Fir S67°E 26' Feet.

✓ S.W. Cor. DLC. #59. I set from Old B.T. Set 4"x4"x36" Cedar Post for corner and marked for New witness Tree, a  
#25 W. Oak 10" N55°E 28' Feet

✓ Sec. Cor of 30 & 31. Set corner from three Old witness trees. I set 4"x4"x36" yew wood Post for corner. The three old wit. Trees being in good shape, I only marked New B.T. in Sec 30. as follows.  
#26 Red Fir 20" N28E 45' Feet.

✓ Sec Cor 36 & 31. Set cor, from Old B.T., where I found remains of rotten Post. For corner I set 1"x18" Drift Bolt. Marking New B.Ts.  
#27 as follows; Fir 12" N 5°W. 9' feet; Fir 10" S88°E 24' feet.

✓ Sec Cor of 31 & 32. Fort. Standard (131/32) in place. Set by Minch U.S. Surveyor. Witness Trees. as follows. Fir 48" N2°E. 52' feet,  
#28 Chincapin 5" N34°W 21' feet Cut Down. I marked a Fir 48" N48-30'W 46' feet.

✓ 1/4 Cor Bet Secs. 31 & 32. This corner was lost, so I ran line from Sec Cor 31 & 32 North to Section corner, <sup>30/29</sup> <sub>31/32</sub> and then set 1/4 Cor Porportional Distance between. Set Post in field and marked as New B.Ts. W. Oak. 10" S4°E 197' feet; O.C.P.C.O. Power Pole <sup>2</sup>/<sub>18</sub> S34W 223' <sup>6</sup>/<sub>18</sub> Feet.

✓ Sec Cor. Secs. <sup>30/29</sup> <sub>31/32</sub> Set from 2 Old B.Ts. <sup>In Sec 30 & 29.</sup> I set 4"x4"x30" Cedar Post for corner. Marking New B.Ts as follows.  
#30 W. Oak 10" N43°E 54' feet; W. Oak 10" S60W 44' ft.

H.L. Eppstein Co Sur.

B.A. Lane

Bob Mathews

Fritz patricks Bros

Witness June 1930

H.L. Eppstein

N.E. Richardson

N.C. Conn

Dysert

Feb 1929

N.W. Cor C152. Set cor from old Oak B.T. scribe Marke set 6"x11"x30" sandstone 1"x7" pipe  
#31 marked N. B.T. 16" Fir S50°E 177 lbs