

28-7.

G.G. Stewart D.C.S.

G.O. Thickland, A. Dyer, A. Erickson witness
Marked 16/1922

1/4 Cor bet 4/9.

Renew from orig B.T. standing.

#7 Set gun barrel for cor. Marked 8" Laurel N. 54° E. 29° ft
12" Pine S 4° W 56° ft.

1/4 Cor bet 4/3.

Renew from stumps of orig B.T.s.

Set Iron Pipe for corner

#8 Marked 12" Fir S 66° W 50° ft; 74" B.O. N. 53° W 163° ft.

Section Corner 3-6-9-10

Establish by intersection of lines between quarter

#9 corners. Set Iron Pipe. Marked 16" B.O.

N 63° E. 71° ft 10" B.O. N 11° W 247 ft

Sec. Cor. bet 31-32 + 5.6 in T 29 S R 7 W.

3 O.B.T.s. present, which do not check with field notes. The distances and bearings evidently twisted. I set marked

rock for cor. and the O.B.T.s. are as follows. 40" Fir S 79° E 49° ft.

15" Laurel N 16 1/2° E. 66° ft. 12" B.O. (down) S 31° E 28°.

Mark new trees: 40" Fir S 79° E 49°; 36" Fir S 46° W 75°; 40" Fir N 24° W 18° ft; 8" Fir N 34° E 53° ft. (See Page 114)

July 8 1922
1/4 Cor So. Side Sec. 31.

#10 Set Iron Pipe. on true line bet. sec. corners. cannot find O.B.T.s.

Marked 14" ash N 24° E 76° ft; 16" ash 54° ft. N 59° W.

Inner L corner D.L.C # 49. John Freeman Claim

#11 Set Iron pipe from O.B.T. Marked 10" B.O. S 83 1/2° E 19°
O.B.T. 18" W.O. N 29° W 35°

G.G. Stewart D.C.S.

C. Erickson, W. Johnson witness
cut 19-22

1/2 Sec. cor. W Cor Cl. 49 set pointed rock for corner from

#12 O.B.T. Marked a 12" Fir N 75 1/2° E 33° ft; 12" Fir N 32° E 64 1/2° ft.

#13 M. E. Cor. Cl. 49. Set Iron Pipe from Remains of O.B.T. pointed out by W. Johnson as O.B.T. 12" W.O. S 65° W 15° ft

6" B.O. N 77 1/2° E