

G. G. Stewart Deputy Oct 19-22

C. Crocker, U. Johnson witnesses #14

SE Corner Cl 49. Set Iron pipe from O.B.T. Marked 12" Fir S41°W 33' and 36" B.O. N35°W 758' ± O.B.T.

N.W. Corner Cl. 49. Set Iron pipe from O.B.T. badly rotted. corner checks in with original line blazes. 16" B.O. N86°E 9' ft 18" B.O. N87°W 18'

S.W. corner Cl 49, O.B.T. is missing. Set Iron pipe at N89°30'W 7176' from SE cor. Drive Iron Pipe marked 8" Fir N87°E 22' ft; 5" W.O. N71°W 18' ft.

Section corner Common T₀ 23-24-25-26 Set Iron pipe from O.B.Ts. Marked 8" B.O. N45°15'W 31' ft; 6" W.O. S54°W 32' ft; 8" W.O. S41°E 27' ft 11" W.O. N80°E 122' ft.

1/4 Cor. bet 25+26. Set I.P. from O.B.T. Marked 18" B.O. S11°W 87' 12" W.O. N34°E 5' ft.

Section corner bet 29-30-31-32. Renewed from O.B.Ts B + one stump set Iron pipe; marked 30" W.O. N6°E 26' ft; 36" B.O. N19°W 9' ft; 36" B.O. S30°E 39' ft; 24" Pine S46°W 60' ft.

1/4 Cor. bet 29+31. Renewed from 2 O.B.Ts which do not agree with Govt. notes; use accepted location for corner. Drive Iron Pipe Mark 30" W.O. S38'2" W 47' ft; 30" W.O. N73°E 85' ft.

1/4 Cor 28+29. B.Ts. gone. Set from so line Cl. 55 as per govt notes set Iron Pipe for corner. Marked 70" B.O. S84°E 93' ft; 8" Fir N36°W 47' ft.

Section Cor. 20-21-28-29. Reset from 30 O.B.Ts. + our stamp. Trees opened + decaying Set Iron pipe and marked 24" B.O. N85°E 31' ft. 48" B.O. N12°W 7'4" 16" B.O. S79°W 28' ft; 24" B.O. S39°E 38' ft.

1/4 Cor. 20+29. Reset from 7 O.B.Ts. agree with distance but bearing one is 90° off. Set Iron pipe marked 6" Fir for corner, 12" Laurel N76°W 37' ft; 8" B.O. S20°E 23' ft.

1/4 Corner between 29+30. Found one stump, + burned B.T. Set NOTE: B.O. B.T. cut. No tree west. Marked 10" W.O. S27-30°E 25' ft. Iron pipe for corner + marked; 10" W.O. N19°E 56' ft; 8" B.O. S89°W 48' ft;

S.W. cor Cl. 54. Found O.B.T. standing; set Iron pipe for corner - marked 18" B.O. N64°E 136' ft; 20" W.O. N70°W 107' ft.

Note by G. G. Stewart Deputy Sept. 19 22

F. L. Eppstein Dept. 19 22
1934 S. Crocker, G. H. Porter witnesses #21
wit.

Vertical text on right margin: E. G. Stewart D.C.S. Mar. 8-1922
Feb 13 1923
C. Crocker

78 S. R. 7 W.

338

G. G. A. forward, Deputy
Sept. 1922

#29 witness
J. C. Crocker, J. H. Carter

SE corner Claim 54. Reset from burned O.B.T. drove iron pipe +
marked 6" Maple S 46° E 12 1/2 ft: 16" W. Fir N 42 1/2° W 47° ft.

#30 ME cor. Cl. 54. Reset from O.B.T. drove Iron pipe and
30" W.O. S 36 1/2° W 236 1/2 ft by H. Eppstein
Feb 14 1935
marked 72" B.O. S 17° E 107° ft: 24" W.O. S 55° W 168 3/4 ft.

#31 NW cor. Cl. 54. Set from O.B.T. decaying. Set Iron pipe and
marked 16" B.O. S 83° W 27° ft: 24" B.O. N 68° W 81 1/2 ft.

#32 NW cor. Cl. 55. Set from rotting O.B.T. set Iron pipe, marked
12" W.O. N 61 1/2° W 31 1/2 ft: 30" W.O. S 40° E 76 1/2 ft.

#33 SW cor. Cl. 55. 8" W.O. N 49° W 65 1/2 ft: 6" Pine S 38° W 122 1/2 ft.
Corner set as per govt field notes, from NW cor. Cl. 55.

E. G. S. forward D.C.S. Mar. 8 - 1922

#34 witness
Harold Nichols, S. McCree, W. H. Coats
J. C. Cabot witness
Vol. 3 Pg. 129

1/4 Cor Bet 31 + 32. Set I. Pipe from one O.B.T. set.
N 18° E 132° from Tree. Govt Notes call for tree bearing S 187° W 132°
Marked 12" W.O. S 75 1/2° W 36 1/2 ft: 14" W.O. S 18° W 132° ft (O.B.T.)
Standard Govt. Corner. (1931) Apr. 1931 - Eppstein

#35 1/4 Cor. bet 31 & 36 (R 7 + 8 W.) Set I.P. from one O.B.T. + 1st stump.
(Ford Survey Cor.) Marked 16" Fir S 17° E 533 1/2 ft: 24" B.O. N 44° W 116 1/2 ft.

#36 Twp. Corner 28 S + 29 S + R 7 W + R 8 W. Set Iron
pipe remarked 4 O.B.T.s. standing (Ford Survey Twp. cor.)

#37 ME cor. D.L.C # 56. Set stake in creek from old Pine
line tree. Marked. 18" Fir S 54° W 68 1/2 ft: On the SW side of
50 Pier of Highway bridge over Looking Glass Cr. N 43° E 196 1/2

#38 M.W. cor. D.L.C # 56. Set Iron Bar as per old fence line
and line Tree; Witness tree gone: Marked 30" B.O. S 1 1/2° E 84 1/2 ft
30" Pine N 42 1/2° W 94 1/2 ft

Feb 13 1923
J. W. Cole Co. Surveyor.
H. Bugh.
E. Richardson
W. H. Coats
Walter Coats

#39 witness
W. H. Coats

#39 Witness Cor. to Corner of Sections 25 and 36
on Township line. (Hathornes Corner)
Section corner is in creek account of channel
having changed. Set an iron pipe 1" x 30" for W.C.
25 feet west of true corner from which
An ash 30" dia bears N 28° W 28 1/2 ft. A Maple 14" in
dia br. N 21° 30' E 11.4 ft. The fallen and decaying
remains, position uncertain of Old B.T. Ash br N 66° E
50° ft. This tree bore scribe marks and was chopped open
years ago and W. H. Coats testifies that it is remains of B 9
35 1/2 24 lbs from corner