

T 28-7W.

Run to this corner. all this evidence corresponding closely. I renewed the corner by evidence on the ground instead of proportionate measure. the 1/4 Corner. set by Gordon Stewart bears North 1958 ft and West 267° ft.

Secs Corner. common to Secs 30nd and 31 on the Twp line bet. T 28 S R 778 W.

I renewed this corner from stump of 30" Oak which I believed to be the remains of the original B.P. called for in field notes as N. 85°00' E 671² ft.

Fords measurement South to Creek would check closely. also line East to 1/4 corner passes between to large oaks bearing very old blazes. Set a 2" x 60" iron pipe for corner and Mark new trees as follows

- 14" W Oak N 53°30' W 188° ft.
- 30" " " N 84°00' E 673 ft.
- 20" " " S 69°40' E 569° ft.

These trees were marked to face a point 78 ft North of corner but I afterwards decided to move same to correspond to evidence found.

Hathornes 1/4 Cor. on East side of Sec. 25

I renewed this corner from stumps of original B.P. which I identified by their size and position. Set a steel plow post 1/2" x 3" x 24" for corner from which Stump bears N 35° W 108⁶ ft. Stump of 30" Oak bears N. 30° E 136⁶ ft.

- marked. new trees W Oak 18" dia N 81°30' W 72² ft.
- Trees marked. 1/4 S, E S, B.P. N 32°30' E 56⁶ ft.

W.H. Coates
 Walter Coates
 N.E. Richardson
 Feb 23 March 1923 Witnesses
 Jesse W. Cole Co. Surveyor.

✓ 1/4 Corner. W Side Sec. 30. (Fords Corner)

✓ I renewed this corner from Original B Ts which are alive and showed scribe marks plainly when chopped. I could not harmonize the calls for directions and distances to these trees with the facing of the blazes so I set the corner where both trees faced and this position also checked with the tie to this corner made by Hathorne during his retracement of the Twp line. I set an iron bar 1 1/2" x 30" and a cedar post 4 x 4 x 36 from which Original B Ts bear as follows:

Same Witness

Co Surveyor

J. W. Cole

Feb 29 March 1923 #50

- A. B Oak 14" in dia N. 25° E 91.7 ft.
- A B " 18" " " N. 1° 00' W 85 ft.
- Marked new trees - - Fir 24" dia N. 69° W 54 ft.
- " " 16" " N. 27° E 17 ft.

✓ Corner to Secs. 24 & 25 on the Twp line bet Rqs 7 & 8.

✓ I renewed this corner from Original B Ts
A large Black Oak bearing scribe marks N. 58° E 30 lks
A W Oak 20" dia bearing scars S. 72° E 76 lks
A Hole where a tree stood bears N. 18° W 38 lks
A stump of large B Oak S. 72° W 30 lks
I set a fir post 5" x 5" x 50" also two conglomerate rocks 8 x 10 x 12" from which
Fir 8" N. 46° 15' E 176 ft. - Fir 12" N. 24° W 123 ft.
Fir 10" S. 38° W 198 ft. Fir 24" S. 52° 30' E 200 ft.

These two corners set by Heydon 20 years ago #51

✓ SW Corner of Coats D.L.C. No. 59 on Twp line
Set a rock 10 x 10 x 12" ^{Hathorne} on Twp line at proper distance from N. W Cor Sec 31. No evidence of witness trees to be found.

#52 L Cor on South 1/2 West boundary is a similar rock set as the SW Cor. is by measurement.