

Corner of ^{N^m} Keeley D.L.C. No 41
SE exterior "L" Cor. Renew Cor from stump
of original BJ and Mark

A W Fir in dia 765°E 8 lks
NW Cor Cl 41 Renew corner from original
tree which is dead - Mark.

A fir 12" in dia S 79°45 E 68 lks
NE Cor Cl 41 Renew Cor from stump
of original BJ Set oak post from which

A Willow 7" in dia S 78°W 114 lks
SE Cor Cl 41 Renew corner from decayed
remains of original tree Set a fir post
and two rocks for corner - from which

A fir 30" in dia, brs 743 1/4° W 135 lks

NW Cor of Coats D.L.C. # 59 see page 114

SE Cor of Lathrop D.L.C. # 37
Renewed this cor from original B. 9 which
shows scribe marks on being chopped open
but is much larger than called for in field
notes Set an iron pipe 1" x 30" marked
a new tree a W Oak 8" dia South 14.7 ft.
U. Chutim 10" dia not marked bears East 05 ft.

NE Cor of of Lathrop Cl 37.
Set from stump of old B. 9 identified by
its position only, Set an iron pipe 1" x 30"
also cedar post from which
A Pine 16" dia S 30°00 W 9 ft.
A W Oak 42" dia S 14°00 E 438 1/2 ft.

F. J. Cole deputy.
Chas. Wilson
P. A. Gurney.
J. W. Gurney.
W. J. Gurney.
#30
#31
#32

Swain Co Surveyor
W. H. Coats
H. Deagh.
E. Richardson
February 1923
Witnesses

Feb 11 1923

T28, R8W,

N.T. Eppstein
N.D. Green
Henry Elphinstone
Sam M. Manfred

Set Corner of Section 29, 30-31 & 32
from old B.T. (the trees gone)
Marked New Trees as follows:
Fir 12" Bears N 50° W 32 feet
" 8" " S 43° W 7.8 "
" 8" " S 16° E 13.0 "
#35 " 10" " N 81° E 4.8 "

Harley Johnson
Mar 4 1930
B.A. Johnson
C. Fuller

1/4 Cor Between Sec 29-32
Set corner from old B.T. which were
badly rotten, Marked New B.T.
#36 R. Fir 10" N 42° W. R. Fir 6" S 41° W the

1/4 Cor bet 11 & 12 set 1 1/4" x 2' torus hat from one old B.T.
#37 30" Fir, Marked New B.T. { 16" W Fir N 44-30 W 96 feet
14" W Fir N 35 E 120 1/2 "

1/4 Cor bet 2 & 11 set a yew wood Post from old B.T. 36" cedar
#38 Marked New witness trees { 6" W. Fir N 65 W 14 feet
14 R. Fir S 80 E 19 1/2 feet

1/4 Cor bet 14 & 11 set ^{Dodge} Ford axle ~~Yankee~~ ^{Corner} ~~lost~~ ^{tree gone} ~~between section~~ ^{corner}
#39 Marked New B.T. { 30" Fir S 63 E 82 1/2 feet
12" Fir N 12 W 120 feet

1/4 Cor bet 10 & 11 set 3" x 3" x 30" oak stake from two ^{Oaks} O.B.T.
#40 Marks New B.T. B. Oak 24" N 26 W 73 feet

Cor 10 1/4 / 14 set a post for corner from O.B.T. in sec 14
#41 which had scribe marks, other trees in evidence
but cut down & partly burned.
Marked 12" Red Fir N 56-30 W 86 1/2 feet, ~~no~~ other
trees near, in other sections.

Cor 11 1/2 / 14 set Post for corner from old B.Ts, namely
a Fir S.W. & Oak N.E. Marked 5" Fir N 39° W
#2 52 feet for witness tree, ~~no~~ tree in the
other section near.

the two corners shown below renewed from orig. trees.

by A. Boyer
Ralph Heater, Wit.

1/4 Corner bet. Sec's. 35 & 36, set 1/2" galv. pipe & marked ^{the} following trees,
#3 18" White Oak, (New Tree) S 73-30 E 108.0' & a 36" Black Oak S 57° W. 42'. (New Tree)
orig. trees dead ^{and} abt. ready to fall.

1/4 Corner bet. Sec's. 34 & 35, 3" x 3" cedar Post ^{the} & marked following new
#4 trees, 18" wh. Oak S 51° E; 35 ft. & 30" Bl. Oak N 21° W. 49'. [orig. B.T.s = Rotten
heart = tree to SE. ^{and} dead wood in stump-hole = B.T. to S.W.]