

✓ 1/4 Cor. on South side Sec. 35

Renew from old bearing trees

1 1/2" x 30" J. P.

Set in ~~1 1/2" x 30" J. P.~~, from which

~~bearing trees~~ Old Gov. B.T.s. br.

6' 8" ~~br.~~ as given. Remark

S.E. Cor. of Cl. N^o 50 - O.K.

(T, 30-4)

Renew from Gov. B.T.s.

Set in 1/2" x 30" Gal. J. Pipe & 4" x 48" fir stake, fr. wh.

#9 G 10" Fir brs. S. 56° E 7 lbs.

G 10 " " N 88 1/4 W. 11 1/2 "

30-4

✓ 1/4 Cor. N. side Sec. 2

? This is (prob) evidently T 30 S R 4 W

30-4

Renew this corner from my own work. Gov. set no corner

#10 Set in 1" x 36" Iron pipe, from which

G 8" Fir brs. S. 45 3/4° W. 5 lbs.

G 20" Fir " N 45° W. 15 "

30-4

S.W. Cor. Sec 36

30-4
29

Renew this corner from old B.T.s.

Set in 1" x 36" I.P. & 4" x 48" cedar stake, from wh.

G 12" Fir brs. N. 13 1/2° E. 20 lbs.

#3 G 48" Cedar " S. 32° W. 9 "

N.E. Cor Sec. 25

? This is evidently T 30 S R 4 W

30-4

Renew this corner from old B.T.s

Set in 1 1/2" x 36" I.P., from which

G 40" W. Oak brs N 46° W. 56 1/2 lbs

G 10" W. Oak stumps brs. S. 76° E. 43 lbs.

On the 1/4 cor. on S. side sec 36, brs. East 30 lbs.

30-4

#11

C.W. Sprunger Deputy Co. Sur.
Marrison Safety H. Wilson A. Wilson C.G. Wilson
F. C. Frear Dep. Co. Sur.

T295 RAW.

Corner to Secs 4, 5, 8, 9.

Renew Corner from original BJs two of which I find standing viz A fir 36 in dia brs S 70° W 35 lks

A fir 10 " " " N 52° W 57 "

#4 Mark A fir 24 " " " N 81° 06 E 25 "

A W Fir 10 " " " N 80° 25 W 70 "

" " 12 " " " S 42° 20 E 27 "

#5 1/4 Cor bet 5 & 8 Renew from stumps of original BJs Set post from which.

An Alder 26 in dia N 88° 11 E 272 lks

" " 6 " " S 78° 09 E 35 "

Cor to Secs 5, 6, 7, 8. Renew from stumps of original witness trees from which A fir 36 in dia brs S 34 1/4 W 151 lks

#6 A Fir 42 in dia brs N 37° W 151 lks A fir 18 in dia brs N 39 1/4 E 36 lks A fir 16 in dia brs S 73° E 39 lks

corners of Secs 4-5-32-33. Renew from original trees two original trees do not check Set post from which original trees bear as follows A Fir 20 in dia brs N 70° 20 E 80 lks

A Fir 20 in dia brs N 82° 15 E 55 "

A Fir 42 in " " S 72° 30 E 125 "

" " 24 " " " S 172° 5 W 138 "

New tree a W Oak 5 " " " S 59° W -

#8 1/4 Cor bet 5 and 32. Renew corner from stumps of original Wit Trees Set charred post from which A Red fir 10 in dia brs S 39° 05 E 56 lks

" " " 5 " dia " S 28° W 60 "

Cor to 5, 6, 31, 32. Renew corner from stumps of original BJs Set oak post from which A fir 12 in dia brs N 37 1/2 W 106 lks

" " 12 " " " N 34 1/2 E 92 "

Pine 42 S 29 1/2 E 210 "

Fir 22 S 21 E 160 "

Frank Cain Co Surveyor

J J Cole

J J Black

W M Burdine

W H Lawrence

Witness

May 1915