

Jan 22, 1902  
Blair Shuring Dep.  
H.E. Richardson  
Phil Briggs  
Weaver } Wit.

NW Cor. D.L.C. No 38. Benj. Stephens.  
Boulder 4" x 10" x 20" long. Old BTs OK but  
badly rotted Blazed and scribed as New BTs  
10" Oak S 38° W 86 lks NWC38 GSBT  
12" " 562° E 58 " " " "

Aug. 24, 1908  
M.B. Allmond  
#18

1/4 Cor. Bet. Secs. 13-24 (F.B. No. 19 Page 41)  
W. Oak post 5' x 5" x 3'  
R. Cedar 5" S. 44 1/2° W. 22 1/2 lks.  
" Fir 8" N. 11 1/2° E. 24 "

Oct. 12, 1938  
Arthur Boyer, Dep.  
P.R. Weaver  
Mrs A.S. Fetterman  
Delbert Trask  
Ted Shellabarger } Witnesses

1/4 Cor. Bet. Secs. 24-25 (F.B. No. 19 Page 42)  
Yew post 4" x 4" x 3'  
W. Fir 6" S. 45° 12' E. 22 lks.  
Maple 6" N. 31° 48' W. 6 "

Oct 12, 1938  
A.B.  
Ted Shellabarger  
Delbert Trask  
Wit.

S.E. Corner Hans Weaver, D.L.C. 39, set from evidence furnished by P.R. Weaver and from remains of old fence: no evidence, except stump holes of orig. bearing trees, remains: Marked 8" Fir N. 33° E. 95. ft. and 6" Fir N. 86° W. 31.5 ft. and drove a 3/4" steel drive shaft for corner, on E. & W. fence line.

#51

N.E. Corner Hans Weaver D.L.C. 39, Found one of two Orig BT's (to S.W) a.k. BT. to NE dead: set 4x4 Oak post & one new BT. 8"W.O. N. 1° E., Bark Blaze 18.0"

Oct 18, 1938  
A.B.  
Ralph Schrader  
Ted Shellabarger } Witnesses

N.W. Cor D.L.C. 39 in Sec. 16: Orig. BT's Dead - Stump of orig. fir corner Tree still standing - New BT. 24" Red Fir, N. 87 1/2° W. 30. ft.

S.W. Cor. NW<sup>4</sup>NE<sup>4</sup> Sec. 16 : Note: In 1883 County Surveyor set this corner & marked one tree: this tree was cut down <sup>abt. 2 yrs. ago</sup> laying at stump, the scribe marks were cut out of stump and "cut off" tree: the corner, a 4x4 Cedar Post, was set from this stump and a new B.T., 18" Fir marked which is N. 62 1/2° W., 21.5 ft. - Bark Blaze "P.C. cs. BT.  
and " " " 15" Cedar " " " N. 38° E., 48. " " "

Ben B Irving Dep.

T29-4

This cor is just off <sup>N. of</sup> old fence line running East

set by Woods

Oct 18, 1938  
A Boyer, D.C.S.  
Ted Shellabarger  
Ralph Schrader  
witnesses

1/4 Cor. bet 9<sup>th</sup> & 16 - Both B.T.'s dead - Set Cedar post back in place from stump of fir B.T. <sup>256.0 ft</sup> down oak which Woods used in 1925 - Marked new trees for

#54 B.T.'s N. 26 1/2 E. 16" Fir

S 50 1/2 E. 314.3 ft 18" Alder, on Creek bank - Bark Blaze - a 4" x 18" Alder against this tree

Oct 12 1938  
A.B. Witsch  
Ted Sh. Delb. Truck

#55

Most easterly S.E. Cor. Lot 4, Sec. 16 Set 1883 by County Surveyor - found his

B.T. - "10" White Oak, N 46° 52' E 30 lks - Set a 4" x 4" Fir Post <sup>9<sup>th</sup></sup> cut out B.T. to Blazed Scribe marks

Oct 22 1938  
A.B. Witsch  
Ted Shell  
Ralph Schrader

#56

SE Cor NW 4 NW 4 Sec. 16, Set 1883 by County Surveyor - found his B.T. 12" w.o.

S 57° 08' W 2.81 chs. - cut out scribe marks <sup>9<sup>th</sup></sup> Set 4" x 4" Post for Corner, in open pasture

Ben B Irving D.C.S.  
Hit,  
N.E. Richardson  
Loren Weber,  
Dale Woodruff  
Oct. 22 1940.

#57

1/4 Cor on East Boundary of Section 24.

Iron pipe as set by F.C. Frear in 1918 in place, Fir 28 1/2 E 19 1/2 lks. as set by Frear cut & scar burned out of stump. Oak

S 15° 3/4 E destroyed cut & stump ~~burned~~ by Fire, stump hole and few roots only being visible. Pine S 20 W 2.10 chs cut & stump burned part of blaze still visible.

Set new bearing trees as follows:

A Fir 30 ins. diam., bears N 51 1/2° W 29.3 ft, mkd 1/4 S 24 es, B.T.

A Fir 30 ins. diam., bears S 33 1/2° W 142.7 ft, mkd 1/4 S 24 es, B.T.