

T. 29-6

Ext. NW Cor. Wm. Dooley D.L.C. N 43.

✓ Renew, by original B.T. decayed, marking plain.

Set an oak post 4x4x3 1/2 marked C 43 T 29 S R 6 W. C.S.

#2 a. Fir 16" in dia "C.S. C 43 T 29 S R 6 W. bears. N 71° W 36 Links

" " 12" " " " " " " " " " S. 58 1/2° W. 8 "

✓ Ext. NW Cor. no evidence of original B.T. at proper distance

Set fir post 4x4x3 1/2 marked C.S. C 43 T 29 S R 6 W. from which:

#3 A Fir 36" in dia marked C.S. C 43 T 29 S R 6 W bears N 67° 40' E. 86 Lks

" " 32" " " " " " " " " " N. 51° 30' W. 26 "

S.W. Cor. Renew by original B.T. decayed marking plain

Set fir post 4x4x3 1/2 marked C.S. C 43 T 29 S R 6 W from which

✓ A fir 50" in dia. marked C.S. C 43 T 29 S R 6 W. bears. S. 23 1/4° E. 55 Lks

#4 " " 20" " " " " " " " " " N. 23° W 79 "

" " 9" " " " " " " " " " S. 52 1/2° W 20 "

✓ S.E. Cor. Renew by original B.T. decayed and fallen down marking plain

Set an oak post marked C.S. C 43 T 29 S R 6 W. from which.

✓ a fir 14" marked C.S. C 43 T 29 S R 6 W. bears, N 56 1/4° E 15 Lks.

" " 17" " " " " " " " " " N 35 3/4° W 50 "

#5 Above corners, established in presence of.

E. J. Rice, S. S. Swickard and S. C. Meredith

Field Book no. 19 p. 35

A. D. Willis D.L.C. N 45

Interior S. Cor. post (fir) marked C.S. C 45 T 29 S R 6 W. from which

✓ a fir 12" marked C.S. C 45 T 29 S R 6 W. bears, S. 15° W. 49 Lks

#6 " " 30" " " " " " " " " " N 6° W 24 "

Notes: This corner found as described Jan. 24, 1929. Drove car along corner and remarked B.T. on Park. Stake + new cor. stake in middle of stone 2 1/2 dia x 1' high

✓ S.E. Cor. fir post 4x4x3 1/2 marked C 45 T 29 S R 6 W from which:

A maple 14" in dia marked C.S. C 45 T 29 S R 6 W bears. S. 20° W 8 Lks

#7 " " 36" " " " " " " " " " N. 72° W. 72 "

Corners Renewed by James Cairn

J. 29 S R 6 W. D.L.C. 43

A pt 28/29 1916

Bears Plunging
Dep. Co. 15411

T. 29-6

4x4x3/2

Sr. Cor postmarked C 45 T 29 S P 6 W from which;

a fir 48" in dia marked C 45 X bears S 70° W. 11 Lks

✓ Corners established in presence of O. F. Mills
Frank Rayer and Elias Mills

Note - Corners renewed by original B.T.s,
where found, and in other case at proper
distances. See Records of Surveys vol 2 p 201

T 29 S R 6 W
D L C 45

Corn Renewed by
Frank Cairn
Feb 19 - 1915
#8

✓ Cor. Secs 11-12-13-14 - Renewed as per Old B.T.s

✓ by setting a 3/4" x 36" I. Bar from which
an 8" W. Oak Brs N. 48 1/2° W. - 1.205 ch. C.S.B.T.

a 30" W.O. " N. 8° W. - 7.50 ch. Old B.T.

a 30" W.O. " S. 73 1/2° W. - 0.39 ch. " "

a 40" W.O. " S. 52 1/4° E. 4.00 " "

✓ 1/4 Cor. Between Secs. 13 & 14 - Set a 3/4" x 36" I. Rod

from which a 28" B.O. Brs. N. 83° W. - 6 1/2 Lk. C.S.B.T.

a 20" W.O. " S. 78° E. - 6 1/2 Lk. C.S.B.T.

Cor. 13-14-23-24 - Renewed from Old B.T.s.

Set a 1 1/2" x 30" Iron Pipe for Corner from which

a 6" W. Oak Brs. S. 84 3/4° E. 11 Lks. C.S.B.T.

a 4" W. " " N. 52 1/4° E. 8 " "

a 8" W. " " N. 42° W. 21 " "

a 6" Fir " S. 58 1/4° W. 14 " "

✓ 1/4 Sec. Cor. Between Secs 14 & 23 - Renewed from Old

B.T. by setting a 1/2" x 1 1/2" x 36" I. Bar from which

an 8" W. Oak Brs. N. 50 3/4° E. 2.60 ch. C.S.B.T.

a 24" Cedar " S. 19 1/4° E. 1.62 " C.S.B.T.

Cor. 14-15-22-23 - Re-establish from Old B.T. viz

a 30" W.O. N. 24° E. 5.00 ch. which I remark and

set a 1" x 30" I. Pipe and 3" x 36" Oak Stake from wh.

a 18" Fir Brs. N. 16° W. - 22 1/2 Lk. C.S.B.T.

a 12" " " N. 83 1/4° W. - 42 1/2 Lk. C.S.B.T.

a 24" " " S. 29 1/2° E. - 32 " C.S.B.T.

a 14" " " N. 44 1/2° E. - 40 " "

F.C. Fear Dep. Co. Surveyor

Fred Smith
Ora Pont

Witnesses

May 1919

#10
Lou Jorgenson

#13