

T. 29-6

J.C. Fearless Co. Surveyor
 Fred Smith
 Geo Rankin
 John Gargison
 Witness

May 1919

✓ 1/4 Sec. Cor. Between Dees 14 & 15 Renewed
 from Old B.T.s which I remarked and
 set a 3/4" x 36" G.I. Pipe for corner from wh.
 #14 a 8" Fir Bros. S. 69° E. - 10 Lks. C.S.B.T.
 a 5" W. Oak " S. 57 1/2° W. - 7 " "

✓ Cor. Dees. 10-11-14 & 15 - Renewed from Old
 B.T.s by setting a 5" x 5" x 40" Oak Stake from wh.
 a 10" Laurel Bros. N. 44° E. - 13 1/2 Lk. C.S.B.T.
 ✓ a 20" Fir " S. 62 1/4° E. - 18 " "
 a 20" " " S. 75° W. - 39 " "
 #15 a 12" " " N. 63 1/4° W. - 30 " "

✓ 1/4 Sec. Cor. Between Dees 11 & 14 - Renewed
 from Old B.T.s by setting a 1" x 36" G.I. Pipe
 from which a 8" W. Oak Bros S. 23° E. - 19 1/2 Lk. C.S.B.T.
 #16 a 8" W. Oak Bros. N. 35 3/4° W. 41 Lk. C.S.B.T.

✓ S.E. Exterior "L" Cor of J.S. Burnett D.L.C. No 42
 I reset from 30" W.O. - N. 41° W. - 150 Lks. Remarked
 and set a 3/4" x 36" I. Rod for corner from wh.
 #17 a 4" W. Oak Bros S. 37° E. - 52 Lk. C.S.B.T.

✓ S.W. Cor. J.S. Burnett D.L.C. No. 42 - Re-established
 from Old B.T. by setting a 3/4" x 36" I. Rod from
 wh. a 6" W. Oak Bros. West - 1 Lk. C.S.B.T.
 #18 a 6" W. " " S. 14° W. - 3 Lks. C.S.B.T.

1/4 Cor. bet Dees 25 + 26.

✓ A Maple 8" in dia Marked C 8 1/4 S
 ✓ from which a fir 30" in dia Mkd C 5 1/4 S, S 25, BT
 755 lks 14 lks.
 #19 A fir 16" in dia Marked. as above 789° W. 59 lks.

T29 S. R. 6. W.

Cor. to Secs. 25-26. - 35-36.

Renewed this corner from two original B.T.s the stumps of which remain this point was set at the intersection of the measurements given in the field notes. The bearings to the old B.T. stumps then bear as follows with a Variation of 21° 15' E.

N 56° W. 250.8 ft.

N 9° 45' E 487 "

New B.T.s properly marked bear as follows

Pine 40" in dia N 9° 45' W. 487°

" 40" " " N 2° 30' W. 485°

Fir 60" " " S 60° 45' E 377.8

out by " 18 " " S 1° 15' E 365.4

Set an Iron pipe 1 1/2" x 36" also a Cedar post 3" x 3" x 36"

#20 Erected Mound of Rock 2 1/2 ft high

Sec. Cor. 5-6-7-8.

Found 7 original B.T.s. Set at each tree and ran course and bearing as called for in notes. Points did not coincide so took the average of two for position of corner. Set I.P. from which 36" Fir S 38° W 286 feet 6" Fir N 72° W 150 "

#21 4" W.O. S 54 1/2° E 345 ft; 8" W.O. N 10° E 325 ft

T29SR7W.

Sec. Cor 6-7- 1-12. Find one B.T. and stump of other.

Set corner from these 7 B.T.s. I. Pipe from which

12" Fir bears N 15° W 130 feet; 14" Fir bears S 48° E 280 feet

#22 14" Fir bears S 14 1/2° W 412 feet; 36" Fir bears N 65° E 450 ft - original

Witnesses of J.W. Cole Deputy

Walter Aldrich J.D. Wolford

G.G. Stewart Deputy Dec. 8-1921 Ed Walker, Geo. E. Keller Chas Voyteke, witnesses

G.G. Stewart Dep. Geo. E. Keller witnesses Chas Voyteke