

T 29 S R 6 W

G. G. Stewart, Deputy
C. W. Malcomb witnesses
W. S. Greener

✓ NW cor. D.L.C. #42. Set 1 1/2" I. pipe with pile rocks around it.
#31 Set from stump in grain field; and checked by SW cor Cl 40.
Marked 18" Balm N 4° W 197 1/2 ft.

✓ 1/4 Cor bet. 7 and 11. Set from Two O.B.Ts, one fallen
and other marks destroyed; set pointed rock + marked
#32 12" B.O. S 76 1/2° W 60 ft. 10" W.O. N 12° W 22 ft.

W. C. Co Surveyor.
E. Richardson chain
H. E. Beegh.

✓ 1/4 Cor. bet. Secs. 16 + 21
Renewed this corner from 24" Oak B.T.
which is alive, standing and bearing
scar. but I did not open it.
Set a cedar post for corner.
and erected a mound of rock 3 ft dia
and 18 in high from which original
#33 B.T. bears S 11° W 111 ft.

✓ NE Corner of A. G. Willis D.L.C. #45.
Renewed corner from old rotten
oak stake marked. C.S. Cl. 45 from.
which stump of 30" fir bears N 10 W 25 1/2
marked B.T. also.

a fir 14" marked. C.S. Cl. 45 B.T.
N 49° 30' W 7 ft.

a fir 14" mark. C.S. Cl. 45 B.T. S 41° W 146 ft.

both firs look as though they had
#34 been marked approx 5 years previous
Erected mound of Rock around old stake
The 1/4 corner bet. 16 + 21 bears East 430 ft
and South 121.4 ft.