

T 295 R 7 W.

✓  
#13  
Cor. of Secs 2-3-10-11

Renewed this corner from the original B.P.  
Set a sand stone 8" x 10" x 15" with cross on  
top and west sides from which

A W Oak  $N 15^{\circ} E$  40.9 ft. alive and bearing scars

" " "  $N 42^{\circ} W$  33.0 ft. " " "

" " "  $S 23^{\circ} W$  69.5 ft. " " "

B Oak stub  $S 6^{\circ} 00' E$  148.5 ft. (dead.)

✓  
#14  
Cor. to Secs <sup>31-32</sup> 34-35-56  $N$  body of T 295 R 7 W.

✓  
I located this corner from the facings  
of the original B.P.s as they were all very  
close to the corner but did not check  
for distance and direction.

Set an <sup>Fir</sup> Oak stake and raised mound of  
earth around stake from which the Orig B.P.s

A B Oak 12" in dia with scribe marks visible

bears  $N 85^{\circ} E$  5.0 ft.

B Oak 14"  $S 28^{\circ} W$  6.0 ft. scribe marks visible

B Oak 12"  $N 48^{\circ} W$  8.0 ft. " " "

" " 12"  $N 22^{\circ} E$  12.0 ft. " " "

I marked new trees as follows

A Fir 14"  $N 72^{\circ} 30' E$  17.0 ft.

A Fir 10"  $N 3^{\circ} 30' W$  12.0 "

" " 10"  $S 65^{\circ} W$  18.0 "

" " 12"  $N 25^{\circ} W$  16.7 "

✓  
#15  
Cor. to Secs 13-14-23-24.

I found stakes nearly decayed and  
erected mound of Rock 24" in dia 18" high  
from which original trees

A Fir 24" in dia  $S 66^{\circ} E$  29.6 ft.

A Fir 24" " "  $N 13^{\circ} W$  33.0 ft.

A Fir 28" " "  $S 74^{\circ} W$  17.1 "

T 29 S. R. 7 W

Also Continued on Page 175.

Continued on Page 196

✓ Cor. to 1-2-11-12

✓ Set an oak post also Gas pipe <sup>Set Gun 1 1/2" x 36"</sup> from which

A W. Oak 12 in dia ~~N 29° W 2630~~ ~~N 28° 30' E 2838~~

#16 " " " " 9" " " S 22° W 12.5 ft

A W Oak 30" S 80° 15' E 225.5 ft

A Rock Ledge mkd. S1, C8, B0, N 8° 30' E 2838

✓ 1/4 Corner between sections 1-12

Set an iron pipe 1" x 36" also Cedar post 4" x 4" x 36

#17 from which A Maple 12" in dia S 76° 30' W 10.7 ft

A B. Oak 8" N 43° W 27.0 ft

#18 ✓ 1/4 Corner bet Secs 2-11

Set an oak post and a rock 6 x 6 x 12" <sup>also Gun barrel</sup> marked

1/4 S. C. S. from which

A Fir 18" in dia Bors S 70° W 17.2 ft

" " 12" " " S 57° 30' E 22.0 "

✓ 1/4 Corner between Secs 1-2

✓ Set a Fir post 4" x 4" x 30" from which

#19 A Fir 30" in dia brs N 30° E 30 ft

A Fir 18" " " " S 86° W 27.5 "

Cor Sec 3-4-9-10

✓ Set corner from old tree, scire mark

#20 plain on B. Oak, Laurel tree in good condition

30" fir in good condition set 4" x 4" x 3'

Laurel post. Marked trees thus

Laurel 20" N 65° E 24.5 feet old tree

Fir 4.8" N 53° W 16.2 feet old tree

Fir 9" S 43° E 33 feet New tree

Fir 15" S 55° W 27.0 " New Tree.

H. Eppstein, SUR.  
Geo Spaur  
J. K. Falbe } wit  
Ed Jennings

MAY 9-1926

Ben Bohning 5-12-27  
Jas Brown  
Bill Sappard } wit.  
Gene Elliott

1/4 Sec. Cor. bet. Sec 32 T28SR7W + Sec 5 T29SR7W.

Identified by an O.B.T. Oak N 40° W 27.7 ft and Laurel S 53° 10' E 35.0 ft

#21 Set 5" cedar Post and marked new B.T. Fir 20" S 78° 45' W 51.3 ft.

Gordon Stewart previously used this as a corner. There is

also a corner set by Cain for 1/4 Cor. Some 800 ft E and 130 ft So.

Some property owners have been claiming each corner. I believe this to be the corner as originally set by "Ford" but have not gone into it sufficiently to prove.

Do not know of Cain's corner until after setting this one.