

29-9

Sub. 13-1920  
J.W. Cole deputy  
P.D. Wolford clerk  
#13

Cor to Secs. 13 + 24 - 18 - 19

Set Rock 6 x 8 x 14 bears from which

A Rock 6 x 8 x 14 bears East 17 ft.

" " " " " West 22 ft.

#14

SW Cor. D.L.C. 37 Set from original B.P.

Set a 1/4" x 36" iron pipe for cor.

E. S. Stewart  
deputy  
May 22-22  
W.S. Craven  
J. J. Kennedy  
witness

~~Cor to 36-25-30-31. 1/4 cor between Secs. 36-31~~

Renewed O.B.T.s marks, set Iron pipe for corner

T.30 SR9.W Referred From Page 157

1/4 Cor Bet Sections 9 & 16 Set from original

B.T. Rock 6 x 8 x 14

W. Oak 12" Dia	S 27° E	30 3/4	Links	} Old Original
Fir 24" Dia	N 2° W	20	Links	
Fir 14" Dia	N 40° E	18	Links	
Fir 24" Dia	S 21° W	22	Links	

H. F. Pyper  
County Surveyor  
May 22-1943  
witness  
J.C. Smith  
B.A. Lane

T 29 S - R 9 W

1/4 Sec. Corner South side Sec. 36. set midway between S.E. & S.W. corners

2" Flue pipe from which 30" Fir bears S 55° W 46.5 ft & 12" Fir brs. N 18° E 40.0 ft.  
Orig B.T.s could not be found; the above trees are new ones

Feb 26, 1943  
A. Boyer, dep. sur  
J. N. Nelson  
J. W. Priest  
witness

Feb 24, 1943  
A. Boyer dep.  
J. N. Nelson  
J. W. Priest  
witness

SW Cor. Sec 36, Renewed from two stumps of orig. witness trees in Sec's

35 & 36. which were found, both being at top of cut for highway - Set a 4x4"

Post for corner from which the following newly scribed trees bear, a 13" Maple

N 5° W 34.5 ft., 12" Fir S 42° W, 2° & 24" Fir N 72° W, 34.5', measurements made on slopes.

#17