30-1

Frank Cain Dep. C. Surveyor
Recorded by F. C. Frear County Surveyor
Nov. 24. 1920

#1 Cor. 9-10-15-16 - Renewed and Post Set from which.
a Pine 36" bears S. 40½° E. 51 Links
a Fir 10" " N. 89½° E. 59 "
No Trees in West all burned

#2 ¼ Sec. Cor. Secs. 15 & 16 renewed by setting a rock
from which a Pine 10" bears N. 73°-35' E. 143 Links
" " " " 8" " S. 57°-05' W. 144 "

#3 ¼ Sec. Cor. Secs. 14 & 15 renewed by rock 6"x8"x12" on a
true line and at 41.09 ch. being a pt. equidistant
from and between Section Corners.
from which a Yellow Pine 42" brs. S. 83° E. 163 Links
" " a Cedar 30" brs. N. 89°-35' W. 226 "

Ben B Irving D.C.S.

T. 30 S. R 2 W.

1/4 Sec. Cor. South Boundary of Sec. 30.

Rock in a mound of stone - Original bearing trees 6" Alder N 70½°W 24 lks - Marked visible but not legible - 10" dogwood N 17°E 36 lks. dead but scribe marks clear. Marked new B.Ts.

#15 10" Hemlock, bears N 33°W 29 lks. Marked 1/4 S 30 C,S,B,T.
10" Fir, bears N 62°E 41 lks Marked 1/4 S 30 C, S, B, T.

Note 1/4 Cor. North Boundary of Sec 31 as described Govt. field notes & in good conditions 9-24-1940

Sec Cor Secs. 22-23-26-27

Location identified from original bearing tree, 24" Fir S 28°E 44 lks - chopped out - scribe marks partially legible - 60" pine down & burned. - Checks original bearing & distance.

#16 Drove 1½" x 1½" x 60" angle iron 30" in ground for Corner & surrounded with a mound of stone from which
A Fir 20" diam. bears S 60 W 19 lks marked T 30 S R 2 W. S 27 C.S. B.T.
" 8" " " S 27 E 63 " " " " " S 26 " "
" 32" " " N 12 W 37 " " " " " S 22 " "
" 24" " " N 15 E 38 " " " " " S 23 " "

1/4 Cor Bet. Secs. 22 & 27.

Location identified from one original B.T. scribed 1/4 S.

Drove 1" x 36" Iron pipe 36" in ground with 2" x 4" Oak stake alongside for Corner from which

#17 Cedar 26" diam., bears S 25°W 13 lks. marked 1/4 S 27 C.S. B.T.
Fir 6" " " North 5 lks. " 1/4 S 22 C, S, B, T.

1/4 Sec. Cor. Bet. Sec. 22 & 23

Location identified one Original B.T. down & rotten but scribe Marks legible.

Set a stone 4" x 7" x 16" marked x 1/4 for Corner from which.

#18 Fir 16" diam. bears N 39°E 47.3 lks marked 1/4 S 23 C.S. B.T.
Fir 16" " " S 31°W 39 lks " " " S 22 " "

Sec. Cor. 13-24 - T 30 S R 2 W; Sec 18-19 T. 30 S. R. 1 W.

Location identified from Original B.Ts. 24" Fir N 56¼°E 31 lks partially visible & 12" Fir S 79½°W chopped out B.T. which is very plain

Set a stone 6" x 8" x 18" for Corner from which.

#19 Fir 20" diam., bears S 53¾°E 14.8 lks. marked T 30 S R 1 W S 19. C.S. B.T.
" 18" " " " S 79½°W 19 lks " " T 30 S R 2 W S 24 " " original B.T.
" 24" " " " N 56¼ E 20 lks " " T 30 S R 1 W S 18 " "
" 24" " " " N 62½°W 48 lks " " T 30 S. R 2 W S 13 " "

1/4 Sec. Cor. 13-24

Original Corner obliterated

Set a Rock 6" x 9" x 20" marked x 1/4 for corner with cedar post 6" x 6" x 48" alongside midway between Cor 13-24 T 30 S R 2 W; 18-19 T 30 S R 1 W and 13-14-23-24 T 30 S R 2 W from which

#20 Fir 20" diam., bears N 48°W 6.7 lks. marked 1/4 S 13 C.S. B.T.
" 36" " " S 10 E. 41 lks. " " S 24 C.S. B.T.

Sec Cor. 13-14-23-24

Location Identified from one Original B.T. which is down but scribe marks legible & 2 other which check for bearing & distance but marks obliterated.

Set cedar Post in field for corner from which;

#21 Oak 16" diam., bears N 55½°W 100. ft. marked T 30 S R 2 W S 14 C,S,B,T.
" 14" " " N 2°E. 46.6 " " " " S 13, " "
Fir 24 " " S 74°W 118.4 " " " " S 23. " "
No Tree near S.E.

Ben B Irving
Witness
N E Richardson
Loren Weber
Y, 16-E, 55
8-2-'40
D.C.S.