

Witness { wh 12 days
 Set by Germond June 9-26. Field notes
 Stanley Road
 #22
 N & E of Co. Sum.
 #23
 #24

Section corner 28-29-32-33 Set 4"x4"x30" hard
 Post from 3 old B.T.s.

Marked Bearing Trees as follows.

- 36" Fir N 39° E 81 lbs
- 20" " N 65° 30' W 72 lbs
- 24" " S 50° W 7 lbs old B.T.
- 30" " S 72° E 16 lbs

Cor. Secs. 24, 25, 19, 30. 1" x 36" Bar. For Cor. on Range Line
 Witness Trees; An Oak, 15" N 45° E 59 lbs?
 " " 15" S 74° E 56 "
 " " 15" S 54° W 37 "
 " " 18" N 38° W 1.41 ch?

C.C. of 19418 Secs. Post 4" Sq. 2.12 ch North of Cor 24 & 13 in T30-3
 From which, Fir 15" N 78 1/2° E 29 lbs.
 " 24" S 55 1/2° E 28 "

Witness {
 #25
 M. Richardson
 J.D. Loffer
 Parker

1/4 Sec Cor 28/33

Corner location identified by a stone 6x8x14" and
 two OBT's, OBT's down and burned out no numbers
 or scribed marks visible. Mr - Parker claims to have seen
 numbers on one of the trees before fire of last year.

Marked stone "X" on top and 1/4 on South face.

- 16" Pine N 65° 30' E 78.8 ft blazed & scribed T30SR24 1/4 533 CSBT
- 24" Fir S 77° 45' W 99.5 ft " " T30SR24 1/4 533 CSBT

Witness {
 #26
 M. Richardson
 Walter Larnell
 Fern Larnell

1/4 Sec Cor 28/27

Location identified from both original BTs as described
 original government field notes. both trees have fallen down
 and decaying rapidly.

Set a 2 1/2" x 18" Iron Pipe for Corner with a serpentine rock
 6x10x18" along side and marked 1/4 S on South face.

- New B.T. Pine 30" dia. N 38° W 32.5 ft. blazed 1/4 228 CSBT
- Fir 30" dia N 40° 40' E 37.0 ft " 1/4 227 CSBT.

Arthur Boyer Dep. Co. Sur.
Geo. Stone } Wit
Mr " sr.
Jan. 31, 1939.

1/4 Corner bet. Sec 30, T30S; R.2W., & Sec. 25, T.30S., R.3W. No trees standing corresponding to Brg. Trees in G.L.D. field notes: set steel auto axle, gear on top, mid way, & on line bet N.E. & S.E. cor's sec. 25, from which 54" Fir, scribed on bark, bears N47 1/2° W. 41. ft. " " a 10" fir bears S49° E 29.7 ft, ^{measured} on slope, - 54" fir mkd. 1/4 S 25 T30S., R3W., C.S. B.T. No trees standing convenient for a B.T. in Sec. 30, so marked 10" fir same as 54" fir. Found a 12"x22" x 28" Granite Rock set in ground as if for a quarter corner but no chiseling was eligible, this rock bears from the established corner S. 58° W. 5.6 ft.

Arthur Boyer Dep. Co. Sur.
Geo Stone } Wit
Donald " }
Jan 30, 1939

S.W. Cor. Sec 30 (Corr. Cor) Map tree to S.E. gone " " rock orig. set for cor. loose " " out of place. set a 3/4" pipe from Maple tree to the N.E. " " put rock back in place as well as possible " " marked a new B.T. 12" Maple S41 1/2° E. 38 ft.

marked CC S 31 T 30 R 2 C.S. B.T. ~~####~~

Sec. Corner to Secs. 27-28-33-34
Location identified from Original B.T.s a Fir 24" diam. S 20° E 25 lks scribe marks partly visible
Set a Rock 8"x8"x20", 16" in ground, marked x on top, 1 notch on South, 3 notches on west, 5 notches on North & 3 notches on East corners, from which;

#3
Fir 30" diam., bears S 53° W 47° ft Marked T30S, R2W, S 33, C.S. B.T.
" 36" " " " S 33° W 42 2/3 " " " " S 34 " "
" 20" " " " N 43 1/2° E 29 1/2 " " " " S 27 " "
" 30" " " " N 37° W 20° " " " " S 28 " "

Sec. Cor. Secs 23-24-25-26
Location identified from original bearing trees.
A 72" Pine N 33° W 50 lks., A 24" Fir (down) S 74° E 46 lks, A Fir 24" (down) N 4° E 75 lks all bearing scribe marks partly legible.
Set Rock 8"x8"x18"-12" in ground, in mound stone, marked X on top - 7 notch East - 2 notches South, 5 notches West & 4 notches on North from which.

A Sugar Pine 8" diam., bears S 80° W 45 1/2 ft Marked T30S R2W S 26 C.S. B.T.
FIR 30" " " N 4° E 74 1/2 " " " " S 24 " "
FIR 6" " " S 34 1/2° E 42 1/2 " " " " S 25 " "
Pine 72" " " N 33° W 33 1/2 " " " " S 23 " "

1/4 Cor bet. Secs 23-24.
All signs of this corner has been obliterated an location falls in a wash. Established new corner mid-way between Sec Corner 13-14-23-24 and 23-24-25-26

Set a stone 8"x8"x22" marked X on top and 1/4 S on south face 26" in the ground with a stone 6"x8"x24" similarly marked on top & surrounded by a alongside marked 1/4 S. C.S. S 23 - S 24 from which:
Oak 8" diam., bears N 15 1/2° W 87 1/2 ft. marked 1/4 S 23 C.S. B.T.
Cedar 18" " " " S 24 1/2° E 94 1/2 " " " 1/4 S 24 C.S. B.T.

V 16 - E 55
Ben. B. 17V179 D.C.S
Wit E Richardson.
Loren Weber.

#5
9-26-1940