

Witnessed by  
Joshua Wright  
Chas. Drumont  
Henry Hartson

Reset 1/4 cor. on line bet. sec's, 27 & 28 T. 30 S. R. 3 W.

One old Gov. witness tree in evidence.

1/4 corner is S. Stone 4" x 8" x 24" marked 1/4 S. from which

a Maple 13" dia. hrs. S 30° 30' E, 32.4 ft

a Maple 10" " " S 67° 00' W. 15.0 "

Trees are marked 1/4 S 27 and 1/4 S. 28

Dec. 29-30 1916 M. B. Gummoud Co. Sur.

Witnessed by  
Joshua Wright  
Chas. Drumont  
Henry Hartson

Reset 1/4 cor. on line bet. sec's, 28 & 29 T 30, S. R 3 W

One old Gov. witness tree in evidence

1/4 corner is W. Paraphery Stone 9" x 10" x 20" from which

a. B. Oak 6" dia. hrs. S 2° 30' W 155.1 ft

a. Maple 12" " " N 7° 25' W 176.3 "

a. R. Fir 36" " " N 15° 00' E 148.5 " Original tree

U. S. G. S. B.M. Elev. 911 S 82° 40' E 28.2 "

Trees are marked according to the Statute

Dec. 29-30, 1916 M. B. Gummoud Co. Sur.

F. C. Frean & Co. Sur.  
Newman and Horton W.A.  
Nov. 1918

Reset "L" Cor. of Q. 37 per old B.T's

Set in a 2" x 36" G.I.P., from which

a 12 in. Alder hrs. S 62 1/2° E. 0.77 ds. Q. 37 C.S. B.T.

Frank Cain & Co. Sur.  
Recorded by F. C. Frean  
Co. Surveyor. 11-23-1920

NE  
N.W. Cor. of D.L.C. No 37

Renew from old B.T's.

Set in a 2" x 30" cast Iron pipe, fr wh.

old Gov. trees unmarked still stand

Cor. Dees. 26-27-34-35 Renewed with Fir Post

from which a Pine 14" hrs. S. 83 3/4° E. 131 1/2 Links

a W. O. 16" " S. 24 1/2° W. 234 "

a Cedar 12" " N. 80 1/2° W. 70 "

a Pine 42" " N. 32° E. 179 "

W. Oak 14" " S. 10° W. 26.8 Feet

Mound of Rock

E. G. Howard, Deft.

MAY 4. 1927

Feb 14 1939

E.G. Howard, Dep.  
V.N. Poole  
J. Davenport } witnesses

Reset 1/4 cor 30 & 31. Found yew post scribed 1/4. B.Ts  
gone. Location pointed out by V.N. Poole. Set I.P. for corner  
marked New B.Ts. 16" Maple N 69° W 24' ft 30" Fir S 46° E 60' ft  
#6 2-17-30- Found as noted- Orig. B.Ts one burned out other down and rotting.  
Check O.F. B.T. Howard Dep.

✓ a. S. E. cor. D.L. E. 38 Set from Old Bearing Tree  
Set a 1/2" x 24 Iron Pipe, Marked New Bearing Tree  
as follows 24" Fir S 10° E 18 Feet 20" Fir  
S 75° 30' E 17 Feet

✓ S. W. cor. D.L. E. 38 Set from Old Bearing Tree  
Set 4" x 4" x 36" Yew Wood Post Marked following  
B.Ts 14" Fir S 85° W 82 1/2 Feet 30" Fir  
S 88° 30' E 243 Feet

✓ Sec. cor. 5-6-31-32 On Township Line  
Set 4" x 4" x 36" Oak Post From one old B.T.  
Marked New B.Ts  
Fir 30" S 66° W 24 1/2 Feet  
#9 30-3 Fir 15" S 30° E 32 1/2 Feet

May 4, 1927

H.L. Epplein Co. Surveyor.  
Henry Raehor  
Bill Raehor  
B.A. Sam  
John Bumbach } witnesses

✓ Sec. Cor 30-31 - Location identified from 3 Orig. B.Ts  
which I rebloze and scribe in the bark. Set a 8" x 6" x 24"  
white Quartz rock for corner and Yew Wood Post alongside  
3" x 6" x 24" scribed S 30 CS on NE face and 8 30 SR 3 W S 31 on  
SE face

#10

✓ 1/4 Corner 19/30 location identified from both orig. B.Ts  
as recorded. NE tree down. Set a fir Post 4" square x  
36" long for corner. Remarked Orig. BT standing and  
a fir 14" dia. N 53° E 65 lks 1/4 S 19 CS BT.

#19

✓ 1/4 Sec. Corner. W. side Sec. 30- Location identified  
to Orig B.Ts as recorded. One only a stump the other  
dying. 4" x 4" x 36" post for corner - Blazed and scribed  
Fir 22" dia N 65° E 63 lks and Fir 30" dia S 80° E 80 lks 1/4 S 30 CS BT

#11

Feb- 18 & 19 1939

Chas B. Shering Dep. Co. Surv.  
John A. Irving  
V.N. Poole  
J.C. Wright  
Walter Poole } witnesses