

T 305-R9W

Done during - June 21-25 1927  
 Lobna Sutherland } Witnesses  
 Herman Sydellot  
 T.L. Clinton  
 Hyde

✓ 1/4 Sec. Corner between Secs. 3+4.

Identified by old fir snag, N46°W 10 lks bearing scribe marks and stump (rotten) probably other B.T. as it checks both bearing and distance.

Set 4" Cedar Post for corner and mark as new B.Ts.

28" Fir S 36° 10' W 10<sup>1/2</sup> ft

22" " N 26° 25' E 11<sup>3/4</sup> ft.

✓ 1/4 Sec. Corner between Secs. 4+5

Identified by portion of original Post<sup>mkd 45</sup> and hole where it set also by 10" Hemlock S 43° 30' E 15<sup>3/4</sup> ft  
 10" Hemlock N 74° 45' W 13<sup>1/2</sup> ft. One of these B.Ts was only a rotten snag bearing scribe marks.

Set 4" Cedar Post for corner marked a new B.T 10" Hemlock S 43° 15' E 13<sup>1/2</sup> ft.

✓ N.E. Cor. Sec. 3. Identified by old cedar post. scribe marks rotted off, and

✓ 1/4 Sec. Cor. Between Secs. 9+16

See Page 138