

Oct 5, 1928
 Wm. N.E. Richardson
 J.A. Bachman
 Harry Young
 H. & E. Eppstein
 Co. Surveyor

✓ $\frac{1}{4}$ Corner Between Sec 10-11 Set Corner
 by placing same $\frac{1}{2}$ way between
 dead corner on line. This corner was
 gone old W. Trees having been burned
 set stake & mound of rocks marked New Wit.
 Trees as follows 14" Fir S 35° E 55 feet
 14" Cedar S 33° W 38 feet.

✓ Corner 10-11-14-15 set oak post & iron off stone
 mound of rock, from old Cedar Wit Tree, have
 marks plain, Pine gone, Fir stump in evidence
 Marked New B.T. 36" Fir N 22° E 51 lbs
 15" Fir S 80° E 59 lbs; 12 Pine S 28° W 59 lbs; 7" Cedar N 11° W

✓ 3-2-10-11 set corner where California Oregon Power Co.
 had iron stake, which tallied out with oak tree
 on which I. S. Barrow, said "he had seen scribe
 marks but were burnt out at this time, Pine
 South, East was in evidence & also Oak S.W. set
 for corner 4" x 4" x 4" Oak Post and marked
 New Wit Tree 20" Fir N 15° W 88 lbs; 12" Fir
 S 79° E 81 lbs; 5" W. Oak N 38° E 45 lbs; 15" Fir S 31° W 133 lbs

✓ $\frac{1}{4}$ Cor. of 11-12 set stone with $\frac{1}{4}$ 5 old B. Trees
 still standing but scribe marks rotted out
 Marked New B.T. 15" Fir S 64° W 82 lbs; 8" Fir S 38° E 53 lbs

✓ $\frac{1}{4}$ Cor 2-11 found of Pine Tree at corner
 & one Wit Tree N.W. set Post & marked New B.T.
 24" Fir N 74° W 24 lbs; 10" Fir S 36° E 44 lbs.

✓ $\frac{1}{4}$ 11-14 set New wood Post. from
 Old Bearing Tree & marked one New Bearing
 Tree 14" W Fir N 51° E 10 lbs.

Rem. of Survey Dept. Co. Surveyor

Jan-12-21 1931 *Remond Shering* Dept. C Survey

NE Richards
 B.A. Lane
 F.L. Thomas
 } witness

✓ Cor. $\frac{11}{14} \frac{12}{13}$ Renewed from 3 OBTs. in good condition. Conglomerate Rock 6x8x16" - 8" in ground
 New BT 8" Fir N 37° 50' W 53 lks. scribed T31SR2WCSBT⁵¹¹
 OBTs as recorded in Orig. Gout field notes.

24" Pine S 24° W 72 lks.

15" Oak (now 20") S 75° E 7 lks. remarked.

24" Fir (now 30") N 45° E 44 lks remarked.

✓ 1/4 Sec Cor 13/14

✓ Position identified from one OBT badly rotted scribe marks still visible position of other OBT identified by rotted stump

Set sandstone 6" x 12" x 14" long 12" in ground for corner - chiseled 1/4 on top.

Fir 14" dia N 49° E 14 lks mkd. 1/4 S 13 CS BT

" 26" " N 62° W 25" " 1/4 S 14 CS BT

✓ 1/4 Sec Cor 12/13

Position identified by one OBT in good shape which was chopped out. scribe mks. legible well preserved. S 38° E 83 lks.

Set Sandstone 8" x 8" x 16" - 14" in ground for corner marked 1/4

12" Fir S 22° 40' W 43 lks 1/4 S 13 CS BT

14" " N 21° 20' E 50 lks 1/4 S 12 CS BT

✓ 1/4 Sec Cor 13-24

Position identified by mound of rock and both Orig. BTs.

Set a sandstone chiseled 1/4 for corner and surrounded with mound of rock remarked OBTs.