

see P<sub>6</sub> for T<sub>31</sub>-3

# T. 31-4

Recorded by  
J.P. Frear  
County Surveyor  
3-7-21

1/4 Sec post between secs, 27 & 34 T<sub>31</sub> S. R 4 W.  
set galvanized iron pipe 1 1/2 in dia, for 1/2 post

From which:

A fir 60" in dia bears, N. 91° E. 55 links  
" " 36" " " " N. 37° W, 93 "

Renewed in the presence of H. Meranda, Levi Spaulding, Paddy McGinnis and Jim McGinnis.

Jan 28, 1921

Set by Frank Cain  
Oct. 20-1922  
Recorded by G.G. Stewart  
Harvey A Brown,  
Levi Spaulding witnesses

1/4 Cor bet 28 & 33: Set from B.T.s. decayed but markings recognized; Set 6x8x10 boulder marked "X"; below boulder is 3/4" Iron Pin, also old stake marked 1/4 S.

38" Fir N 110 3/4 E 145 1/2 links; W. Fir 40" N 21 1/2 W 168 links

Corner section 26-27-34-35

Set 4" x 4" - 36" Oak stake from old B.T., which were all in good condition

B.T. One. A Fir 14" N 75 E. 39 1/2 k. Cedar 12" S 40 E 35 k.

A Fir 40" S 35 W. 51 1/2 k. Fir 16" N 62 W 36 k.

Corner 27-28-33-34

Set a 4" x 4" x 5' stake from 3 old B.T.s

and marked B.T. Fir 12" N 24 E - 20 1/2 feet

old Fir 12" N 51 W 9.5 feet Mark Plain on this tree

Fir 20" S 76-30 E 21.3 feet; Fir 24" S 66 W - 36.5 feet

2 old handwrit in evidence but marking bears out

Note above

1/4 Sec Cor bet Sec 28 & 33 Located at fence corner from B.T.s as described by Co. Surveyor in 1909

Both trees broken off & in poor shape. Marked New B.T.s

Fir 6" dia. N 28° E 51 1/2 k. Marked 1/4 S 28 C.S. B.T.

Fir 10" diam. S 18° E 69 1/2 k. Marked 1/4 S 33 C.S. B.T.

1/4 Cor bet. sec 21 & 28 Set Yew Wood Post 4" Dia & 36" Long, 12" in ground from B.T.s. as described in

Government Field Notes, One tree broken off & rotten post scribed 1/4 S C.S. on E Face; S 21 on N Face, S 28 on S Face.

New B.T.s Fir 22" dia. N 38° W 51 1/2 k. MK. 1/4 S. 21 C.S. B.T.

Fir 32" dia. S 67 1/2° E 58 1/2 k. Marked 1/4 S, 28 C.S. B.T.

Set Nov. 10, 1927  
by Ben B. Irving  
Witness { N.E. Richardson  
N.H. Haskell  
E.H. Bushman  
Leaves out.