

✓ Closing Section Corner Secs 1 & 2.

Location identified from Original BTs as described in government field notes. 12" Fir ~~544~~⁵⁴E 41 lks - 12" Fir N 85° E 54 lks. Pine 536° W cut for wood but scrite marks visible on stump. Blazed and scribed for new BT 12" Fir 532° W 46 lks T 335 R 56 S 2 C 5 BT. C.O. Garrett had driven a 1/4" iron pipe for corner. All original BTs reblazed and scribed.

June 10 1930

✓ Closing Section Corner Secs 2 & 3

A rock 6" x 8" x 6" above ground original corner as described Original BTs in good condition as follows

8" Fir (now 12") N 70° E 33 lks. - 12" Fir 562° E 8 lks and an 8" Madrona (now 12") 568° W 8 lks. I reblaze and scribe all BTs.

June 11 1930

✓ Closing 1/4 Sec. Corner Sec 2.

Placed on township line midway between section corners. Drove 1/4" x 42" Iron Pipe 3/4" in ground for corner. 6" x 8" x 60" New Wood Post alongside scribed CC 1/4 S 2 on South face and C 5 on North face.

June 11 1930

20" Fir South 73 lks blazed and scribed CC 1/4 S 2 C 5 BT
20" Fir 558° E 64 lks

✓ 1/4 Sec. Corner Secs. 1 & 2.

Rock (serpentine not basaltic) as called for in govt field notes. Original BTs alive and in excellent shape.

30" Sugar Pine N 41° W 39 lks - 10" Fir 539° 30' E 91 lks.

June 12 1930

Dennis J. Shuning Dept. of Surveyors

witness Frank Kruse
NE Richardson

Don Richardson
 Dep to Surveyor
 NE Richardson
 Frank Kruse } witnesses

June 23-1930

June 23 1930

✓ 1/4 Sec. Corner Secs 1-11

5" x 8" x 6" above ground Granite boulder as described in govt. field notes. Orig. BTs in excellent condition one having been chopped out scribe marks legible. Reblazed and scribed in bark both trees. 24" Fir (now 32") N 27° 30' E 53 lks.
 24" Fir (now 32") S 41° W 44 lks.

✓ 1/4 Sec. Corner Secs 2-3

6" x 12" x 6" above ground slate (or schist) stone as described in govt field notes. BTs in good condition, did not chop out but reblazed and scribed
 12" Fir (now 18") N 30° 45' E 149 lks.
 30" Sugar Pine (now 34") S 36° 30' W 112 lks.