

J.W. Cole Surveyor
E.H. Bahnert Chain
Dec. 1 1923

✓ Sec. Corner 2-3-10-11 T 33 S R 7 W. Where I found remains of old stake and 3 old original ^{be} which check with Govt. field notes: the Sugar Pine was entirely gone and I marked

A Maple 10" Dia S 45° 45' W 25° ft.

And set a Creek Boulder 8x12x15 Marked on Top + C.S. with 2 notches on E and S notches on South sides

29-8

Continued from 197.

Set by C.W. Crocker
of Oregon State
Highway Department

#29 ✓
#28 ✓
Sept 14 1939
Dec 29 1939

1/4 Cor 9:10

Set a 3/4" x 30" Iron rod from 50" Fir, Original, in good condition, N 1/2 W & 20" Fir down, but in good condition, Original, N 1/2 E; and at bottom of steep North hillside. Marked & Blazed two new trees as follows
30" Hemlock, Bears N 70° - 30' W. 55.7 ft.
48" Fir, Bears S 46° E. 37.6 ft. Scribed on Bark.
###

1/4 Cor. 4

Set a 3/4" x 30" Iron Bar. from 12" Oak S 40° W 137 chs & ~~other~~ ^{this} Oak was rotted down, Found Old blazes, but no scribe marks, & Found 36" Fir scribed on bark, same Original 16" Fir scribed, Following witness trees
36" Fir N 9° - 30' E. 164 chs Blazed & Scribed C.S.B.T. Original.
16" Fir S 10° W. 66° ft. Blazed & scribed. New Tree.

1/4 Cor 8:9

Set a 3/4" x 30" Iron Rod from original B.T.s; 12" Fir N 78° E 17 Iks is stump in poor condition & 10' Fir S 32° W 13 Iks, has been cut open, tree in fair condition, Blazed & Scribed two new trees as follows
24" Fir, Bears S 43° - 30' W 25.8 ft.
40" Fir, Bears S 78° - 15' E 48.0 "
####