

Waters 176

T 30 S R 5 W

✓ 1/4 Section Corner between Secs 19 & 30

Location identified from one Orig. BT as described in Gout field notes. i.e. 17' fir N 80° E 171 kts. this tree is now 24" ~~dia~~ ^{dia 30" RA}

B. Rock which was set for corner knocked out and ~~blaze~~ ^{blaze} in creck.

Replace Rock which I chisel 1/4 on Sa face. Blaze and scribe as new BT's

18' Fir N 45° E 70 kts 1/4 S 19 CS BT

26' Fir S 45° W 67 kts 1/4 S 30 CS BT

Sec/Cor $\frac{21}{25} / \frac{19}{30}$

✓ Sec. Cor $\frac{26}{35} / \frac{25}{36}$

Location identified from Alder S 50° E 54 kts property marked notes call this tree S 5° E which would not check facing.

18 Oak N 70° E 93 kts. gone but an old B Oak formally stood in this location now down and badly rotted. 14" BO N 38° W 214 kts all gone but stump.

Drove 1" axle for corner with pipe on upper end

30' fir N 30° E 32 kts blazed & scribed T 30 S R 5 W S 25 CS BT

17' " N 66° W 45 " " " T 30 S R 5 W S 26 CS BT

18' " S 12° W 43 " " " T 30 S R 5 W S 35 CS BT

10' " S 65° E 103 " " " T 30 S R 5 W S 36 CS BT

✓ 1/4 Cor $\frac{26}{35}$

Drove ford axle at mid point between Sec. corners

8' Fir N 10° E 7 kts blazed and scribed 1/4 S 26 CS BT

10' " S 35° W 6 " " " 1/4 S 35 CS BT

Int. L. Cor. A. J. Miller D.L.C. 63, Buggy Axle 5 1/2' lg, S. Side County Rd. Set from 1 Old B.T. 16" W.O. N 35° W. 50.2' also new B.T. 18" Pine N 84 1/2° W 109.0'

By G. C. Frear
4-7-36
J. Wolford
P.D. " } Wit.
Gene Richardson
U. V. Ash

N.L. Eppstein

Pepin

B
N
R

T 30 S R 5 W

N.H. Eppstein
C.O. Sawyer
G.B. Nichols
G.A. Fitzpatrick
W.F. Briggs
Jan. 21 - 1925
Witness
Edwin Weaver
J.E. Weaver
W.S. Oran
Clara Fields

1/4 Corner between Sec 17/18 - Renewed from Old B.T.'s. Could not see scire marks but had indications of old. B.T. other trees gone but stump in place. Edwin Weaver claims it to be the B.T. and he had seen marks before they became obliterated.

Set Ford axle for corner. and marked

W. oak 16" dia. 569° E 32.7 ft.

W. oak 7" " 542° W 23.5 feet.

Sec. Cor. 7-8-17-18 Renewed from 2 old B.T. NE & SE ^W 1 1/2" x 30" I.P.

Marked a 14" W. Oak 55° W - 163 lbs

For tree gone in Sec 18.

1/4 Cor W side Sec 7

Set by proportional measurement

Drove 2" x 24" Pipe 24" underground with wooden plug.

An Apple 12" dia bears N 15° E 18 lbs sciled 1/4 57 CS B#

Black Oak 57 " 545° W 237 " 1/4 5 BT

Sec. Cor 1/7 on range line

Set from Texas B.Ts as recorded p 145 this volume. bolt and stone gone.

Drove 1" x 36" Pipe 26 in underground.

1/4 Cor. Bet. 16 & 17

W. Oak 15 in N 42° E 50 lbs.

B " 8 " N. 25° W 30 "

Int. L. Corner DLC #40 Isaac Bailey. 8" x 8" Stone set in the ground x Std. U.S. Geological Survey B.M. Elev 642' set 1903

North 135.7 ft. & SPRR. bears N 107.4 ft. point 19.9 ft from RR. Sta. 1309+68! B.C. spiral, No 407.

Ben B. King
NE Richardson
RL Irwin
Dep. wit
June 27-1885
W.F. Briggs
Dec. 13, 1934