

✓ 1/4 Sec Cor ²²/₂₇ Location identified from old hub in fence corner and stump of OBT as recorded in orig. field notes N65°W 55 lks bearing scribe marks.

Set sandstone 3'x6"-18" long for corner chisted X on top and 1/4 Sec E face CS on West face.

New B.Ts W. Oak 14" dia 585°W 117 lks Blazed & Scribed 1/4 S 27 CS BT

Fir 36" - N 70° W 130 " 1/4 S 22 CS BT

✓ W 1/6 S ²²/₂₇ - Drove 1 1/2" x 48" pipe 44" in ground midway between 1/4 Cor ²²/₂₇ and Sec Cor ²¹⁻²²/₂₈₋₂₇ Post along side scribed W 1/6 S CS - 527-522-

B.Ts - 28" Fir N 2° E 23 lks Blazed & Scribed W 1/6 S 22 CS BT

24" " 582 1/2° W 12 lks " " W 1/6 S 27 CS BT

SE ext Cor DLC # 46.

✓ A 60" Oak tree - probably orig. corner as it check bearing and distance from Sec. Line and Int. Cor. Drove pipe along side to N.W.

New B.Ts - 28" Fir N 55° W 59 lks Blazed & Scribed CL 46 CS BT

60" " N 35° E 16 " " CL 46 CS BT

✓ NE Cor DLC # 46.

✓ Set this corner from SE Ext. Cor CL 46 + Sec. Cor.

Drove 2" x 42" pipe 32" in ground for corner set 3" sq. post along side scribed NE CL 46 CS.

New B.Ts 36" Fir 530° W 87 lks Blazed & Scribed NE CL 46 CS BT

30" " 540° E 33 " " NE CL 46 CS BT.

✓ Int. Cor DLC # 46

Set 6" x 6" x 18" sandstone chisted CL 46 CS on NW face 12" in ground for corner from orig B.Ts. As they are in good condition Replace and scribe CL 46 CS BT

Deputy County Surveyor

Edmund J. Downing

NE Richardson
WF Holcomb

Witacus
Kausche

Sept 9 1929

Index of 1928

23-7

Deputy County Surveyor
Ben B. Irving
NE Richardson
W.K. Holcomb
Kaweha
Wit.

1/4 Cor 27/28 - Location identified from Oak
BT dead and rotting. Scribe marks in
good condition
Set 4" x 4" x 24" Sandstone 12" in ground for
corner. Chisled X on top 28 on W face + 27 on E face
New BTs - 24" white Fir N16° E 24 kts Blazed & Scribed
1/4 S 27 CS BT - 24" Red Fir N67° W 37 kts
1/4 S 28 CS BT

Cor. Secs. 34-35-2-3 T. 23 & 24 S. R. 7 W.
Sandstone 6x13x21 marked with X on top
B. Oak 20" marked C.S. Sec. 35. N. 49° E. 176 kts.
Fir 30" " " " N. 83 3/4° E. 130 "
No other trees F. Book 33

N.E. Cor. J.B. Goff D.L.C. 38
20" B. Oak N. 30° W. 470 kts.
4" W. " N. 43° 17' W. 438 "

S.E. Cor. D.L.C. 38
Fir 30" N. 53° 20' W. 38 kts.
" 20" S. 15° E. 35 "
Sandstone 2x10x24 marked X

F. Book 33

July 9, 1938
Ben B. Irving Depositor
Wit { N.E. Richardson
S.A. Mode
G.C. Sparte

N.E. Corner of Ziba Dimmock D.L.C. #45
Location identified from both original B.T.
as described in the original Govt. field note
Trees dead & deteriorating rapidly
Drove 1" x 24" drift pin ^{lullwill} in ground ~~alongside~~ for
corner & 1" x 20" pipe 10" in ground ~~alongside~~ for
marker from which
B.O. 16" Brs East 15 kts, & W.O. 15" Brs
S 45° W 57 kts both blazed & scribed D.L.C. 45, C.S. 36