

✓ Sec. Cor. 10-11-14-15

O.B.T.s as called for in Original field notes, both down. 1 with scribe marks well preserved and the other so badly charred that no scribe marks remained but position checked.

Set 2" x 36" iron pipe for corner. driven 30" in ground.

A 36" B. Oak.	bears N 15° E	380 lks.	on slope of 21' 40" scribed	T 225 R 6 W
				S 11 CS BT
24" W "	"	5 65 1/2 W	143 " "	19' 10' "
				T 225 R 6 W
				S 15 CS BT
30" "	"	5 27° W	202 " "	18' 36' "
				T 225 R 6 W
				S 15 CS BT

✓ N.W. Cor. of Donation Land Claim #41 (Henry Christian)

Replaced from Original B.T.s. as called for in original notes. Both trees gone but scribe marks BT visible on stump.

Set a cam shaft with gear attached driven flush with the ground for corner.

An 8" W. Oak	54° 9' E	461 lks	scribed Cl. 41 CS BT
20 " "	5 82 1/2 W	450 lks	" "

✓ S.W. Cor. of Chas. F. Putman - D.L.C. 39.

Set 1 1/2" x 30" iron pipe driven flush with ground from Original B.T.s.

Remarked Original B.T.s.	36" Fir	55° E	30 lks.
	40"	55° W	30 lks.

✓ Sec. Cor. 15-16-21-22.

Chopped out Old B.T. 40" Fir 54° 5' E 111 lks. Scribe marks plain. The burned out stump of an old Maple bears N 85° W 41 lks. This may be remains of an Old BT as the original field notes call for a maple N 85° W 51 lks.

Bend Johnson Deputy C. Surv. Dec. 1927 & Jan 1928

Witnesses - W.S. Grear Geo. Montgomery

2-2-6

James J. Shuring - Deputy County Surveyor Jan 1928

W.S. Clear
Geo. Montgomery
Witnesses

Set 8"x6"x20" sandstone for corner
~~mark~~-chisled x 1/4 and having 3 notches
on each face.

- An 8" Fir bears N 40° W 41 lks scribed T22SR6W S16 CS BT
- 14" " " N 85° E 52 " " T22SR6W S15 CS BT
- 15" " " S 15° E 48 " " T22SR6W S22 CS BT
- 16 " " S 38° W " " T22SR6W S21 CS BT

SW. Cor. Cl. 41 Henry Christman

Position computed by proportional distances between
NW Cor. Cl 41
NE & SE corners of D.C. 39. Set sandstone 6"x10"x18"
set 10" in ground chisled x on top.

- 18" Fir 559° 37' E 169² lks scribed Cl 41 CS BT
- 30" W. Fir N 44° 50' E 305⁵ lks " " " "

SE. Cor. Cl 39.

Position determined by intersection of E & S lines
of the claim. Set boulder 7"x10"x10" flush with
the ground

- A 20" Fir 519° E 89⁸ lks. scribed Cl 39 CS BT
- Fir N 19° W 68⁹ lks. " " " "

1/4 Sec. Cor. between Sec. 10 and 15.

Position determined by proportional measurements between
sec. corners. Set 1/2" x 48" pipe driven 48" in the ground
for corner.

12" Ash on west bank of Jack Crk. bears East 152⁸ lks.
scribed 1/4 S CS BT

16" Locust N 88° 20' W 689⁵ lks scribed 1/4 S 10 CS BT.

X 1/4 chisled on top of N. wing wall on old bridge
Abutment S 43° 55' E 230 lks.