

Feb. 7 1928

Ben S. Young Dep. Co. Sur.  
W. S. Grear, Chain  
Lee McCaro.

C.S. 17/28 d 20/21/19

May 24, 1937  
Arthur Boyer, Dep. Co. Sur.  
B. A. Lane  
Walden Stone  
Maurice Reid

Vol. 3 P. 282

JUNE 15, 1928  
A. L. Stephens Co. Surveyor

W. S. Grear } Witness  
F. H. Perry } Vol. 3 P. 282

Continued on  
Page 190

Vol. 3 P. 282

1/4 Sec. Cor. 1 and 12.

On Right bank of No. Umpqua River  
Old Fir Stake in place badly rotted. Found O.B.T.  
down and rotting badly bearing scribe marks 1/4 5 BT  
in bark. This OBT a 12" Fir bears N 35° W 12 lks from stake.  
Had no field notes to check so replaced stake with a  
6' x 8' x 14' river boulder. chiseled X on top  
Scribed a 40° cedar 52° E 75 lks and a 14" Fir  
N 71 3/4° E 1 1/2 lks as new BTs.  
Scribed 26" Fir N 0° 30' E 27.5' for Witness Tree to 1/4 Sec Cor Secs 1 and 12

Note: May 24, 1937 - this 14" Fir is  
dead so scribed another  
tree as shown

Section cor 16-17-20-21.

Found remains of old corner stake, and old  
W. Trees down & rotten. Set stake where old  
stake was and marked new trees as follows  
Fir 16" Bears N 68° E 24 lks  
" 24" " N 44° W 78 " "  
" 12" " S 32° E 60 " "  
" 20" " S 76° W 51 " "

Corner of sections 8, 9-16-17, corner set by  
Government surveyor, standard pipe for corner.  
with following Witness Trees  
W. Oak 12" S 35°-30' W 23 lks.  
" " 12" N 72° E 54 " "  
" " 16" S 79°-30' E 120 " "  
" " 16" N 79°-30' W 131 " "

1/4 corner between sec 16 & 17

This corner was gone, and no evidence  
of old corner, so I established it on the ap-  
propriate distance between section corners  
by driving 1" x 30" bolt in the ground  
and marking following Trees

Fir 12" Bears N 75° E 17.5 feet  
" 10" " N 64°-30' W 12.0 feet

Continued on  
Page 190

26-4

REN # 20

Nov. 18-28 - 1925  
see survey 3-20

Sec. cor 25-26-35-36  
Set W. Oak Stake 4"x4"x3'  
Lauvel 24" Brs. N25W 21L } Old B.T.  
B. Oak 18" Brs N87E 68L }  
Fir 15" Brs S48E 23L B.T. D36 C.S.  
" 12" Brs. S31W 62L B.T. D.35 C.S.

REN # 21

1/4 cor to 35-26  
Set Cedar 4"x4"x3'  
W. Oak 12" S88W 22L B.T. 535 C.S.  
B. Oak N42E 24L Old B.T.

W. H. Woods Sp. Sur  
W. A. Crear Chain  
O. G. King }  
A. P. Casberry }  
Witness

1/4 Cor. to 24-25  
Set 4"x4"x2' Stake  
REN # 22 B. Oak N89°E 120L Old B.T.  
15" Fir S23°10'W 34L 1/4 S 25 C.S. B.T.

H. L. Eppstein Sp. Sur  
S. P. Wolford }  
Chain  
H. C. Witham }  
H. Carvine }  
Witness

REN # 23 Section corner to secs. 13-14-23-24, T26S R4W  
Set 1"x40" Galv. Iron Pipe for corner  
from two old B.Ts one S.W. oth N.W.  
Marked 3 New trees 5" W.O. N43°E 203 1/2 feet  
6" W.O. S25°-30'E 301 feet; 12" Fir S43°-30'W 73 feet

Feb. 16, 1929  
Wit. Clarence Tester  
H. L. Eppstein  
Co. Surveyor

REN # 24 1/4 Cor between sec 7-18 Set Oak Post from old  
B. Ts, namely a.W.O. 25" N75°W 47 lbs; Oak 18" N75°E 54 lbs,  
in place but cut out. ~~scribe~~ marks visible; Marked  
New trees as follows: W. Oak 10" S68°E 34 lbs; W.O. 10" N10E 49 lbs

May 24, 1929  
W.P. Richardson  
BA Lane  
Allen Moore  
Deputy County Surveyor

1/4 Cor Sec 19-24 T26S R3+4 W.  
Identified as recorded by Cole. Drove ~~74"x36" Galv~~ 1"x16" iron bar  
alongside Post and Blazed and scribed as new B.T. a.  
Fir 16" dia S43 1/2 W 20 lbs 1/4 S24 C.S. B.T.

Over