

T 22 R 6.
 continued from p 186.

✓ Sw lot. Cor C145 cont.

and in good condition. This corner comes at the intersection of an old 45 rail fence and a board fence running W. Drove an iron pipe 3/4 x 36" for corner. Set 1 new BT.



✓ Section Corner Secs. 13-14-23-24

I identified the location of this corner by a stake set by Surveyor Thiel also 2 orig BTs

A B Oak S 85° E 87 lks and
 O B O S 68° W 32 "

A B oak bears N 73° E 233 lks which appears to be an OBT. blazes have been chopped out and marks obliterated. Recorded as N 63° E 133 lks.

Set ~~new~~ 3/4" x 36" pipe for corner and new BTs.

2 14" Fir N 45° E 31 ft scribed S 13 T 22 R 6 W C 5 BT

10" " S 35° E 135 " " S 24 " " " "

18" " S 30° W 373 " " S 23 " " " "

6" " N 95° W 26 " " S 14 " " " "

April 19 1928
 Dept. of Surveying
 R.L. Irving } witnesses
 J. W. Widely }

T 26 R 3

May 22 1929
H.L. Eppstein Co. Surveyor
J. Richardson }
B. Lane }
H.E. Wood }
Witnere

1/4 Sec. Cor. Between Sections 9 and 10
Old White Oak 14" in Dia S 85° E 100 lks Scribe marks
are very plain yet.
Black Oak 8" Dia. N 62° W 79 lks Stump is
all that remains. Marked the following trees
Fir 8" Dia. N 27° E 11 lks.
Fir 12" Dia. N 65° W 16 lks.

June 21 1930,
H.L. Eppstein Co. Surveyor
N.E. Richardson }
B.A. Lane }
Davis }
Wit.

S.W. Cor D.L.C. No 40 from old B.T. Set 18" x 12" x 12"
stone in ground. Marked 40 For corner Marked NW Oak 18"
S 33 3/4 E 287 2/3 ft.
SE Cor D.L.C. No 40 from old Pine tree, No scribe marks
Phil Strader, said he had seen marks on same. Set Post
and marked a Pine 15" S 50-30 E 158° ft.
S.E. Cor D.L.C. No 38 from Old B.T. Stump, Set Rock
18-14" x 8" Marked 38 for cor. Marked 18" W Oak, S 33 3/4 E 287 2/3 ft.
SW Cor D.L.C. No 41. from Pine Stump No scribe
marks, but checking out from S.E. Cor C 140, Set a post.
Flush with ground. Marked 15" ^{Fir} S 14-30 E 49° ft.

1/4 Cor. Bet. Secs. 16-21 (F.B. No. 19 Page 47)
old post lying on ground from this position etc. (R)
Red Cedar 16" S. 70° 20' W. 22
" " 24" N. 65° 40' E. 44

Ben B Irving Rep
M.L. Kinnel }
Fred Schmidt }
N.E. Richardson }
Witness
Feb 6 1933
Feb 3 1933

1/4 Cor bet. Secs 11-12 Location identified from DBT 36" Fir
S 10° W 10 lks. Set a fir Post 4" x 4" x 42" from which
a Fir 18" dia bears S 28° E 45 lks. mkd 1/4 S 12 CS BT
Fir 15" " " S 44° W 85 " " 1/4 S 11 CS BT

May 22 1937
Arthur Boyer Dep C.S.
B.A. Lane }
Maurice Reid }
Welden Stone }
Wit

W.C. for 1/4 Sec Cor 10-11 BTs destroyed. set new trees
30" Fir N 82° 13' W 142 1/2 ft. WC 1/4 S 10 CS BT
27" " N 85° 37' E 52 1/2 " " 5 11 "

May 20, 1937
Arthur Boyer Dep. C.S.
B.A. Lane }
Maurice Reid }
Welden Stone }
Pickett Mc Millan }
Wit.

1/4 Cor bet Sec 6, T 26 S R 2 W and Sec 1, T 26 S R 3 W - set one
new tree 40" Fir North 24.3 ft mkd 1/4 S CS B.T.
Only one B.T. 24" Fir S 73° E 14.5 remaining
1/4 Cor bet Sec's 1 and 2, T 26 S R 3 W set from evidence on
ground = E + W. Fence and pile of rocks as confirmed by Pickett
Mc Millan who saw original stake set by U.S.G.L.D. from this 1/4 cor
also by F.C. Frear who also saw this orig stake as witnessed by Mc Millan
Set 10 gage shot Gun Barrel in ground and scribed 15" Fir N 27° E 28 ft.
and 18" Fir S 83° E 14.7 ft.