

Continued from page 132.

T 29 S. R 6 W

January 26 and Feb. 1 1929.

Benjamin Spring

42 Deputy County Surveyor

Witnesses
W.S. Crear.
Char. Lucas.
Edward Evans.

44

Exterior l. corner Claim #45

No evidence of this corner found.

Set fir post 4"x4"x48" for corner scribed and a car axle with gear attached, N 17° E 49 lks. Cl. 45-C.S. from which a 16" fir bears ~~S 17° W 47 lks~~ scribed CL45-C.S.-BT

This post was set at the intersection of a line south from the NE corner of the claim and a line east from the interior l. corner as set by Kane in 1913.

1/4 Sec. Corner 16/21

As described by Cole. one OBT alive and in excellent condition. Cedar stake in fair condition. No B.T. in sec. 16.

Drove car axle for corner and marked a new B.T. 6" Fir N 20° W 18 lks. 1/4 S 16-C.S.-BT

Section corner 16/15 21/22

No evidence of corner post or B.Ts found after extensive search. Located corner at intersection of Blazed line east and north as being unquestionably the original lines.

Drove a car axle for corner from which

- a. W. Oak 12" dia. bears N 55° E 22 lks. scribed T29SR6W S 15 CS BT
- Fir 15" " " S 37 1/2° E 64 " " " 522 " "
- " 14" " " S 10° E 57 " " " 521 " "
- " 30" " " N 37 1/2° W 93 " " " 516 " "

1/4 Sec. Corner 21/22.

Position identified by OBT S 55° W 5 lks. as described in original notes. BT now dead. Drove 3/4"x54" GI pipe for corner and a 6"x6"x42" cedar post scribed 1/4 S 21 on W face + 522 on E face. marked new B.Ts { 14" Fir N E 14 lks 1/4 S 22 CS BT, 15" " S W 53 " 1/4 S 21 CS BT.

45

