

T 29 R 8

Jan. 4 1928
W.S. Crear.
C. McCann
W. N. Porter
Deeds & Surveying Deputy Co. Sec.
witnesses

Section Corner 17-18-19 and 20

Set by double proportionate distances from 1/4 section corners N-E and W and Sec. Co S.

Set a Sandstone 4"x6"x20" 12" underground for corner 10' ^{set} from creek bank chiseled X on top

and 5 notches on E face

- 1 " " W "
- 3 " " N "
- 3 " " S "

20" Ash N18°33'W 1112 lks. scribed T29S28E518 CS BT


14" Fir S 52°6'E 935 " " T29S28E520 CS BT

No other tree within reasonable distance in proper quadrants.

Peak of Signal Tree lookout house on Kenyon Mtn is S61°22'W

Look out Tree " " S61°25'W

Group of high trees on top of Ketchum Mtn. S 33°3' W




1/4 Section Corner between Secs. 19 & 20

Set by single proportional measurement along the west line of sec. 20

Set Sandstone 4"x6"x14" chiseled X on top + 1/4 on E face 14" underground for corner.

#20 14" Fir S 18°45'W 913 lks scribed 1/4 S 19 CS BT

16" " S 1°1'E 865 " " 1/4 S 20 CS BT



Center of Section 20

Set at intersection of lines connecting opposite 1/4 section corners of sec. 20.

Set a pipe 1 1/4" x 24" driven flush with the ground.

#21 A. Yew wood Tree bears S 0°12'E 506 lks scribed

e- s 20. es. BT

Old yew wood post used as center of section bears N 53°37'W 48.6 lks.

29-8

Continued to Page 179.

1/6 Sec. corner. between the center of sec. 20 and the E 1/4 sec. Cor.

Set a 1 1/4" x 24" iron pipe driven flush with the ground for corner.

BT An 18" Fir N 53° 30' W 31 lks scribed C-E 1/16 S

(NOTE - On Acct of Road Constr. 6-9-'32

20 CS BT - I marked a 12" W. Fir S. 6 1/2° W. 31.5 ft. F.C. Furr Co. Rdmstr.

corner of sec 1 & 12 standard 1/4 Cor

Marked from which, 10" Fir S 75° W 9.6 feet, 8" " N 12° W 19.8 feet

Section corner 28-29-32-33

Set from old original B.T.s

Set 4" x 4" x 36" Fir Stake 18" in ground

- #27 Fir 60" dia N 57° W 51 feet
- Laurel 12" dia N E Laying down } Old Original
- Fir 12" dia S 43° W 35 1/2 feet
- Cedar 30" dia S 5° E 33.9 feet
- Fir 8" dia N 35° 30' E 22.8 feet

1/4 Cor. bet. sec's 2 & 11, 3" x 3" fir post the following new trees set

from orig. B.T.'s. - 30" Bl. Oak, N 3° E 111.0 ft.

#24 Orig. B.T.'s dead. 14" Wh " S 19 1/2° W. 129.0 ft. = 133' on 14° slope msmt.

(Sec. Cor 2 & 3, 29/8 34 & 35 28/8, Renewed 1 Tree only from corner as located from trees now in; 12" Red Fir S 72° W 50.5 ft.

#25 Orig. trees still in are, 40" Fir N. 53° W. 97 lks.

36" " N 62° E 113 "

Bark Scribes

24" oak S. 75° E 47 lks.

1/4 Cor Bet 21 & 22 Chinq. B.T. to SW. dead + fallen down - set

3" x 3" sq. post for Cor from 18" Fir to the NE blazed

a 40" Fir + scribed it - for BT in Sec 21 - N 46° W 36.5' from 1/4 Cor.

March 6 1931
H. L. Eppstein
County Surveyor
June 2 - 1931
B.A. Lane
Giles
Ben Bennett

H. L. Eppstein
County Surveyor
June 2 - 1931
B.A. Lane
Giles
Ben Bennett
Witness

A. Boyer Surveyor D.C.
Aug 25, 1936
Ralph Heater Wit.
C. Mc Cann
Lewis Morris } Wit.

#21 A
NE Richardson
H. Z. Driskell } Wit.

#26