

T 30 S R 4 W.

SE Corner Claim 44

Replaced from original B.T. Standing and in excellent condition which I Chop out.

Set Stone ~~6~~ 6"x6"x18" for corner, stone marked with crows foot (Y)

Orig. BT bears N 89° W 648 lks. 36" B.O.

New BT bears. S 80° W 22 lks 12" Fir

SW Corner Claim 44

Replaced from Original B.T. standing but interior badly rotted and splintered. Original reverse growth plainly visible as is also latter scribe marks. Old BT N 20° E instead of N 20° W was recorded in original notes.

Set Auto axle with gear attached for corner from which original B.T. B.O. 36" bears N 20° E 323 lks. dist

New B.T. 18" Fir South 15 lks dist

Tripp Corner. Sec. 36 of T 29 R 4 - Sec 31 T 29 S R 3 W - Sec. 6 T 30 S R 3 W and Sec. 1 T 30 S R 4 W. Identified by old rotted stake down and bearing faint scribe marks and original B.Ts. O B.T in sec 36, down and rotting. BT in Sec 31 broken off and dead, B.T. in sec 1 dead and B.T in sec 6 alive but blazes having been chopped out are badly rotted.

Set a cedar post 4"x6"x72" for corner, scribed T 29 S - 5 31 on NE face R 3 W 5 6 on SE face, T 30 S - 5 1 on SW face, and R 4 W 5 36 on NW face.

New B.Ts as follows = 15" B. Oak. N 60° 5' W 45 1/2 lks scribed T 29 S R 4 W 5 36 CS B.T.  
12" Fir N 53° E 29 1/2 lks scribed T 29 S R 3 W 5 31 CS BT  
O B.T. 14" B Oak S 79° 20' E 47 1/2 lks not chopped out or remarked  
14" B Oak S 84° 10' W 41 lks scribed T 30 S R 4 W 5 1 CS BT

Ben J. Downing Deputy Co. Surveyor.  
Wm. Clear } Witnesses  
R.L. Irving } Nov 29 1927

Feb. 28 1928  
Set By Ben B. Irving Deputy  
Wm. Clear } witnesses  
R.L. Irving }

M. T. N. E. Richardson

T 30<sup>s</sup> R 4<sup>w</sup> ?

Closing 1/4 Sec. Cor E side of Sec. 1 T 30 S R 4 W.  
 This cor. set as instructed by US Survey Office. Set  
 by proportional measurement between the closing section  
 corner between 1 + 62 and the NE corner of the township.  
 Set a 3/4" x 36" pipe driven 32" in the ground  
 A 30" W. Oak N 70° 45' W 62 lks. scribed "451 CC CS BT.  
 8" W. Oak S 43° 50' W 20 lks. " "451 CC CS BT.

Feb. 28 1928  
 Ben B Irving Deputy Co. Surveyor  
 W.S. Carter  
 R.L. Irwin } Witnesses

1/4 Cor. between Sec 9-16 Set 1 1/4" x 3" Shaft  
 for corner from old B.T. Marked New  
 B.T. 8" Fir S 21° W 6 lks; 30" Fir N 71° E 25 lks.

1/4 Cor between Sec 4-9 Set corner from  
 old Black Oak B.T. S 86° W 10 10 lks; other  
 tree gone. Marked New B.T. B.O. 24"  
 N 10° 30' W 7 41 lks.

1/4 Corner between 9-10 This corner  
 was gone so set it proportional distance  
 & bearing between section corners by  
 placing 1" x 18" Galv. iron pipe 10" under  
 ground and marked New wit tree  
 22" W. Oak S 46° E 9 16 lks; 5" Prun tree S 15° 30' W 5 12 lks

W. Cor. to 1/4 Cor Bet 8 & 9 Set Ford axle for corner  
 From 40" B. Oak S 75° 30' W 180 link. O. B.T.

Marked 18" Fir N 57° W. 27. links

Cor 2 1/12 Conglomerate Rock 6x6x18"  
 6" W. Fir N 45° E 7 ft. - 24" Fir N 14° W 13 ft Orig. BT.  
 #47 8" W. Fir S 62° W 23 ft - 6" W. Fir S 42° E 2.5 ft.

Cor 21 22 / 28 27 Remarked Orig. BT's (9/4 Set Post or stake) as follows  
 21.5' 12" Laurel S 48° E 44.2' - 30" Ced. S 75° W 29' and marked new tree, 6" Fir  
 N. 80° W. 37.0' 12" cedar 36" Fir N 7 1/2° E

WIT N.E. Richardson  
 William Racher  
 Henry Racher  
 J. A. Fenn }  
 Wm Myers } Witnesses  
 Oct 26 1928

Ben B Irving Deputy Co. Surveyor  
 Ernest Brown  
 Joe Snyder. W. Thayer  
 Nov. 19, 1934

Sept 3, 1937  
 Arthur Boyer D.C.S.  
 J.A. Fenn }  
 Wm Myers } Witnesses