

Douglas County Surveyor's Record of
Government Corners Renewed

T. 25 S. T. S. R. 1 E. R. W. W. M.

HOKE-CHAPMAN CO., EUGENE, ORE. 21881

7

$\frac{1}{4}$ Cor. to Section 36 only, T25-1W.
Found - Orig. 50" Fir, now stump, N. $80\frac{1}{2}^{\circ}$ W. 28.4 ft., shows "T".
8" Fir, now down, S. 37° W. 30.4 ft., shows "S36" & unhealed blaze. No trace of Rock called for.
Set - Brass Cap at Cor. Mkd: Doug. Co. Surv. Office, 1966 R1W $\frac{1}{4}$ S 36 R1E
(14" in ground & mnd of 1927)
New BT's: 8" Fir S. 39° W. 12.9 ft. mkd. $\frac{1}{4}$ S36 CS BT.
12" Hemlock S. 16° W. 18.6 ft. mkd. $\frac{1}{4}$ S36 CS BT.
Note - This corner lies on right bank of Canton Creek.

RE-RENEWED, SEE CORNER NO. #43

8

$\frac{1}{4}$ Corner to Section 31 only, T25-1E.
Found - 1927 GLO Brass Cap mkd. " $\frac{1}{4}$ S31", nearly on of rock mound.
Reset Brass Cap in new mound of approx. 2' high.
Both 1927 BT's. alive & show scar. 14", now 18" D. Fir S. 18° E. 19.0 ft. rescribed " $\frac{1}{4}$ S31 CS BT".
8" Fir S. 18° E. 4.0 ft. rescribed " $\frac{1}{4}$ S31 CS BT".
Note - Corner lies 50 ft. W. of Canton Creek, course S. on right high bank & approx. 40 ft. S. of the $\frac{1}{4}$ Cor. Sec. 36 only, T25-1W.

RE-RENEWED, SEE CORNER NO. #44

9

Closing Corner to Sections 30 and 31, T25-1E.
Found - 1927 GLO Brass cap, properly mkd.
10", now 14" Fir, S. 64° E. 41.6 ft. (face) prev. opened, scribe marks visible. Alive. N.E. BT. lying face down.
New BT's: 8" D. Fir S. 37° E. 14.6 ft. mkd. CC S31 CS BT.
8" Pine N. 44° E. 11.7 ft. mkd. CC S30 CS BT.
Note - This cor. lies in logged off unit 150' N. of small ravine, course SW.

Vernon "Ray" Tracy
Jack Heritage & E. West
October, 1966
C. S. File No. 52/30

10

Sec. Cor. to Sections 25 and 36 only, T25-1W.
Found - 1927 GLO Brass cap, properly mkd.
Orig. 36", now 57" Pine Stump (not Fir) N. 25° W. 33.7 ft., shows fair scar. We rescribe.
Orig. 30", now 30" Fir Stump, 14 ft. high, S. 14° W. 43.6 ft.
14", now 20" Pine Shattered Stump, S. 70° W. 46.2 ft.
Also find stumps of obliterated BT's. to E. of line.
New BT's: 14" D. Fir N. 39° W. 42.0 ft. mkd. T25S R1W S25 CS BT.
12" Pine S. 60° W. 108.3 ft. mkd. T25S R1W S36 CS BT.
Note - This corner lies approx. 85 ft. north of closing corner of secs. 30 & 31, T25-1E.

RE-RENEWED, SEE CORNER NO. #59

11

Township Corner, T24S-T25S- R.1W. & R.1E.
Found - Orig. 18", now 28" Cedar N. 64° E. 11.2 ft., prev. opened many years ago "S E S3" scribe visible on nearly rehealed blaze. We rescribe "T24S R1E S31 DCS BT".
Orig. 28", now 36" Fir S. 37° E. 43.6 ft. Alive, good condtn., shows very good scar.
Orig. 30", now 36" Fir S. 86° W. 33.0 ft. Alive, good cond., shows very good scar.
Orig. 18", now 21" Fir N. 25° W. 31.0 ft. Alive, good cond., shows very good scar.
Set - Brass Cap at Cor. Mkd: Doug. Co. Surv. Office, 1966 T24S R1W $\frac{S}{S} \frac{36}{1} \frac{S}{S} \frac{31}{6}$ R1E
New BT: 10" Hemlock N. 60° W. 34.8 ft. mkd. T24S R1W S36 DCS BT.
No smaller trees close to S.E. or S. W.
Note - This corner is on Douglas-Lane County Line.

Nov. 3, 1966

12

Closing Corner Sections 18 and 19, T25S-R1E.
Found - 1927 GLO Brass Cap, properly marked & BT's. allows:
8", now 11" Fir, N. 61° E. 30.4 ft., now small, shows scar, we do not open.
8" now 10" Fir Snag, S. 40° E. 27.7 ft., shows scar, Don't open.
New BT's: 36" Cedar S. 48° E. 7.4 ft. mkd. T25S R1E S19 CCOCS BT.
12" D. Fir N. 1° E. 31.6 ft. mkd. T25S R1E S18 CC CS BT.
Note - This corner lies on S.W. slope approx. 150 ft. south of corner to Secs. 13 & 24, T25-1W, Ren. #22 which is O. K.

RE-RENEWED, SEE CORNER NO. #34