

Douglas County Surveyor's Record of
Government Corners Renewed

T. 25 S. T. S. R. 1 E. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Witness Corner(South) T25S RLW $\frac{S 12}{S 13}$ RLE 13
 Found - Rock mkd. "WC S12" on N.E. & "S13" on S.W., firmly set
 1.3' north of cl. corner of Secs. 7 & 18, T25-1E which is
 a 1927 GLO Brass Cap firmly set in mound of stone.
 Orig. 40", now 40" Fir Snag, N. 89° W. 13.2 ft. (slope), shows good
 scar, we do not open.
 30", now 34" Fir S. 24° W. 31.7 ft., now stump, shows good scar,
 we do not open.
 Orig. 20", now 20" Fir Snag, N. 58° E. 13.2 ft., recorded as
 being obliterated, frag. scribe marks visible on chopped face.
 New BT's: 12" Cedar S. 71° W. 40.3 ft. mkd. W.C. T25S RLW S13 CS BT.
 12" Pine N. 14° W. 106.3 ft. mkd. W.C. T25S RLW S12 CS BT.
 Note - This corner lies on precip. west slope on N.-S. cutting line,
 cut off to west.

Wit. Cor. (North) $\frac{S 12}{RLW S 13}$ T25S RLE 14
 Found - Steel tube & Alum. Cap & Rock face mkd. S12 B.O. N. 16° W. 17.7 ft.,
 as recorded in Ren. #24 (T25-1W)
 Orig. Rock with "WC" only.
 Set - Brass Cap 482.5 ft. N. of True Corner, note dist. to true cor.
 not on Brass Cap
 Set Steel Tube along same B.C. Wit. Cor. $\frac{S 12}{S 13}$ RLE
 There are no live trees west of line. Mark New BT's. to East.
 9" Fir S. 26° E. 39.0 ft. mkd. W.C. CS BT.
 1" Fir N. 85° E. 24.9 ft. mkd. W.C. CS BT.
 Note - This corner lies on top of verticle rock bluff 60' high above
 N. fork of H1 Power Creek.

$\frac{1}{2}$ Corner to Section 24 only, T25-RLW. 15
 Found - Basalt Stone mkd. "1/2 W on W. face.
 No trace of 1927 GLO Brass Cap.
 26", now 30" Fir Stump, N. 45° W. 66.0 ft., shows good scar. Don't open
 8", now 11" Madrone N. 64° W. 4.6 ft., prev. opened & shows fragments
 of scribe. (Recorded as S. 64° W.)
 Also obliterated 16" Madrone N. 53° E. 7.9 ft.
 Set - Brass Cap Mkd: County Surveyor's T25S RLW $\frac{1}{2}$ S24 RLE
 New BT's: Office, 1966
 6" Madrone N. 39° E. 6.0 ft. mkd. "1/2 S CS BT".
 5" Madrone N. 21° W. 5.5 ft. Mkd: "1/2 S24 CS BT.
 11" Madrone N. 64° W. 4.6 ft. remarked: "1/2 S24 CS BT.
 Note - This corner lies at foot of 30 ft. bluff on top of 100' high bluff.

Sec. Corner to Sections 1 & 12 only, T25S-RLW. 16
 Found - 1927 GLO Brass Cap, properly mkd. & nearly out of ground.
 Reset - Brass Cap 12" in ground & buried mound of stone 15" high around
 Orig. 60", now 60" Fir Stump, cut low, S. 48° W. 19.1 ft., no scribe.
 Orig. 30", now 31" Fir N. 71° W. 26.4 ft. (recorded as 4 lks., should
 be 40 lks.) scribe marks visible on nearly healed blaze. Alive.
 Obliterated BT's. to N.E. & S. E., now turned out.
 New BT's: 31" Fir S. 74° W. 61.6 ft. mkd. T25S RLW S12 CS BT.
 5" Hemlock N. 59° W. 29.4 ft. mkd. S 1 CS BT.
 Note - This corner lies at N.E. corner of cut off unit on top of round spur.

$\frac{1}{2}$ Corner to Section 1 only, T25-1W. 17
 Found - GLO 1927 Brass cap, firmly set & properly marked.
 Orig. 30" Fir, now Snag, S. 50° E. 63.4 ft. This BT. was obliterated
 in 1927, rehealed blaze. Use as ref. since bear. to fallen BT.
 does not check.
 8", now 14" Pine, N. 76° W. (not N. 62° W.) 14.5 ft., partial scribe
 marks visible on nearly healed blaze. Alive.
 Rescribe: "1/2 S 1 CS BT".
 8", now 14" Chinq., S. 35° W. 15.2 ft., frag. scribe marks visible
 on badly decayed & unhealed blaze. Alive.
 New BT: 12" D. Fir S. 6° W. 22.5 ft. mkd. $\frac{1}{2}$ S 1 CS BT.
 Note - This corner lies 25' E. of new logging Rd., course N.&S., curving S.E.

Vernon "Ray" Tracy
 Jack Heritage & E. West
 November, 1966
 C. S. File No. 52/30

RE-RENEWED SEE CORNER NO #33

RE-RENEWED SEE CORNER NO #60

RE-RENEWED SEE CORNER NO #61