

Douglas County Surveyor's Record of  
Government Corners Renewed

T 25 T. S. R 1 E R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21001

L. E. Monrean, Doug. Co. Surveyors Office  
P. L. Earle  
Sept. 13, 1976  
C.S. 59/24

32

Section cor. for Secs. 13 and 24 only, T25-1 W.  
Found - 48" (rec. 60") Fir, now a stump, bears N.74°W., 29.0 ft. with blaze. I open & find scribing "T25S RIW S13 BT".  
Stone, 16"x14"x7" (rec. 6"x10"x8" above ground, Orig. 12"x10"x8") found 3 notches on opposite faces and S 13 on another face. Rock has been dislodged by windfall bearing tree.  
38" Fir (Rec. 36") is now a windfall. Tree has well healed blaze.  
Steel tube with survey cap, dislodged by uprooted BT. Ren. #22, T25-1W.

Set - Brass cap at section corner stamped:  
"County Surveyors Office" T 25 S  
1976 R S 13 R  
1 S 24 S 18 1  
W S 24 E

Set - Corner stone on north side of cap, set steel tube on south side of cap  
Set - 5/8" x 30" iron rod with alum cap. in BT stump, bears N.75°W., 28.7 ft.  
Cap stamped "B.O. 1"  
Set - Spike in 40" Fir stump, bears S.50°W., 33.8 ft. stamped "B.O. 2".  
Set - Cedar post 2" square x 9 ft. Set post 2.4 ft. in the ground, bears North, 4.0 ft.

9/13/76

33

Witness Corner (south) for Secs. 12 and 13 of T.25-1W.  
Found - 39" D. Fir bears N.87°06'W., 13.2 ft. with good scar.  
33" D. Fir stump bears S.25°04'W., 31.7 ft. scribing partially visible.  
11" Cedar bears S.73°12'W., 39.9 ft. scribing visible. Ren. #13  
12" Pine bears N.14°08'W., 107.9 ft. with good scar.  
Set - A 2" x 30" Galv. steel pipe 24" into the ground and constructed a mound of stones around it. I marked the attached 2 1/2" brass cap: T25S WC S12 S13 RIW R1E PLS 866 1978.

34

Closing Corner for Secs. 18 and 19 only.  
Found - 2" Iron pipe with 2 1/2" brass cap marked U.S. General Land Office  
T25S T25S  
S24 S18 R1W R1E 1927.  
S19<sup>CC</sup>

30" Cedar snag bears S.28°E  
9" D. Fir snag bears S.40°E  
New BT's- 15" D. Fir blazed & scribed "T25S R1E S19 CC, BT" with brass washer marked "LS 866" attached, bears S.07°30'E., 31.3 ft.  
20" D. Fir blazed & scribed "T25S R1E S18 CC, BT" with brass washer marked "LS 866" attached bears N.77°00'E., 80.5 ft.

35

1/4 Corner for Sec. 13 only of T.25-1W.  
Found - 5/8" Steel tube buried 12" under the berm at the side of a skid trail  
1" Alum. cap attached marked "Property Corner"  
36" D Fir stump with axe marks in bark bears S.26°55'W., 20.8 ft.  
12" Cedar stump approx. 16" high with face charred from slash fire bears N.45°00'E., 55.8 ft.  
Set - Replaced with 2" x 30" Gal. Steel pipe 26" in the ground.  
Placed tube next to pipe. Marked the attached 2 1/2" brass cap T25S RIW 1/4 S13 PLS 866 1978"  
Cedar scribed "1/4 S13 BT" and attached brass washer marked "L.S. 866" bears S.20°55'W 77.8 ft.  
Drove green 6 ft. steel fence post 18" into the ground and painted red, bears N.45°56'W., 55.8 ft.  
Constructed mound of stones around the 2" x 30" steel pipe.

36

Closing Corner for Secs. 7 and 18 only.  
Found - 1 1/2" Pipe with 2 1/2" brass cap properly marked as recorded U.S. GLO 1927.  
Both had slid several feet down hill with pile of stones.  
38" D. Fir, N.23°49'E., 90.5 ft. Shows good scar.  
22" D. Fir, S.36°06'E., 97.3 ft. Shows good scar.  
Set - I reset orig. pipe with brass cap S.00°58'E., 1.32 ft. from the pipe I had previously set for the witness corner to the corner of sections 12 and 13. I constructed a mound of stones around it.

William J. Rupper, L.S. #866  
For: U.S. Forest Service  
November 1978  
C.S. 58/176

RE-RENEWED, SEE CORNER NO. #53  
RE-RENEWED, SEE CORNER NO. #54