

Douglas County Surveyor's Record of  
Government Corners Renewed

T 25

T. S.

R I E

E  
R. W. W. M.

KORE-CHAPMAN CO., EUGENE, ORE. 21001

48

Douglas County  
Surveyors Office  
L. E. Monrean,  
Deputy  
J. Lundeen  
R. Smith  
S.J. Flause  
Sept. 21, 1984  
S. 62/21

Closing Corner for Sections 3 and 4 only.  
Found - 1928 GLO 2 1/2" cap on a 2" iron pipe protruding 21" above  
ground, properly marked.  
12" now 18" fir bears S.60°E., 14.2 ft. to center of root  
crown 15.2 ft. to center of tree (Rec. S.60°E., 15.2 ft.) Has  
well healed single blaze.  
A 14" now 20" fir with well healed single blaze bears S.10°W.  
25.7 ft. to center of root crown.  
New BTs - 28" diam. D. fir double blazed and scribed "S 34 CS BT" bears  
N.21 1/2°E., 29.7 ft.  
29" diam. D. fir double blazed and scribed "T25S RIE CC S3  
CS BT" bears S.3 1/2°E., 28.5 ft.  
New BTs measured to center of root crown.

9/21/84

49

Douglas County  
Surveyors Office  
Randall Smith  
Stephen Flause  
Dec. 9, 1985  
C.S. 62/29

Corner #4, Mineral Survey #501  
Found - A Doug. Co. brass disk on an I.P. protruding 7 ins. above  
ground marked as noted in Ren. #28.  
An orig. BT, 36" now 39" dia. 3 1/2 ft. high D. fir stump with a  
partial well healed lower blaze bears N.48 1/4° W., 26.0 ft.  
agrees with Ren. #28. (Rec. N.48 1/4° W., 26.0 ft.)  
An orig. BT, a 18" now 22" dia. 2 1/2 ft. high D. fir stump with a  
single fully healed blaze bears S.14°W., 24.0 ft. agrees with  
Ren. #28. (Rec. S.14°W., 24.0 ft.) This BT will be  
lowered by May 1986 per Ron Murphy, N. Umpqua Ranger  
District.  
New BTs - 22" D. fir double blazed and scribed "4 MS 501 CS BT".  
Bears N.2°W., 26.7 ft.  
12" D. fir double blazed and scribed "4 MS 501 CS BT" bears  
S.61°W., 27.5 ft.  
Corner lies at west end of Steamboat Falls Campground near picnic tables.

12/9/85

50

Stamped  
in Error

Section Corner for Secs. 5, 6, 7 and 8.  
Found - 1927 GLO 3" brass cap on a 2" dia. I.P. leaning North protruding  
29" above ground.  
10" now 14" dia. western white pine with a partially healed  
single blaze "T25S RIE 5/BT" bears N.52°E., 11.2 ft.  
(Rec. N.55°E., 11.2 ft.) (Checked from plumb pos. of monument.)  
10" now 10" dia. western white pine with a partially healed single  
blaze "T25S RIE S8/BT" bears S.45°E., 15.8 ft. (Rec. S.43°E.,  
15.8 ft.) (BT checked from plumb position of monument.)  
12" now 20" dia. hemlock with a partially healed single blaze  
illegible scribing visible bears N.24°W., 13.2 ft. agrees with  
record. (Orig. BT called a spruce)  
12" now 13" dia. dead still standing western white pine with a  
partially healed single blaze "T25S RIE S7/BT" bears S.22°W.,  
45.5 ft. agrees with record. (BT checked from plumb position of  
monument.)  
Set - Plumb position of Brass cap/iron pipe remonumented as corner  
location distances and bearings fit well with record information.  
B.C./I.P. returned to plumb position and a 3 ft. dia. x 2 ft.  
high mound of stone placed around iron pipe.  
New BT - 8" dia. western white pine double blazed and scribed "T25S RIE  
S7 CS BT" bears S.19°W., 16.0 ft.  
Corner lies on a gentle SE slope.

1/13/86

51

Douglas County Surveyors Office  
Deputies: Randall Smith  
Stephen Flause  
January 13-14, 1986  
C.S. 62/31

Section Corner for Secs. 28, 29, 32 and 33.  
Found - 1927 GLO brass cap/iron pipe protruding 18" above ground, leaning  
7" southeast of plumb.  
8" now indeterminable dia. rotted 6" high D. fir stump. No scribing  
found bears N.56°E., 17.16 ft. (agrees with record)  
8" now 18" dia. D. fir with a fully healed single blaze bears  
S.34 1/2°E., 13.5 ft. (Rec. S.33°E., 20.46 ft. dist. is  
probably to NW BT.)  
8" now 17" dia. D. fir with a fully healed single blaze bears  
N.39°W., 19.6 ft. (Rec. N.39°W., 13.20 ft. dist. is probably  
to SE BT).