

**Douglas County Surveyor's Record of  
Government Corners Renewed**

T 25

T. S.

R 1 E

R. ~~W.~~<sup>E.</sup> W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97301

cont. from prev. pg. - (cor. for 28, 29, 32, 33)

51

8" now 15" dia. D. fir with a fully healed single blaze bears S.67 1/2° W., 13.8 ft. (Rec. S.69 1/2°W., 14.52 ft.)  
Set - USGLO brass cap/iron pipe returned to plumb position and a 2 ft. dia. mound of stone 14" high placed around I.P. BC/I.P. protrudes 4" above mound of stone.  
Plumb position of BC/IP remonumented as corner location. The NW and SE BTs distances appear to be interchanged; if that problem is corrected the bearings and distances to orig. bearing trees agree closely with record information.  
New BT - 14" dia. D. fir double blazed scribed "T25S R1E S28 CS BT" bears N.64 1/2°E., 51.3 ft.  
Corner lies on level ground.

1/14/86

1/4 Corner for Sections 30 and 31

52

Found - A 1927 GLO brass cap on an I.P. protruding 11 ins. above ground.  
18" now 24" dia. 6 ft. high fallen D. fir stump with a fully healed single blaze bears S.48°W., 23.8 ft. (agrees with orig.)  
10" now 16" dia. 2 ft. high decayed hemlock stump, with a partially healed blaze, scribing visible "S 30 BT" bears N.10 1/2°W., 33.0 ft. (agrees with rec. Orig.)  
6" now 10" dia. chinquapin with a partially healed double blaze no scribing visible bears N.26°E., 69.4 ft. (rec. N.26°E., 68.7 ft. dist. to center of trunk) Per Ren. No. 23  
New BTs - 8" W. fir double blazed, scribed "1/4 S30 CS BT" bears N.19 1/4°E., 56.3 ft.  
10" W. fir double blazed, scribed "1/4 S31 CS BT" bears S.30 3/4°W., 15.9 ft.  
8" D. fir double blazed, scribed "1/4 S31 CS BT" bears S.56°W., 34.6 ft.  
Corner lies on North edge of fire trail.

Section corner for Secs. 18 and 19 only. (west side)

53

Found - 1927 GLO brass cap, properly marked.  
30" Cedar snag, bears S.28°E., 6.4 ft.  
9" D. fir snag (down) bears S.40°E., 27.7 ft. Ren. #34  
10" D. fir bears N.77°E., 80.5 ft.  
15" D. fir snag bears S.07°30'E., 31.3 ft.  
New BT - 6" D. fir bears N.02°W., 21.5 ft. scribed "X" on small upper blaze and "BT" on small lower blaze. A 1/2" brass washer marked "RLS 1035" is nailed flush to lower blaze.

1/4 Corner for Section 13 only of T.25-1W.

54

Found - 1978 brass cap set by PLS 866, properly marked. Ren. #35  
36" Fir stump bears S.26°55'W., 20.8 ft.  
12" Cedar stump bears N.44°05'W., 55.8 ft.  
16" Cedar bears S.20°55'W., 77.8 ft.  
A 6' steel fence post bears N.45°56'W., 55.8 ft.  
New BT - 8" D. fir bears N.37°W., 7.0 ft. with single blaze scribed "1/4 S13 RS1035 BT". A 1/2" brass washer marked "RLS 1035" is nailed flush to lower end of blaze.

"I hereby certify the above corner points were perpetuated as hereon described on June 11, 1987. U.S.F.S. bearing tree signs and monument signs were placed on all BT's without them and a 6" red band was painted around each BT.

West 1/4 Corner for Section 7 only.

55

Found - 1928 2 1/2" dia. GLO brass cap on a 1" O.D. iron pipe protruding 11" above ground. A 2 ft. dia. mound of stone is found along east edge of BC/IP. (Rec. raised mound of stone 3 ft., 2 ft. high E. of cor.) (orig. corner)  
20" now 39" dia. D. fir with a fully healed single blaze, bears N.56°E., 19.1 ft. (Rec. N.60°E., 19.1 ft.) (Orig. BT.)  
New BTs - 14" dia. D. fir double blazed and scribed "1/4 S7 CS BT" bears S.28°E., 4.6 ft.  
15" dia. D. fir double blazed and scribed "1/4 S7 CS BT" bears S.2°E., 34.8 ft.  
8" D. fir double-blazed & scribed "1/4 S7 CS BT" bears N.71°E. 32.7'.

Douglas County Surveyor Office  
R. Smith/S. Flause  
Jan. 13-14, 1986  
C.S. 62/31

Douglas County Surveyor Office  
Randall Smith  
Stephen Flause  
April 8, 1986  
C.S. 62/34

Gerald V. Nygren  
For: U.S.F.S.  
June 11, 1987  
C.S. 63/50

Douglas County Surveyors Office  
Randall Smith, Dep.  
Stephen Flause  
Terrie Franssen  
April 4, 1991  
C.S. 64/13