

Douglas County Surveyor's Record of  
Government Corners Renewed

T 25 T. S. R 1 E R. W/W.M.

FORE-CHAPMAN CO., EUGENE, ORE., 1981

56

Closing Corner for Secs. 6 & 7 only. (NW Cor. Sec. 7)  
Found - 1927 GLO 2" I.P., firmly set, projecting 9" above the ground  
with a 2½" brass cap, properly mkd.  
24" D.Fir stump bears N.61°E., 6.6 ft. with a healed blaze.  
24" windfallen D.Fir bears S.17°E., 49.5 ft. with a healed blaze.  
14" Grand Fir bears S.7°E., 42.7 ft. with healed blaze. Ren. #494  
New BT - 8" Grand Fir bears N.44°E., 56.6 ft. scribed "T25S R1E S6 BT".  
5/13/92

57

West 1/4 Corner, Section 7 only.  
Found - 1927 GLO brass cap, properly mkd., on 1" I.P., firmly set, flush  
with the ground.  
30" broken top D.Fir bears N.50°E., 47.5 ft. with a healed blaze.  
(Rec. N.49°E., 71 lks.) (1927 BT)  
52" uprooted D.Fir bears S.46°E., 43.0 ft. with a burned blaze.  
(Rec. S.51°E., 65 lks.) 1927 BT.  
42" D.Fir stump bears N.2°E., 14.0 ft. with scribe marks "1/4  
S7 CS BT" visible. Ren. No. 19  
48" D.Fir stump bears S.78°E., 27.2 ft. with scribe marks  
"1/4 S7 CS BT" visible. Ren. No. 19  
New BT - 10" D.Fir bears S.59°E., 33.8 ft. scribed "1/4 S7 BT".  
4/14/92

58

East 1/4 Corner Section 12 only, of T.25-1W  
Found - 1966 DCSO brass cap, properly mkd., on 1½" I.P., firmly set,  
projecting 16" above ground. Ren. No. 20  
43" Fir bears N.60°E., 10.5 ft. with a healed blaze. (Rec.  
N.63°E., 18 lks.) 1896 BT.  
21" Fir stump bears N.47°W., 35.0 ft. with a healed blaze. (Rec.  
N.49°W.) 1896 BT  
36" Fir stump bears S.21°W., 42.4 ft. with scribe marks "12"  
visible. (Rec. 60 lks.) 1927 GLO BT.  
20" D.Fir bears N.78°E., 24.9 ft. with a healed blaze. Ren. No. 20  
1/2" steel tube with 1" survey cap bears S.58°E., 1.6 ft. See  
Ren. No. 57 in T.25-1W.  
New BT - 9" D.Fir bears S.30°W., 59.9 ft. scribed "1/4 S12 BT".  
5/14/92

59

Sec. Cor. for 25 and 36 only, of T.25-1W  
Found - 1927 GLO brass cap on 2" I.P. firmly set, projecting 20" above  
the ground.  
42" Pine stump bears N.23°W., 33.7 ft. with a healed blaze. (1896  
23" x 15 ft. tall Pine snag bears S.605W., 106.5 ft. with a  
healed blaze. (Rec. 108.3 ft. Ren. No. 10  
23" D.Fir bears N.39°W., 42.9 ft. with a healed blaze. (Rec.  
42.0 ft.) Ren. No. 10  
New BT - 6" D.Fir bears S.25°W., 31.9 ft. scribed "T25S R1W S36 BT".  
4/27/92

60

Wit. Corner for Secs. 12 and 13 only, of T.25-1W  
found - 1966 DCSO brass cap on 1½" I.P., firmly set, projecting 16"  
above ground. Ren. No. 14  
12" Yew bears N.26°E., 39.0 ft. with scribe marks "WC CS BT"  
visible. 1966 BT.  
8" Yew bears N.85°E., 24.9 ft. with scribe marks "WC CS BT"  
visible 1966 BT.  
1/2" steel tube with a 1" alum. cap is set flush with the south  
edge of the 1" BC/IP. Ren. No. 24 in T.25-1W  
New BT - 6" D.Fir bears N.42°W., 31.1 ft. scribed "T25S R1W WC S12 BT".  
5/15/92

61

Sec. Cor. for Secs. 1 & 12 only of T.25-1W  
Found - 1927 GLO 2" I.P., firmly set, projecting 9" above a 30" dia.  
mound of stone with a 2½" properly mkd. brass cap.  
60" d.Fir stump bears S.48°W., 19.1 ft. with a healed blaze.  
32" d.Fir stump bears N.71°W., 26.4 ft. with a healed blaze and  
a sheet metal cap over the stump. 1896 BT.  
6" W.Fir bears N.59°W., 29.4 ft. with scribe marks visible. (Rec  
Hemlock) Ren. No. 16  
14" W.Fir snag bears S.74°W., 61.6 ft. with scribe marks visible  
New BT - 10" W.Fir bears S.23°W., 73.0 ft. scribed "T25S R1W S12 BT".  
5/13/92

Kristian DeGroot, L.S. #1941  
For: U.S.F.S. April/May 1992  
C.S. File 63/138

Note: All BTs have a 6" red band painted around the tree & the blazed face painted red. U.S.F.S sign 54-3, BEARING TREE, and sign 54-9 LAND SURVEYING MONUMENT, are nailed to all BTs. All new BTs have double blazed faces with a brass washer stamped "PLS 1941" nailed into the lower blaze. Brgs. are taken to the center of the tree at the root crown & dists. are measured to the root crown at the side & center of the tree.