

Douglas County Surveyor's Record of
Government Corners Renewed

T 25 S T. S. R 1 E R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97401

62

Cor. Secs. 26, 27, 34, & 35

Found - 2" O.D. iron pipe buried 12" below the rocked road surface of USFS
Road 4713-500 with a 1927 2½" brass cap properly stamped.

No evidence of Grant's (1957) (Rem #1)

Set - 2½"x30" aluminum monument, 26" in the ground with a ¾"
aluminum cap stamped:

US DEPT. OF AGRICULTURE FOREST SERVICE

T25S R1E

S27 RM

S.29°E., 43.3

1997

PLS 1941

bears N.29°W., 43.3 ft.

Chiseled "X BO" in 3" tall letters in a vertical rock face that bears
S.13°E., 13.35 ft. to the center of the X.

5/8"x30" iron rod with plastic cap "BTS ENG-SUR" bears S.57°W.,
45.7 ft.

9" D.Fir bears N.57°E., 35.1 ft. scribed "T25S R1E S26 BT" with a
brass washer stamped "PLS 1941" nailed in lower blaze.

Painted a 6" red band and BT faces red and nail USFS "BEARING
TREE" and "LAND SURVEY MONUMENT" signs to
bearing trees.

Kristian DeGroot, PLS 1941

For: USFS

Crew: Les Fanning, Matt

Dixon, & Aaron Fanning -

March 1998

C.S. File 65/20-697

63

1/4 Cor. Secs. 27 & 34

Found - 1" O.D. iron pipe, firmly set, projecting 10" above the ground with a
2½" brass cap properly stamped.

30" high stumped D.Fir bears N.31°W., 37.0 ft. w/ healed face. 1927

24" Cedar root crown bears S.25°W., 15.2 ft.

Set - I build a stone mound, 48" dia., base to top of monument.

6" D.Fir bears N.21°E., 12.5 ft. scribed "¼ S27 BT"

6" D.Fir bears S.20°E., 12.5 ft. scribed "¼ S34 BT"

I nail a brass washer stamped "PLS 1941" into the lower blaze of the
new BTs and paint a 6" red band and BT face red and nail
USFS "BEARING TREE" and "LAND SURVEY
MONUMENT" signs to all BTs.