

LANE COUNTY SURVEYORS OFFICE
DEPARTMENT OF PUBLIC WORKS

FILE NO: 24-15-35 S1/4 ONLY
TRGCDB: 2415540100
INDEX NO:

14958

CORNER REPORT

THE 1/4 CORNER ON SOUTH LINE OF SECTION 35 ONLY, T24S, R1E, W.M.

DATE	1898	1928	1979
SURVEYOR	A. GESNER	J. COLLINS	D. GAYLORD
SOURCE	GLO VOL R-411	GLO VOL R-535	RE 7914 & DOUG. CO. RENEWAL
MONUMENT FOUND		6" x 10" x 4" BASALT STONE, "1/4" FD. ON NORTH FACE	20" x 14" x 5" STONE. BROKE IN HALF AND LOOSELY SET
MONUMENT SET	20" x 10" x 4" BASALT STONE MK'D "1/4" ON NORTH SIDE	ADD "S35" ON NORTH FACE TO REFER TO SEC. 35 ONLY	1-1/2" x 36" I. PIPE W/ B. CAP, BURY STONE ALONGSIDE
BEARING OBJECT 1	10" FIR MARKED "1/4 S BT" S45°30'E @ 4 LKS = 2.6'	30" FIR, HEALED FACE S44°E @ 45 LKS = 29.7', MARKS GONE	30" FIR STUMP, CHOPPED OUT BLAZE S45°30'E @ 29.7'
BEARING OBJECT 2	7" MADRONE MK'D "1/4 S BT" N33°E @ 18 LKS = 11.9'	12" MADRONE, HEALED FACE, N32°E @ 16 LKS = 10.6'	MADRONE STUMP, NO MARKS & BLOW-DOWN, N33°E @ 11.9'
BEARING OBJECT 3		10" FIR MARKED "1/4 S35 BT" N44°E @ 42 LKS = 27.7'	14" D. FIR STUMP W/ MARKS IN DOWN SNAG N44°W @ 25.9', 27.72' SLOPE DISTANCE
BEARING OBJECT 4		SET B. CAP N1/4 SEC. 2 ONLY S88°14'W @ 0.96 CHS = 63.4'	N1/4 SEC. 2 BRS WEST @ 65.97'
BEARING OBJECT 5			26" D. FIR MK'D "1/4 S35 BT" ON DOUBLE BLAZE N54°W @ 70.2'
BEARING OBJECT 6			19" D. FIR MK'D "1/4 S35 BT" ON DOUBLE BLAZE N24°E @ 27.2'

BOLDED ENTRIES IN THE ABOVE TABLE CORRESPOND WITH FOUND OBJECTS DESCRIBED IN "EVIDENCE RECOVERED" SHOWN BELOW. THOSE ENTRIES NOT BOLDED WERE NOT FOUND.

CORNER EVIDENCE

EVIDENCE RECOVERED:

AT THE CORNER POSITION FOUND A 2-1/2" BRASS CAP DATED 1979 IN A STONE MOUND, AND MARKED 'PLS 1636'.
 1898 [1] A 30" ROTTEN FIR STUMP WITH A CHOPPED OUT FACE BRS S44°10'E @ 29.7' (S45°30'E @ 29.7').
 1928 [3] A 14" ROTTEN FIR STUMP WITH "1/4 S35 BT" FOUND IN LOOSE SLAB BRS N43°10'W @ 26.6' (N44°E @ 27.7').
 1928 [4] A 2-1/2" BRASS CAP MARKING THE NORTH 1/4 CORNER OF SECTION 2 ONLY BRS S89°41'40"W @ 65.65' (S88°14'W @ 63.4').
 1979 [5] A 34" D. FIR WITH A HEALED FACE BRS N53°06'W @ 70.4' (N54°W @ 70.2').
 1979 [6] A 26" D. FIR WITH A HEALED FACE BRS N24°30'E @ 27.0' (N24°E @ 27.2').

MONUMENT SET: NOTHING NEEDED, ACCEPTED THE FOUND BRASS CAP AS MARKING THE CORNER POSITION.

ACCESSORIES ESTABLISHED:

2007 [7] SET A 2" ALUM. CAP "LCSO-RP1-2007" ATOP A 5/8" x 30" REBAR BRS S16°27'E @ 11.47'.

NOTES AND OTHER INFORMATION

GEOGRAPHIC MAP LOCATION: USE FOR NAVIGATING TO CORNER AREA – NOT OF SURVEY GRADE ACCURACY.

LATITUDE = N 43°26'17.1" LONGITUDE = W 122°39'07.5" NAD 83/91 VALUES

BASIS OF BEARING: TRUE BEARINGS BASED ON GPS OBSERVATIONS.

EQUIPMENT USED: WILD TC-1010 TOTAL STATION & HP-48 GX DATA COLLECTOR.

BEARING TREES: ALL DISTANCES SHOWN ARE TO CENTER UNLESS OTHERWISE NOTED.

DATE: SEPTEMBER 13, 2007

BY: BRUCE BOTHEL, P.L.S., ASSOCIATE SURVEYOR **BB**
JOHN RANDALL, ENGINEERING TECH. I **JR**

LANE COUNTY SURVEYORS OFFICE
DEPARTMENT OF PUBLIC WORKS

FILE NO: 24-15-35 S1/4 ONLY
TRGCDB: 2415540100
INDEX NO: **14958**

