

Douglas County Surveyor's Record of
Government Corners Renewed

T 25 T. S. R 2 E R, . W. M. E

ROKE-CHAPMAN CO., EUGENE, ORE. 21881

Dennis Gaylord
U.S.F.S.
Bill West
Oct. 26, 1978
C.S. 59/30

MOVED TO CS 62/50-9

1/4 Corner for sections 10 and 11.

REFERENCED NOTES ONLY

Found - 7" cedar corner tree, is still standing but nearly dead. Unhealed blazes show scribing of "1/4" on the west and "S11" on the east. 11" hemlock snag with a healed blaze bears N.49°30'W., 13.1 (Rec. N.46°W., 11.88 ft.) A 16" cedar snag bears N.62°30'E., 11.9 ft. (Rec. N.59°E., 11.54') Previously opened blaze has scribing "1/4 S11/BT"

This corner falls in a proposed landing & will therefore be destroyed during construction.

New accessories:

A 5/8" x 36" I. rod with a 1 1/2" alum. cap attached bears N.80°30'E., 70.7 ft.

17" cedar bears N.18°E., 56.1 ft. scribed "1/4 S11 CS BT" on a double blaze.

A 5/8" x 36" I. rod with a 1 1/2" alum. cap attached bears N.47°30'E., 64.9 ft.

Placed county BT signs on all 3 BTs and on corner tree.

10/26/78

Section corner for Secs. 16, 17, 20 and 21

Found - 2" diam. iron post, firmly set, projecting 12" above ground, leaning slightly northerly, with 1928 GLO brass cap marked: "T25S R2E S17 S16 S20 S21 1928". Used point where the I.P. comes out of the ground as the corner point.

12" D. fir stump, N.52°E., 9.3 ft. with log alongside with scribe marks "5S 2E S6 BT" visible on partially healed blaze.

12" D. fir, N.16°W., 35.6 ft. with healed blaze.

Set - Added a 2 foot diam. mound of stone. Iron pipe now projecting 4".

New BTs - 6" D. fir, S.41 1/2° E., 12.8 ft. scribed "T25S R2E S21 CS BT"

6" D. fir, S.25 1/2°W., 30.2 ft. scribed "T25S R2E S20 CS BT" on a single blaze.

Note - Corner is in cutting line of old clearcut unit on steep east slope. To reach, proceed up USFS Rd. #3816 approx 2 miles from Steamboat Creek, then follow north boundary of clearcut unit #25-2E-16-1 approx. 1/4 mile to the corner. Corner is about 530 ft. west of 2 small cks.

5/10/83

Section corner for Secs. 18 and 19; and Secs. 13, 24 of T.25-1E.

Found - 1927 GLO brass cap, properly marked, on 2" diam. iron post, firmly set, projecting 6" above ground, leaning westerly, Used the point where the I.P. comes out of the ground as the corner point.

Orig. 26" D. fir, stump, N.31°E., 31.9 ft. (Rec. 32.3 ft.) with healed blaze.

Orig. 44" D. fir, S.28°E., 9.9 ft. with healed blaze.

A roothole, N.38°W., 51.5 ft. with 14" D. fir log alongside with fragmentary scribe marks visible on partially healed blaze.

New BTs - 12" maple, N.78°E., 29.2 ft. scribed "T25S R2E S18 CS BT" on single blaze.

5" W. fir, S.73°W., 26.8 ft. scribed "T25S R1E S24 CS BT" on single blaze.

40" D. fir, N.70°W., 38.3 ft. scribed "T25S R1E S13 CS BT" single blaze. (Blaze is on old logging scar.)

Note: Corner is approx. 250 ft. south of USFS Rd. #3811-100 in the NW corner of clearcut unit #25-2E-19-5. Corner is about 66 ft. north of creek.

5/10/83

James N. Landrum
U.S. Forest Service
(Deputy, Doug. Co.
Surveyors Office)
Witness: Leonard
Herzstein
May 10, 1983
C.S. 62/10

Jim Landrum, U.S.F.S.
Deputy, Doug. Co.
Surveyors Office
Leonard Herzstein,
Witness.
May 10, 1983
C.S. 62/10

Jim Landrum, U.S.F.S.
Deputy, Doug. Co.
Surveyors Office
Leonard Herzstein,
Witness
May 12, 1983
C.S. 62/10

Section corner for sections 30 and 31; and secs. 25 & 36 of T.25-1E.

Found - 1927 GLO brass cap, properly mkd., on 2" iron post, firmly set, projecting 6" above the ground.

A 20" D. fir, N.32°E., 40.9 ft. with healed blaze.

A 21" R. cedar, S.42°E., 29.6 ft. (rec. 30.4 ft.) with healed blaze.

A 17" W. fir, S.56°W., 21.5 ft. (rec. 22.4 ft.) with healed blaze.

A roothole, N.86°W., 21.1 ft. with decayed log, size indeterminate alongside with fragmentary scribe marks visible on decayed blaze.

C O N T . N E X T P A G E