

Douglas County Surveyor's Record of
Government Corners Renewed

T. 25 S. T. S. R. 2 E. R. W. W. M.

KORE-CHAPMAN CO., EUGENE, ORE. 97401

C O N T. _ _ _

Douglas County
Surveyors Office
S. J. Flause and
R. W. Smith, Deputies
March 30, 1988
C.S. 62/50-9

(1/4 Cor. 10 & 11)

set and protrudes approx. 5" above ground and bears N.41½°E.,
66.6 ft. (Rec. N.47°30'E., 64.9 ft.)

- Set - The corner position is perpetuated by establishing a brass cap monument within the apparent remains of the corner tree. This position agrees well with the well defined remaining evidence of the original northeast bearing tree. Two out of three distances to the references from Renewal #5 agree well with record and the distance to the NNE reference would indicate a possible error in slope measurement. Bearings from corner tree remains to the references from Ren. #5 indicate a possible problem with compass declination. Monument set is a 2 3/8" dia. brass cap marked "Douglas County Surveyors T25S 1/4 S10|S11 R2E 1988" on a 1" I.D. 32" long iron pipe protruding 10" above ground.
- New BT - A 17" dia. 2 foot tall cedar stump with a boat spike driven into stump through a bearing tree tag. Boat spike is stamped "B0 1" and bears S.81°W., 24.5 ft. dist. from BC monument.
- Monument on a northwest slope at top of clearcut and just off of log landing at turn to east in USFS Road #3850.

3/30/88

12

1/4 Corner for Sections 29 & 30

Found - 2½" dia. properly marked brass cap on a 1" O.D. iron pipe, protrudes 11" above ground. (U.S. General Land Office Survey, 1928; Original corner)

Accessories Found -

- 14" now 26" dia. D.Fir with a fully healed single blaze, bears N.82°E., 6.0 ft. (rec. N.82°E., 7.9 ft. Distance fits well with a slope measurement). O.B.T.
- 10" now 11" dia. D.Fir with a fully healed single blaze bears N.28°W., 10.6 ft. (rec. N.32°W., 10.6 ft. Bearing possibly read on wrong side of compass). O.B.T.

New Accessories -

- 12" dia. D.Fir double blazed and scribed "¼ S29 CS BT" bears S.35°E., 9.5 ft.
- 9" dia. Maple double blazed and scribed "¼ S30 CS BT" bears S.30°W., 36.4 ft.

Douglas County
Surveyor's Office
Randall Smith
Stephen Flause
Nov. 6, 1996
C.S. File 65/9-32

13

1/4 Corner for Sections 29 & 28

Found - 2½" dia. brass cap on 1" O.D. iron pipe, protrudes 14" above ground. (U.S. General Land Office Survey, 1928; Original corner)

Accessories Found -

- 20" now 24" dia. D.Fir with a fully healed single blaze, bears N.65°E., 40.9 ft. (agrees with rec.) O.B.T.
- 8" now 9" D.Fir with a fully healed single blaze, bears N.85°W., 42.2 ft. to center of trunk 42.9 ft. to center of root crown. (rec. N.85°W., 42.2 ft.) O.B.T.

New Accessories -

- 11" dia. W.Fir double blazed and scribed "¼ S29 CS BT" bears S.33°W., 16.0 ft.
- 21" dia. Maple double blazed and scribed "¼ S28 CS BT" bears N.79°E., 35.0 ft.

Douglas County
Surveyor's Office
Randall Smith
Stephen Flause
Nov. 6, 1996
C.S. File 65/9-33