

Douglas County Surveyor's Record of
Government Corners Renewed

T. 25 S. T. S. R. 2 E. R. W. W. M.

ROKE-CHAPMAN CO., EUGENE, ORE. 97501

14

Douglas Co. Surveyor's
Office
Randall Smith
Shen Flause
21, 1996
File 65/9-34

Section Corner for Sections 20, 21, 28 & 29
Found - 2½" dia. brass cap on a 2" O.D. iron pipe protrudes 30"
above ground. A 2 ft. dia. mound of stone is around base.
(U.S. General Land Office Survey, 1928; Original corner)
Accessories Found - (Original bearing trees)
12" now 12" dia. 6 ft. high Cedar stump with an unhealed
single blaze, scribing visible "25S 2E S21 BT" bears
N.67°E., 8.5 ft. (rec. N.67°E., 7.9 ft. dist. to blaze)
16" now 20" dia. 5 ft. high Hemlock stump with an unhealed
single blaze, scribing visible "25 2E S28 BT" bears
S.41½°E., 10.7 ft. (rec. S.39°E., 9.9 ft. dist. to blaze)
16" now 20" dia. 5 ft. high Hemlock stump with an unhealed
single blaze, scribing visible "25 2E S2 BT" bears
S.45°W., 15.1 ft. (rec. S.45°W., 14.5 ft. dist. to blaze)
9" now 9" dia. down and rotted Hemlock with a rotted
unhealed single blaze, bears N.31°W., 17.8 ft. to root
hole. (agrees with rec.)
New Accessories -
5" dia. D.Fir double blazed and scribed "T25S R2E S21 CS BT"
bears N.82°E., 28.2 ft.
5" dia. D.Fir double blazed and scribed "T25S R2E S21 CS BT"
bears N.43½°E., 23.8 ft.
3" dia. Cedar double blazed and scribed "X BT"
bears S.11°E., 11.2 ft.
5" dia. D.Fir double blazed and scribed "T25S R2E S20 CS BT"
bears N.75°W., 6.0 ft.
Note - Will set monument lower at a future date.

15