

Douglas County Surveyor's Record of
Government Corners Renewed

T. 26 S. T. S. R. 2 E. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

FD OK 2/24
M. DEAN
M 98-6
C.S. 58/204

FD OK 12/84
R. DEAN
M 98-4
C.S. 58/204
(CARRIAGE)

Vernon "Ray" Tracy
Jack Heritage & V. Perron
October, 1969 C.S. File No. 52/43

HES 178
Robert Dean
FDOK Jan 1985
M 98-20
CS 63/5-2

Corner No. 3 of H. E. S. #142.

Found - Orig. Corner Stone, in place, mkd: "X" on top with "HES 142" on side.
Orig. 6", now 24" Y. Pine, alive, S. 16 1/2° E. 35.0 ft., healed blaze.

Rescribe: "3 HES 142 CS BT".
18" D. Fir, N. 22° E. 52.1 ft., alive, blaze healed, we tag. Ren. #9.
Set - Brass Cap in place of Stone: County Surveyor's T 26 S R 2 E.
(Reset Cor. Stone Alongside) Office, 1969 Cor. #3 HES 142

This corner lies on moderate S.E. slope.

10/27/69

Corner No. 4 of H. E. S. #142.

Found - Orig. Corner Stone, in place, & mkd: "X" on top with
"HES 142" facing claim.

Orig. 30", now 36" D. Fir, alive, S. 37 1/2° E. 122.1 ft., shows good scar. We Tag.
Orig. 6", now 18" Fir, N. 22° 10' E. 89.1 ft., now stump. We open & find scribe.
Ren #10 BT: 16" D. Fir S. 62° W. 7.9 ft., alive, healed blaze, we tag.

Set - Brass Cap in place of Stone: County Surveyor's T 26 S R 2 E.
(Reset Cor. Stone Alongside) Office, 1969 Cor. #4 HES 142

New BT's: 8" D. Fir N. 28° E. 19.4 ft. mkd: "4 HES 142 CS BT".
This corner lies about 10.83 chs. westerly of Cor. #5, HES #142.

10/27/69

Corner No. 1 of H. E. S. #178.

Found - Orig. 30", now 32" Pine Corner Tree. Opened & "S178" visible.

Orig. 14", now 16" Oak Snag, S. 39° 40' W. 35.0 ft., scribe vis. on unhealed bl
Orig. 14", now 32" D. Fir, alive, N. 38° W. 32.3 ft., shows good scar, we tag.

Set - At Base of Cor. Tree, 24" W. of center Brass Cap Mkd: #54
County Surveyor's T 26 S R 2 E
Office, 1969 Cor. #1 H.E.S. 178

New BT's: 12" D. Fir N. 74° W. 31.2 ft. mkd: "1 HES 178 CS BT".
15" D. Fir S. 62° W. 7.4 ft. mkd: "1 HES 178 CS BT".

This corner lies on southerly side of old Illahee Road, course N. E.
Bear. & Dist. from center of Corner Tree.

10/28/69

Corner No. 2 of H. E. S. #182.

Found - Granite Corner Stone, in place, mkd: "2 HES 182" on side facing claim

Orig. 36", now 45" D. Fir, alive, S. 29° 20' W. 110.9 ft., shows good scar, Tag.
Lookout Mt. bears S. 64° W. as called for.

Set - Brass Cap in place of Cor. Stone mkd: County Surveyor's T 26 S R 2 E
Office, 1969 Cor. #2 HES 182

New BT's: 14" D. Fir N. 16° E. 53.4 ft. mkd: "2 HES 182 CS BT".
16" D. Fir S. 81° E. 40.1 ft. mkd: "2 HES 182 CS BT".

This corner lies on top of rocky spur, sloping S. 25° W.

Note - Brass Cap set in Mound of Stone 3 ft. in diam. & 2 ft. high.

10/29/69

Corner No. 3 of H. E. S. #178.

Found - Corner Stone, in place & mkd: "3 HES 178" on side & "X" on top. Ren #1
Orig. 14" ?, now 40" D. Fir, alive, N. 83° 15' E. 77.2 ft., shows good scar, Tag.

10", now 18" D. Fir, alive, N. 17 3/4° W. 15.4 ft., shows very good scars, Tag.
Set - Brass Cap at Cor. in place of Stone, mkd: County Surveyor's T 26 S R 2 E
Office, 1969 Cor. #3 HES 178

New BT: 13" D. Fir N. 54° W. 7.1 ft. mkd: #3 HES 178 CS BT".

This cor. lies on steep, southerly slope about 100' S. of old Illahee
Guard Station Road.

10/28/69

Corner No. 4 of H. E. S. #178.

Found - No trace of I. Rod called for in Ren. #2. Old Corner Stone broken
in 2 pieces with mkd. "4 HES 178" on smaller piece.

Orig. 14", now 20" Oak, alive, N. 74° W. 84.5 ft., faint scribe mks. visible.
Orig. 14", now 36" Pine Stump, N. 75° 15' E. 15.2 ft., blaze visible on top.

Set - Brass Cap at Cor. Mkd: County Surveyor's T 26 S R 2 E
(Reset Cor. Stone Pieces Alongsd) Office, 1969 Cor. #4 HES 178

New BT's: 18" Y. Pine S. 7 1/2° E. 88.1 ft. mkd: "4 HES 178 CS BT".
16" D. Fir S. 83° W. 77.2 ft. mkd: "4 HES 178 CS BT".

This corner lies 8.0 ft. N. of fence, course Easterly & Westerly.

10/28/69

25

26

27

28

29

30

RE-RENEWED SEE CORNER NO.