

Douglas County Surveyor's Record of
Government Corners Renewed

T. 26 S. T. S. R. 2 E. R.W.W.M.

KOKE-CHARMAN CO., EUGENE, ORE. 21001

36

Corner No. 4 of H. E. S. #182.
Found - Corner Stone, in place, mkd: "X" on top & "4 HES 182" on side facing claim.
Remains of Mound of Earth with Pits to either end 3½ ft. in claim, as called for in old field notes.
Orig. 48", now 52" Fir, alive, N. 69° 45' W. 23.8 ft., shows good scar, we tag.
Orig. 40", now 50" Fir, N. 26° 30' W. 49.5 ft. (Rec. 42.9) or 10 lk. difference. Alive, shows good scar, we tag.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 26 S R 2 E
(Reset Stone Alongside) Office, 1969 Cor. # 4 HES 182
New BT's: 6" D. Fir S. 87° E. 19.2 ft. mkd: "4 HES 182 CS BT".
8" D. Fir N. 21° E. 25.5 ft. mkd: "4 HES 182 CS BT".
Corner lies on moderate southeast slope. 10/30/69

37

Corner No. 1 of H. E. S. #227.
Found - 1½" I. Pipe at corner point in good condition & BT's., See Ren. #6.
18" D. Fir N. 37° E. 31.0 ft., alive, face burned, scribe visible.
16" D. Fir N. 67° W. 38.9 ft., now sawed stump, scribe visible.
New BT: 18" D. Fir N. 56° W. 28.1 ft. mkd: "1 HES 227 CS BT".
This corner lies on fence corner 40 ft. W. of Gateway.
Remains of Orig. BT. Stumps still evident. 10/27/69

38

Corner No. 1 of H. E. S. #229.
Found - Original Corner Stone, in place, mkd: "X" 1 HES 229".
Orig. 6", now 24" D. Fir, Alive, N. 66° 15' W. 41.6 ft., shows good scar, we tag.
Only Madrone Stool at Locus Orig. BT. to N. E.
Set - Brass Cap in place of Stone mkd: County Surveyor's T 26 S R 2 E
Office, 1969 Cor. # 1 HES 229
New BT: 12" D. Fir N. 36° E. 36.4 ft. mkd: "1 HES 229 CS BT".
This corner lies in dense growth of Madrone. 10/30/69

39

Corner No. 2 of H. E. S. #229.
Found - Corner Stone, in place, mkd: "X" on top & "2 HES 229" on side facing claim.
Orig. 16", now 23" Fir, alive, N. 82° E. 21.1 ft., shows good scar, we tag.
Orig. 16", now 22" Fir, alive, N. 28° E. 43.6 ft., shows good scar, we tag.
Set - Brass Cap in place of Stone mkd: County Surveyor's T 26 S R 2 E
(Reset Stone alongside) Office, 1969 Cor. # 2 HES 229
New BT: 10" D. Fir S. 63° W. 24.6 ft. mkd: "2 HES 229 CS BT".
This corner lies on the edge of bench beginning to roll off to very steep N. E. slope. 10/31/69

40

Corner No. 3 of H. E. S. 229.
Found - Corner Stone, in place, mkd: "X" HES 229".
Orig. 14", now 22" Fir, alive, S. 56½° E. 12.5 ft., shows good scar, we tag.
Orig. 8", now 15" Fir, alive, N. 26° 45' E. 15.2 ft., shows good scar.
Rescribe: "3 HES 229 CS BT".
Set - Brass Cap in place of Stone mkd: County Surveyor's T 26 S R 2 E
(Reset Stone alongside) Office, 1969 Cor. # 3 HES 229
New BT: 9" D. Fir S. 81° W. 6.6 ft. mkd: "3 HES 229 CS BT".
This corner lies on steep easterly slope that descends to Copeland Creek. 10/31/69

41

Corner No. 4 of H. E. S. #229.
Found - Orig. Corner Tree, 30", now 42" D. Fir, alive, shows good scar, facing claim.
Orig. 28", now 40" D. Fir, N. 85½° E. 13.9 ft. (rec. S 85½° E) Alive, shows good scar, we tag.
Orig. 24", now 36" Fir sawed stump, N. 39½° W. 110.2 ft., bottom of #56 axe blaze visible on top of stump.
At Point 4.0 ft. north of the center of old Corner Tree,
Set - Brass Cap at Cor. Mkd: County Surveyor's T 26 S R 2 E
Office, 1969 Cor. # 4 HES 229
New BT's: 6" D. Fir S. 85° W. 32.3 ft. mkd: "4 HES 229 CS BT".
9" D. Fir N. 6° W. 62.1 ft. mkd: "4 HES 229 CS BT".
Note - Bearings & distances from center of old corner trees. 10/31/69

Vernon "Ray" Tracy
Jack Heritage & V. Perron
October, 1969 C. S. File No. 52/43

Case FO. ok 12/30/64
R. DEAN M 98-14

FO. ok By
R. DEAN

FO. ok By R. DEAN
M 98-14

RE-RENEWED, SEE CORNER NO. #49

#56