

Douglas County Surveyor's Record of
Government Corners Renewed

T. 26 S. T. S. R. 2 E. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

42

Corner No. 5 of H. E. S. #229.

Found - Corner Stone, in place, mkd: "X" on top & "5 HES 229 on side facing claim.

Orig. 15", now 19" Fir, alive, N.51°15'W. 5.9 ft., shows good scar.

Rescribe: "5 HES 229 CS BT".

Orig. 12", now 16" Fir, alive, N.48°30'E. 5.3 ft., shows good scar.

Rescribe: "5 HES 229 CS BT".

Set - Brass Cap in place of old Corner Stone mkd: (Reset Stone Alongside)

County Surveyor's T 26 S R. 2 E

Office, 1969 Cor. # 5 HES 229

This corner lies on top of low rounded spur, sloping gently N. E.

10/31/69

*Case File # 12/30/69
By R. DeW. - 11/98-16
C.S. 63/15*

43

Corner No. 6 of H. E. S. #229.

Found - Orig. 16", now 18" D. Fir Corner Tree, alive, shows good scar facing claim. Open & find "S22" scribe & reverse.

Orig. 16", now 21" Fir, alive, N.42°15'W. 9.2 ft., shows good scar.

Rescribe: "6 HES 229 CS BT".

Orig. 20", now 22" Fir, alive, N.85°45'E. 8.6 ft., shows good scar.

Rescribe: "6 HES 229 CS BT".

At a point 24" N.60°E. from center of Corner Tree, Set -

Brass Cap at Cor. Mkd: County Surveyor's T 26 S R 2 E

Office, 1969 Cor. # 6 HES 229

This corner lies on moderate N. E. slope.

10/31/69

RE-RENEWED, SEE CORNER NO. #57

44

Corner No. 7 of H.E. S. #229.

Found - Corner Stone, in place, mkd: "X" on top & "7 HES229" on side facing claim.

Orig. 8", now 26" Pine, alive, N.66½°W. 37.0 ft., shows scar, we tag.

Orig. 7", now 24" Pine, alive, S.45°45'W. 27.1 ft., shows scar, we tag.

At Point in place of Corner Stone, Set - (Reset Stone Alongside)

Brass Cap at Cor. Mkd: County Surveyor's T 26 S R 2 E

Office, 1969 Cor. # 7 HES 229

New BT's: 15" Pine N.14°E. 31.9 ft. mkd: "7 HES 229 CS BT".

15" Pine S.83°E. 39.0 ft. mkd: "7 HES 229 CS BT".

This corner lies in small grassy clearing about 100 ft. in diam.

10/31/69

*Vernon "Ray" Tracy
Jack Heritage & V. Perron
C. S. File No. 52/43
10/31/69
11/28/70*

45

Section Corner, Secs. 22 - 23 - 27 - 26.

Found - 1929 GLO Brass cap out of ground.

9" D. Fir, S.22°E., 21.7 ft. scribe visible. Ren. No. 15

Orig. 10" Yew, dead, S.33°W., 33.0 ft. scribe visible.

All other BT's down or stumps.

Renewal - Reset Brass Cap at Sec. cor. in mound of stone.

New BT's - 8" D. Fir, N.58°W., 8.9 ft. scribed T26S R2E S22 CS BT.

9" D. Fir, N.7°E., 46.2 ft. scribed T26S R2E S23 CS BT.

No trees available to the SW.

4/11/73

MARCH 71

**John M. Powell
J. Heritage
April 11, 1973
C.S. File 56/25**

46

Section corner for Secs. 3 and 2; and Secs. 34 and 35 of T.25 1/2 -2E.

Found - Original corner tree, 16" now 21" fir. Found good scars on NE, SE, SW and NW sides.

Orig. 14" now 18" fir with good scar bears N.64°E., 9.9 ft.

Orig. 8' x 8' x 5' boulder with "X BO" visible on NW face bears S.16°E., 5.3 ft.

Orig. 56" now 57" fir with good scar bears S.17°W., 51.5 ft.

Orig. 36" now 45" Pine with good scar bears N.14°W., 55.4 ft.

Set = Put metal tag on south side of corner tree marked:

"T25 1/2S 35 34 3 2 T26S R2E".

Set concrete nail in 8' x 8' x 5' boulder just above "X BO" bears S.16°E., 5.3 ft.

Note: Section corner is at bottom corner of steep clear cut.

10/28/81

**3/77
10N 75**

**Gregory Quibell
Deputy, Doug. Co.
Surveyors Office
Teresa Buley
Oct. 28, 1981
C.S. 61/29**

*Jan 28
1-77*