

Douglas County Surveyor's Record of  
Government Corners Renewed

T 26 S T. S. R 2 E R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Cor. Secs. 13, 14, 23, & 24

68

Found - 2" O.D. iron pipe, firmly set, projecting 12" above the ground in a deteriorated mound of stone with a 2½" brass cap properly stamped. GLO 1929

New - I rebuild a mound of stone, 72" dia. base to top of monument.  
10" D.Fir bears N.13°E., 25.0 ft. scribed "T26S R2W S13 BT"  
11" D.Fir bears S.10°E., 19.9 ft. scribed "T26S R2W S24 BT"  
9" D.Fir bears S.35°W., 15.4 ft. scribed "T26S R2W S23 BT"  
20" D.Fir bears N.3°W., 35.0 ft. scribed "T26S R2W S14 BT"  
I nail a brass washer stamped "PLS 1941" into the lower blaze of the new BTs and paint a 6" red band and BT face red and nail USFS "BEARING TREE" and "LAND SURVEY MONUMENT" signs to all BTs.

Kristian DeGroot,  
PLS 1941  
For: USFS  
Crew Les Fanning,  
Matt Dixon,  
& Aaron Fanning

March 1998 -

C.S. File 65/20-10 &  
11

1/4 Cor. Secs. 14 & 15

69

Found - 1" O.D. iron pipe, firmly set, projecting 10" above the ground with a 2½" brass cap properly stamped. GLO 1929

A root hole bears N.32°W., 16.5 ft. GLO 1929  
13" Fir bears S.65°E., 19.1 ft. with a healed blaze. GLO 1929  
New - I rebuild a mound of stone, 42" dia. base to top of monument.  
13" D.Fir bears N.9°30'W., 22.5 ft. scribed "WC ¼ S15 BT" with a brass washer stamped "PLS 1941" nailed in lower blaze.  
Paint a 6" red band and BT face red and nail USFS "BEARING TREE" and "LAND SURVEY MONUMENT" signs to all BTs.

Corner #3 HES 178

70

Found a 1" iron pipe with 2½" brass cap established by Tracy in 1969, properly marked, firmly set in concrete, projecting 12" above a 2-foot diameter mound of stone. Ren #29

From which the remaining original bearing tree: A 46" D.Fir, bears N.83°30'E., 76.4 feet (rec. N.83°15'E., 77.22 ft., Rase, 1916, and N.83°30'E. 75.0 ft., Dean, 1985), with a healed blaze.

From which the remains of the listing survey bearing tree: A root hole bears S. 47°30' E., 26.1 feet (rec. S.50°E., 29.70 ft., listing survey, 1913, & S.47°30'E., 26.1 ft., Dean, 1985), with downed 16" ponderosa pine alongside with healed blaze.

And from which the following bearing tree marked by Irving in 1945:

A 20" D.Fir stump, bears N.13°W., 15.3 feet (rec. N.17¼°W., 15.4 ft., Irving, 1945, and N.16°15'W. 15.3 ft., Dean, 1985), with healed blaze.

And from which the following bearing tree marked by Tracy in 1969:

A 16" D.Fir stump, bears N.54°45'W., 6.7 feet (rec. N.54°W., 7.1 ft. Tracy, 1969, & N.54°45'W., 6.7 ft. Dean, 1985), with healed blaze.

I mark new accessories for the corner:

A steel fence post, bears N.7°30'W. 3.4 ft. projecting 4 feet above the ground, with Forest Service "Property Boundary" sign attached.  
An 18" D.Fir, bears S.27°30'W., 29.0 feet, scribed "HES 178 3 BT" on a single blaze with a ¾" brass washer stamped "LS 2150" nailed to the face of the blaze.

A steel fence post, bears N.74°30'W., 3.2 ft., projecting 4 ft. above the ground, with Forest Service "Property Boundary" and "Land Survey Monument" signs attached.

A 6" diameter wood fence corner, bears N.3°30'W., 0.7 ft., 4 ft. above the ground, set in concrete.

Bearings are based on S.7°24'E., for the line between corners 2 & 3 & reported to the nearest 15 minutes. Tree measurements are to the center of the root crown. Tree diameters are at breast height.

Leonard E.  
Herzstein, USFS  
Chris Sturman,  
witness  
10/22/2001  
C.S. File  
65/40-8